

**138500400**

DATE 04/12/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 14 CORNER SOUTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 15  
NORTHEAST CORNER SECTION 22  
NORTHWEST CORNER SECTION 23**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A HEMLOCK POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T13SS14" ON NORTHEAST FACE, "R8WS23" ON SOUTHEAST FACE, "S22" ON SOUTHWEST FACE, AND "S15" ON NORTHWEST FACE, WITH 3 NOTCHES ON SOUTH EDGE AND 2 NOTCHES ON EAST EDGE, FROM WHICH A HEMLOCK 36" DIA BEARS N59°E, 53 LINKS (34.98 FEET), MARKED "T13SR8WS14BT"; FIR 18" DIA BEARS S65°E, 14 LINKS (9.24 FEET), MARKED "T13SR8WS23BT"; HEMLOCK 36" DIA BEARS S69°W, 42 LINKS (27.72 FEET), MARKED "T13SR8WS22BT"; HEMLOCK 32" DIA BEARS N6°W, 13 LINKS (8.58 FEET), MARKED "T13SR8WS15BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. THE SECTION CORNER DETERMINED AT RECORD DISTANCE FROM A HEMLOCK 38" DIA (GLO BT) BEARS N59°E, 53 LINKS (34.98 FEET), MARKED "W" ON EXPOSED FACE OF BLAZE; FIR 25" DIA (GLO BT) BEARS S56°E, 14 LINKS (9.24 FEET), MARKED "T S R8W" ON FACE OF EXPOSED BLAZE; HEMLOCK 45" DIA (GLO BT) BEARS S64°W, 42 LINKS (27.72 FEET), WITH A HEALED BLAZE; HEMLOCK 32" DIA (GLO BT) BEARS N6°W, 13 LINKS (8.58 FEET), MARKED "8W S15" ON FACE OF EXPOSED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W S15 S14 S22 S23 1960" FROM WHICH A HEMLOCK 24" DIA BEARS N73-1/2°E, 52 LINKS (34.32 FEET), MARKED "T13S R8W S14 BT"; HEMLOCK 6" DIA BEARS S42-1/4°E, 21 LINKS (13.86 FEET), MARKED "T13S R8W S23 BT"; HEMLOCK 6" DIA BEARS S83-1/4°W, 19 LINKS (12.54 FEET), MARKED "T13S R8W S22 BT"; HEMLOCK 12" DIA BEARS N37-1/2°W, 57 LINKS (37.62 FEET), MARKED "T13S R8W S15 BT".
- [03] LINCOLN COUNTY SURVEY NO. 10806 BY JAMES W. PROCHNAU, P.E., DATED JULY 24, 1972. FOUND 1965 BRONZE CAP.
- [04] BENTON COUNTY SURVEY NO. 10547 BY ROBERT ALAN COOK, P.L.S., DATED JUNE 8, 2012. FOUND 1960 BLM BRASS CAP. D. FIR 12" DIA BEARS S44°E, 13.6 FEET; D. FIR 22" DIA BEARS N80°W, 19.4 FEET. RAILROAD SPIKE BEARS S2°32'28"E, 96.17 FEET.
- [05] BENTON COUNTY SURVEY NO. 10974 BY ROBERT ALAN COOK, P.L.S., DATED JUNE 28, 2019, ALSO FILED AS LINCOLN COUNTY SURVEY NO. 20916. FOUND 1960 BLM BRASS CAP AND RAILROAD SPIKE RM FROM RECORD [04]. HEMLOCK STUMP REMAINS 30" DIA (GLO BT) BEARS N6°W, 13 LINKS (8.58 FEET); HEMLOCK STUMP REMAINS 40" DIA (GLO BT) BEARS N59°E, 53 LINKS (34.98 FEET); D. FIR 14" DIA BEARS S44°E, 13.6 FEET, HEALED FACE; D. FIR 24" DIA BEARS N80°W, 19.4 FEET, WITH HEALED FACE.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME