

**138600300**

DATE 03/18/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 23 CORNER SOUTHEAST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 24  
NORTHWEST CORNER SECTION 25  
NORTHEAST CORNER SECTION 26**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A MAPLE POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T13SS24" ON NORTHEAST FACE, "R8WS25" ON SOUTHEAST FACE, "S26" ON SOUTHEAST [sic.] FACE, AND "S23" ON NORTHWEST FACE, WITH 2 NOTCHES ON SOUTH EDGE AND 1 NOTCH ON EAST EDGE, FROM WHICH A CEDAR 20" DIA BEARS N33°E, 48 LINKS (31.68 FEET), MARKED "T13S R8W S24 BT"; FIR 36" DIA BEARS S24°E, 100 LINKS (66.00 FEET), MARKED "T13S R8W S25 BT"; MAPLE 6" DIA BEARS S19°W, 36 LINKS (23.76 FEET), MARKED "T13S R8W S26 BT"; MAPLE 6" DIA BEARS N44°W, 45 LINKS (29.70 FEET), MARKED "T13S R8W S23 BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. THE SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A CEDAR 30" DIA (GLO BT) BEARS N33°E, 48 LINKS (31.68 FEET), WITH A HEALED BLAZE; FIR SNAG 40" DIA (GLO BT) BEARS S24°E, 100 LINKS (66.00 FEET), WITH A HEALED BLAZE; MAPLE 36" DIA (GLO BT) BEARS N44°W, 45 LINKS (29.70 FEET), WITH A HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W S23 S24 S26 S25 1960" FROM WHICH A FIR 10" DIA BEARS N11°E, 42 LINKS (27.72 FEET), MARKED "T13S R8W S24 BT"; MAPLE 8" DIA BEARS S2°E, 34 LINKS (22.44 FEET), MARKED "T13S R8W S25 BT"; MAPLE 8" DIA BEARS S17°W, 30 LINKS (19.80 FEET), MARKED "T13S R8W S26 BT"; FIR 10" DIA BEARS N25°W, 86 LINKS (56.76 FEET), MARKED "T13S R8W S23 BT".
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY FRANK A. TUERS AND ROBERT L. AARSETH, CADASTRAL SURVEYORS, DATED AUGUST 9, 1979. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 8" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S23 S24 S26 S25 1960" FROM WHICH A CEDAR 40" DIA (GLO BT) BEARS N29-1/4°E, 43 LINKS (28.38 FEET), WITH SCRIBE MARKS "S R8 S2 BT" VISIBLE ON OPEN AND BURNED BLAZE; FIR SNAG 50" DIA (GLO BT) BEARS S26-3/4°E, 104 LINKS (68.64 FEET), WITH HEALED BLAZE; DECAYED MAPLE 44" DIA (GLO BT) BEARS N48-3/4°W, 41 LINKS (27.06 FEET), NO MARKS VISIBLE; FIR 16" DIA (BLM BT) BEARS N11°E, 40 LINKS (26.40 FEET), WITH HEALED BLAZE; MAPLE 11" DIA (BLM BT) BEARS S2°E, 31 LINKS (20.46 FEET), WITH HEALED BLAZE; MAPLE 11" DIA (BLM BT) BEARS S14-1/4°W, 28 LINKS (18.48 FEET), WITH HEALED BLAZE; FIR 18" DIA (BLM BT) BEARS N27-1/4°W, 82-1/2 LINKS (54.45 FEET), WITH HEALED BLAZE.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED DECEMBER 12, 1989. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 8" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S23 S24 S26 S25 1960" FROM WHICH A CEDAR 40" DIA (GLO BT) BEARS N29-1/4°E, 43 LINKS (28.38 FEET), WITH SCRIBE MARKS "T R8 S2 BT" VISIBLE ON BURNED FACE; FIR SNAG 48" DIA (GLO BT) BEARS S26-3/4°E, 100 LINKS (66.00 FEET), WITH HEALED BLAZE; MAPLE 36" DIA (GLO BT) BEARS N48-3/4°W, 41 LINKS (27.06 FEET), WITH HEALED BLAZE; FIR 19" DIA (BLM BT) BEARS N11°E, 40 LINKS (26.40 FEET), WITH HEALED BLAZE; MAPLE 13" DIA (BLM BT) BEARS S2°E, 31 LINKS (20.46 FEET), WITH HEALED BLAZE; MAPLE 12" DIA (BLM BT) BEARS S14-1/4°W, 28 LINKS (18.48 FEET), WITH HEALED BLAZE; FIR 19" DIA (BLM BT) BEARS N27-1/4°W, 82-1/2 LINKS (54.45 FEET), WITH HEALED BLAZE.
- [05] BENTON COUNTY SURVEY NO. 9149 BY HARVEY M. CHRISTENSEN, P.L.S., DATED OCTOBER 20, 1996. FOUND 1960 BLM 3" BRASS CAP MARKED "T13S R8W S23 S24 S26 S25 1960". B. MAPLE CLUMP 14" DIA (BLM BT) BEARS S20°W, 18.4 FEET, NO VISIBLE FACE; B. MAPLE CLUMP 14" DIA BEARS S22°E, 65.9 FEET, ROTTEN-OPEN FACE; D. FIR 19" DIA (BLM BT) BEARS N12°E, 26.3 FEET, HEALED FACE; D. FIR SNAG 48" DIA (GLO BT) BEARS S22°E, 65.9 FEET, ROTTEN-OPEN FACE; R. CEDAR 38" DIA (GLO BT) BEARS N30°E, 28.3 FEET, BURNED FACE; D. FIR 17" DIA (BLM BT) BEARS N27°W, 54.9 FEET, HEALED FACE.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME