

145400500

DATE 02/06/2013TOWNSHIP 14 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 9 CORNER SOUTHEAST
DONATION LAND CLAIM NONE CORNER NONE**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 10
NORTHWEST CORNER SECTION 15
NORTHEAST CORNER SECTION 16**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE NOTES BY KIMBALL WEBSTER, D.S., DATED FEBRUARY 2, 1853. SET POST FROM WHICH AN ASH 8" DIA BEARS S27°E, 31 LINKS (20.46 FEET); AN ASH 10" DIA BEARS S88°W, 29 LINKS (19.14 FEET); AN ASH 8" DIA BEARS N16°W, 55 LINKS (36.30 FEET); AN ASH 20" DIA BEARS N11°E, 58 LINKS (38.28 FEET).

[02] BENTON COUNTY ROAD NO. 332-1/2 FIELD NOTES (FIELD BOOK 16, PAGE 18) BY W.C. GALLOWAY, C.S., DATED FEBRUARY 17, 1914. SET 3/4" GALV. PIPE. 4 PRONG OAK 36" DIA BEARS N51°45'E, 1.687 CHAINS (111.34 FEET); AN ASH 9" DIA BEARS S0°50'W, 1.777 CHAINS (117.28 FEET); AN ASH 16" DIA BEARS S45°W, 2.074 CHAINS (136.88 FEET); AN ASH 15" DIA BEARS N88°40'W, 1.660 CHAINS (109.56 FEET).

[03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 76, BY W.C. GALLOWAY, C.S., DATED MARCH 21, 1914. SET 3/4" GALV. PIPE FROM STUMPS. 4 PRONG OAK 36" DIA (CSBT) BEARS N52°20'E, 1.687 CHAINS (111.34 FEET); AN ASH 9" DIA (CSBT) BEARS S0°50'W, 1.777 CHAINS (117.28 FEET); AN ASH 16" DIA (CSBT) BEARS S45°W, 2.071 CHAINS (136.69 FEET); AN ASH 15" DIA (CSBT) BEARS N88°40'W, 1.660 CHAINS (109.56 FEET).

[04] BENTON COUNTY CORNER RESTORATION NO. 2219. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

[05] BENTON COUNTY MAP NO. 14-5-00007 BY W.C. GALLOWAY, C.S., DATED AUGUST 10, 1918. 3/4" GALV. PIPE. PRONG OAK 36" DIA (CSBT) BEARS N51°45'E, 1.687 CHAINS (111.34 FEET); AN ASH 9" DIA (CSBT) BEARS S0°50'W, 1.777 CHAINS (117.28 FEET); AN ASH 16" DIA (CSBT) BEARS S45°W, 2.074 CHAINS (136.88 FEET); AN ASH 15" DIA (CSBT) BEARS N88°40'W, 1.660 CHAINS (109.56 FEET).

[06] BENTON COUNTY SURVEY NO. 1229 (OLD NO. 19) FIELD NOTES (FIELD BOOK 76, PAGE 14) BY W.C. GALLOWAY, C.S., DATED JUNE, 1934. OAK 14" DIA OF 50" (CSBT) BEARS N52°20'E, 1.687 CHAINS (111.34 FEET); AN ASH 8" DIA BEARS S11°30'W, 0.153 CHAINS (10.10 FEET); AN ASH 9" DIA (CSBT) BEARS S0°50'W, 1.777 CHAINS (117.28 FEET) STUMP; AN ASH 22" DIA (CSBT) BEARS S45°W, 2.071 CHAINS (136.69 FEET) REMARKED; AN ASH 7" DIA BEARS N19°18'W, 0.675 CHAINS (44.55 FEET).

[07] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 76, BY W.C. GALLOWAY, C.S., DATED JUNE, 1934. UPDATED PREVIOUS ENTRY TO ADD AN ASH 8" DIA (CSBT) BEARS S11°30'W, 0.153 CHAINS (10.10 FEET); AN ASH 7" DIA (CSBT) BEARS N19°18'W, 0.675 CHAINS (44.55 FEET); THE ASH 9" DIA (CSBT) NOW STUMP; THE ASH 16" DIA (CSBT) REMARKED; AND THE ASH 15" DIA (CSBT) NOW OUT.

[08] BENTON COUNTY CORNER RESTORATION NO. 2219. TRANSCRIBED FROM RECORD [07] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

[09] BENTON COUNTY MAP NO. 14-5-00016, NO DATE OR DRAFTSMAN GIVEN. 3/4" PIPE. OAK 36" DIA (CSBT) BEARS N52°20'E, 1.687 CHAINS (111.34 FEET); AN ASH 9" DIA (CSBT) BEARS S0°50'W, 1.777 CHAINS (117.28 FEET) STUMP; AN ASH 16" DIA (CSBT) BEARS S45°W, 2.071 CHAINS (136.69 FEET) REMARKED; AN ASH 15" DIA (CSBT) BEARS N88°40'W, 1.660 CHAINS (109.56 FEET) STUMP; AN ASH 8" DIA (CSBT) BEARS S11-1/2°W, 0.153 CHAINS (10.10 FEET); AN ASH 7" DIA (CSBT) BEARS N19°20'W, 0.675 CHAINS (44.55 FEET).

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

Road 332 1/2

Sec. cor. to sec's 8, 9, 16, 17. Sp. 14. 5.

Set stone 8" x 12" x 20"

Granite stone 8" x 8" x 16" four neck 20 ft.

N.W. cor. of track station Ch. bears S. 5' W. 44 1/2 cts.

Witnesses G. W. Bairn, C. W. Gray, Feb. 21, 1914

" 332 1/2

Section corner to sec's 9, 10, 15 & 16 Tp. 14-5

Set 3/4" galv. pipe set from stumps

4 prong oak 3 1/2" in dia. bears N. 52° 20' E. 1687 cts.

Ash 9"	S. 10° 50' W.	1777	" stump
" 16"	S. 15° 30' W.	1753	"
" 15"	S. 15° 16' W.	2076	" rem'd.
	N. 88° 40' W.	1660	" out. Jan 1914

Witness D. B. Farley

March 21, 1914.

Road 335

Sec. cor. to sec's 11, 12, 13 & 14 Tp. 13-5

Set 1 1/4" gal. pipe brick bats, found point of stake

Oak 8" in dia. bears N. 6° 46' E. 2. 87 cts. stl.

Pine 2 1/2" " S. 80° 30' E. 2. 87 "

Oak 3 1/2" " S. 53° 30' W. 3. 10 "

Pine 1 1/2" " N. 65° 30' W. 2. 80 "

Witness Peter Whitaker, C. W. Gray, D. B. Farley Feb. 26, 1914

" "

Sec. cor. set. sec's 13 & 14 Tp. 13-5

Set 3/4" pipe oak stump 30" S. 60° W. 6. 78 cts.

Oak 5 1/2" in dia. bears S. 9° 30' E. 10. 114 cts.

" " S. 41° 5' W. 6. 657 "

Witness Peter Whitaker, C. W. Gray, D. B. Farley Feb. 26, 1914

" "

Sec. cor. set. sec's 13, 14 23 & 24 Tp. 13-5

Set 1" pipe orig. cor. Pine stump S. 5 1/2° W. 1. 52 cts.

Pine 2 1/2" in dia. bears N. 58° E. 2. 28 cts. stl.

Oak 9" " East 1, 129 "

Witness Peter Whitaker, C. W. Gray, D. B. Farley Feb. 26, 1914

" "

N.E. cor. of Robert D. Grimsley D.S.P. #49. Tp. 13-5

Set 3/4" iron pin orig. cor. Stump hole N. W. stump S. W.

S. pine oak 12" in dia. bears N. 28° 30' W. 1. 449 cts.

Maple 18" " N. 79° W. 2. 759 "

Witness Peter Whitaker, C. W. Gray, D. B. Farley Feb. 27, 1914

Road # 335

S.E. corner of R. W. Russell D.L.C. # 69 Tp. 10-5. T. 4-11. W. 11.

Stone 6" x 6" x 7" set

Oak 3" in dia. S. 16° 40' W. 398 cts.

Witnesses D. B. Farley & A. M. Gray March 5, 1914.

CORNEL RESTORATION BOOK NO. 1

Survey

L. H. C. G.
and set 1
July 1914

Survey

Section-corner to sections 9, 10, 15, and 16, Twp. 14-5

2219

Reestablishment by ~~W. C. Galloway~~ *

March 21, 1914

Set 3/4" galvanized pipe, set from stumps
4 prong Oak 36" in diam bears N 52° 20' E
Ash 9" in diam bears S 0° 50' W
Ash 16" in diam bears S 45° W
Ash 15" in diam bears N 88° 40' W

1.687 chains
1.777 chains (stump)
2.071 chains
1.660 chains

Witness D. B. Farley

--- BENTON COUNTY SURVEYOR'S OFFICE, SEE FIELD BOOK NO. 16 PAGE 18 (CJL 6/17/92) ---

Replacement by W. C. Galloway
Ash 8" in diam bears S 11° 30' W
Ash 7" in diam bears N 19° 10' W
9" Ash now stump
16" Ash remarked
15" Ash now out

June, 1934
.153 chains
.675 chains

2614