

146860040

DATE 08/05/2007

TOWNSHIP 14 SOUTH, RANGE 06 WEST, WILLAMETTE MERIDIAN; SECTION 10 CORNER NONE
DONATION LAND CLAIM JAMES MC COY NO. 60 CORNER SOUTH-SOUTHEAST

COMMON CORNER(S):

NORTHWEST INTERIOR CORNER OF M. L. CHARLES DONATION LAND CLAIM NO. 61

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE JAMES MC COY DONATION LAND CLAIM (DLC) NO. 60 BY DENNIS HATHORN, D.S., DATED JANUARY 30, 1855. **SET POST FOR CORNER FROM WHICH A YEW 18" DIA BEARS N40°E, 15 LINKS (9.90 FEET); A FIR 18" DIA BEARS S50°E, 24 LINKS (15.84 FEET).**
- [02] GENERAL LAND OFFICE (GLO) NOTES OF THE M. L. CHARLES DONATION LAND CLAIM (DLC) NO. 61 BY DENNIS HATHORN, D.S., DATED JANUARY 31, 1855. **SET POST FOR INTERIOR CORNER FROM WHICH A YEW 18" DIA (GLO BT) BEARS N40°E, 15 LINKS (9.90 FEET); A FIR 18" DIA (GLO BT) BEARS S50°E, 24 LINKS (15.84 FEET).**
- [03] BENTON COUNTY SURVEY NO. 1191 (OLD NO. 336) FIELD NOTES (FIELD BOOK NO. 78, PAGES 11-12) BY W. C. GALLOWAY, C.S., DATED NOVEMBER 5, 1932. **SET 1" PIPE.**
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 199 BY W. C. GALLOWAY, C.S., DATED JULY 28, 1929. **SET PIPE.**
- [05] BENTON COUNTY CORNER RESTORATION NO. 2477. **TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [06] BENTON COUNTY MAP NO. 14-6-00005 BY BENTON COUNTY SURVEYOR'S OFFICE, NO DATE GIVEN. **3/4" PIPE. YEW 18" DIA BEARS N40°E, 0.15 CHAINS (9.90 FEET); FIR 18" DIA BEARS S50°E, 0.24 CHAINS (15.84 FEET).**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.
DATA ENTRY BY: CODY WHEELER, SURVEY TECH.

C.S. Road #1
W.C. Galloway
Roy S. Lec
1930

Most North N.E. Corner of Bushrod W. Wilson C1. 64 T. 12-5
Set a Stone 15 1/2" x 15" x 3"
Oak 40" in dia. bears N 4° 30' E. 153 chs.
" 20" " " 5 32' W. 136 "

"

N.W. Corner of Nicholas Owenby D.L.C. #62 T. 12 S. R. 5 W.
Found Orig. sandstone, set E. 5.03'
Referenced by 1/2" Iron pipe East Lts. 35.03 feet and 1" Iron rod W. Lts. 24.97'
Top of Marys Peak is S. 87° 57 1/2' W. (Bearing from O.S.C.)

Bellefontaine-Danvers
Road Survey
July 28, 1929
Witnesses
Gordon Bath
W.C. Galloway

Interior Cor. of James McCoy D.L.C. #60 T. 14 S. R. 6 W.
Set 3/4" pipe 12" under surface Found fir stump and log of oak.
Marked fir 20" in dia. bears S 73° E 4,800 chs.
" Oak 24" " " 5 53' W 5,880 "

Most South S.E. Cor. of James McCoy D.L.C. #60 T. 14 S. R. 6 W.
Set pipe

C.S. 286 in Road
Survey Summit Col. line
by W.C. Galloway
Witnesses
Geo. Streets
Geo. Gilbert
Jan. 1929

N.W. corner of Sec. 6 and N.W. corner of Township 11 S. R. 7 W.
Set 22 gauge gun barrel

S.W. snag has measure notch and 7
Sigs. N.W. blazed for stiffness tree
N.W. 97 E stamps in place, S.E. gone - log running N from
position

Marked Fir 7" in dia. N. 30° E. 14.5' = 220 chs.
" 5" " " N 88° E 7.4' = 112 "
" 6" " " S. 53 1/2° W. 9.3' = 141 "
" 6" " " N. 31 1/2° W. 8.07' = 122 "

C.S. #134 continued
by W.C. Galloway CS
March 3, 1933.
Witnesses
J.C. Smith, E. Ellorin
Wm. Coats

1/4 Sec. cor. between Secs. 17 & 20 T 10 S. R. 5 W.
Set 1/2" Galv. pipe Yew stake near.
Fir 12" now 36" in dia. N. 35° W. 94 chs. std. measure to cen.
" 60" " " N 82° W. 1055 "
" 26" " " S. 41° E. 161 "

Corner to secs. 17, 18, 19 & 20 T 10-5
Set 1/2" Galv. pipe. Found 2 stakes and Fir 30" x 8.702° W. 121 in trees gone.
Mtd. Fir 20" N. 5° W. .081 chs.

" 13" N. 51 1/2° E. 3.10 " std.
" 24" S. 32° E. 212 "
" 20" S. 78 1/2° W. 272 "

C.S. 134
March 4, 1933
Jos. C. Smith
Emile E. Lark in
Wm. Butolph

1/4 Section corner bet. Secs. 18 & 19 T 10-5
Set 3/8" black pipe and rock pile
Fir 20" in dia. bears N. 44 1/2° E. 2.94, rotten stump std.
" 18" " " S. 70° W. 3.29, Standing, good condition.
Marked " 22" " " N 42 1/4° E. 604
" 6" " " N 80 3/4° W. 428

Most south S. E. corner James McCoy DLc 60, Twp. 14 S., R. 6 W. 2477

Reestablishment by W. C. Galloway

July 28, 1929

Set Pipe

Witness Gordon Bath