

147240100

DATE 08/15/2019TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 32 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON NORTH LINE OF SECTION 5, TOWNSHIP 15 SOUTH, RANGE 7 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.**

[01] GENERAL LAND OFFICE (GLO) NOTES BY CHARLES M. COLLIER, D.S., DATED APRIL 24, 1893. *SET FIR POST 3 FEET LONG, 3" SQUARE, 24" IN GROUND MARKED "1/4S" ON NORTH FACE FROM WHICH A FIR 5" DIA BEARS N52°E, 137 LINKS (90.42 FEET), MARKED "1/4S BT"; FIR 5" DIA BEARS S64-1/2°E, 130 LINKS (85.80 FEET), MARKED "1/4S BT".*

[02] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. *POINT DETERMINED BY REFERENCE TO THE RECORD BEARING AND DISTANCE FROM THE ORIGINAL SOUTHEAST BEARING TREE. AT POINT FOR CORNER, SET AN IRON POST, 3 FEET LONG, 1" DIA, 28" IN THE GROUND WITH BRASS CAP MARKED "1/4 S32 1940" FROM WHICH A FIR 20" DIA (GLO BT) BEARS S64-1/2°E, 130 LINKS (85.80 FEET), MARKED "1/4S BT". I DESTROY ALL MARKS ON THIS ORIGINAL BEARING TREE. A FIR 24" DIA BEARS N40°E, 25 LINKS (16.50 FEET), MARKED "1/4 S32 BT". FIR 10" DIA BEARS N53°W, 59 LINKS (38.94 FEET), MARKED "1/4 S32 BT".*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME