

147340500

CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc
10/04/2010

CORNER NUMBER
147340500

STEP	HISTORY	RESTORATION
Form Prepared, DB	10/17/10	
Field Inspection, DB		
Finish index (count unit)	10/17/10	
Counter Index		
GIS Index Form		
Checked, DB		
Form Edited, DB		
Form Signed, DB		
Authorize Payment, DB		
Archive Digital Files		
Collect Documents		
PDF File		
Copy For Filming		
Scanned (pdf to laserfiche)		
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

COMMENTS:

DATE 10/17/2016

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 9 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):
NORTH 1/4 CORNER SECTION 16

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)
BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE
SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY CHARLES M. COLLIER, D.S., DATED MAY 12, 1893. SET POST 3 FEET LONG, 3"
SQUARE, **24" IN GROUND, MARKED "1/4S" ON NORTH FACE, FROM WHICH A FIR 48" DIA BEARS N6-1/4°E, 22 LINKS (14.52**
FEET) MARKED "1/4S BT"; A FIR 20" DIA BEARS S6-1/4°W, 59 LINKS (38.94 FEET) MARKED "1/4S BT".

[02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LARRY D. EVANS, CADASTRAL SURVEYOR, DATED MARCH 23, 1977. THE 1/4
SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR 55" DIA (GLO BT) BEARS N6-1/4°E, 22 LINKS
(14.52 FEET), WITH HEALED BLAZE; A ROOT HOLE (GLO BT) BEARS S6-1/4°W, 59 LINKS (38.94 FEET), WITH A DOWN FIR
ALONGSIDE, 36" DIA, WITH HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST 28" LONG, 2-1/2" DIA, 24" IN THE
GROUND, WITH BRASS CAP MARKED "T14S R7W S9 1/4 S16 1976" FROM WHICH A MAPLE 18" DIA BEARS S59-1/2°W, 44
LINKS (29.04 FEET) MARKED "1/4 S16 BT".

[03] BENTON COUNTY CORNER RESTORATION NO. 2546. TRANSCRIBED FROM RECORD [02] AND MAY CONTAIN ERRORS AND/OR
OMISSIONS.

[04] BENTON COUNTY SURVEY NO. 6325 BY ARNOLD BRUBAKER, P.L.S., DATED MARCH 23, 1977. FOUND BLM BRASS CAP "1976".
GREEN FIR 50" DIA (GLO BT) BEARS N6-1/4°E, 14.52 FEET; FIR WINDFALL 20" DIA (GLO BT) BEARS S6-1/4°W, 38.94 FEET;
MAPLE 16" DIA (BLM BT) BEARS S59-1/2°W, 29 FEET.

[05] BENTON COUNTY CORNER RESTORATION NO. 2545. TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR
OMISSIONS.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME


BENTON COUNTY SURVEYORS OFFICE · CORNER RESTORATION

2545

T. 14 S. R. 7 W. W. B. & M., BENTON COUNTY, OREGON
SECTION 9

REPORTED BY Arnold Brubaker
TITLE Survey or 992
DATE March 1977

The information shown hereon was taken from
the referenced county survey. Date: 7/30/90



● OFFICIAL CORNER FOUND

○ CORNER SET

1/4 CORNER COMMON TO SEC. 16 & 9
Blas CA-1

DESCRIBE

ADDITIONAL INFORMATION

P.S. # 6.3.25

LEGIBLE MARKS ON BEARING OBJECTS

(New)	(Original)	(Original)
Maple	Fir	Fir
16"	48"	20"
S 59 1/2° W	N 6 1/4° E	S 6 1/4° W
29'	14.52'	38.99'
BT TAG POSTED		

OVER