


**147400200**

DATE 07/02/2024TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 27 CORNER SOUTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 28  
NORTHEAST CORNER SECTION 33  
NORTHWEST CORNER SECTION 34**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY CHARLES M. COLLIER, D.S., DATED MAY 12, 1893. *SET STONE 16" X 8" X 7", 12" IN GROUND, MARKED WITH 3 NOTCHES ON EAST EDGE AND 1 NOTCH ON SOUTH EDGE, FROM WHICH A DEAD FIR 48" DIA BEARS N41-1/2°E, 54 LINKS (35.64 FEET), MARKED "T14S R7W S27 BT"; DEAD FIR 20" DIA BEARS S75-1/2°E, 76 LINKS (50.16 FEET), MARKED "T14S R7W S34 BT"; DEAD FIR 48" DIA BEARS S51-1/2°W, 235 LINKS (155.10 FEET), MARKED "T14S R7W S33 BT"; DEAD FIR 48" DIA BEARS N55-1/2°W, 71 LINKS (46.86 FEET), MARKED "T14S R7W S28 BT".*
- [02] BUREAU OF LAND MANAGEMENT REPORT ON CORNERS OF THE CADASTRAL SURVEY GRID BY TOM MAKEY, FORESTER, DATE APPEARS TO BE JUNE 15, 1962. *ROUND WOODEN POST. BURNED 40" DIA TREE, 15' HIGH, SCRIBED "T14S R7W S27". CRUISERS MARKS ON NEARBY TREES.*
- [03] BENTON COUNTY SURVEY NO. 6489 BY ARNOLD BRUBAKER, P.L.S., DATED SEPTEMBER 28, 1977, AND REVISED AS SURVEY NO. 6489-A DATED JANUARY 24, 1978. *FOUND STONE 7" X 8" X 16" WITH 3 NOTCHES ON EAST SIDE AND 1 NOTCH ON SOUTH SIDE. STONE IS AGAINST THE BASE OF A D. FIR 26" DIA ON WHICH I PLACED A BLM TAG. SAID TREE IS S15°E, 2 FEET FROM STONE. FOUND D. FIR 48" DIA (GLO BT) BEARS N41-1/2°E, 35.64 FEET, VISIBLE SCRIBING; D. FIR 20" DIA (GLO BT) BEARS S75-1/2°E, 48 FEET; D. FIR 48" DIA (GLO BT) BEARS S51-1/2°W, 123.1 FEET; D. FIR 48" DIA (GLO BT) BEARS N55-1/2°W, 45 FEET. BEARINGS ALL CHECK REAL GOOD.*
- [04] BUREAU OF LAND MANAGEMENT LOCAL RECORD CORNERS OF THE CADASTRAL SURVEY GRID BY N. B. WOOD, JR, ENG. TECH., DATED MARCH 3, 1978. *REPORT OF INFORMATION ON RECORD [03].*
- [05] BUREAU OF LAND MANAGEMENT LOCAL RECORD CORNERS OF THE CADASTRAL SURVEY GRID BY N. B. WOOD, JR, CET, DATED FEBRUARY 25, 1986. *FOUND ROCK 7" X 8" X 16". ROTTEN D. FIR SNAG 48" DIA BEARS N41-1/2°E, 35.7 FEET WITH SCRIBING "R7W S27". ROTTEN SNAG 48" DIA BEARS S51-1/2°W, 123.1 FEET. ROTTEN SNAG 48" DIA BEARS N55-1/2°W, 45 FEET. D. FIR 26" DIA BEARS S15°E, 2.0 FEET. LOCATION TAGS POSTED ON: D. FIR 28" DIA BEARS S86°E, 19.0 FEET; D. FIR 10" DIA BEARS N78°W, 24.0 FEET; D. FIR 20" DIA BEARS N19°E, 6.4 FEET. CORNER STONE IS WEDGED IN BARK OF 26" D.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME



REPORT ON

CORNERS OF THE CADASTRAL SURVEY GRID

T. 14S R. 7W Sec. 27 Mer., Oregon State.



SYMBOLS

- ◆ Official corner found
- ◇ Corner found, authenticity doubtful
- Corner searched for and not found

DESCRIPTION OF CORNER MONUMENT.

Round wooden post.

DESCRIPTION OF BEARING TREES, MOUND OF STONE, ETC

1 BT - 40' Burned ~~at~~ tree 15' high.  
 Scribed as follows - T14S R7W S27  
 Cruisers Marks on nearby trees.

DESCRIPTION OF LOCATION TO ENABLE RECOVERY BY OTHERS

Corner is marked (not punched) c:  
 photos ABS 8 - 849

Tom Mabeey  
 Reported by Paul E. Lindenberg

6-15-62

Reported by

F-9180-A  
Jan. 1965

LOCAL RECORD  
CORNERS OF THE CADASTRAL SURVEY GRID

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

T. 14 S. R. 7 W., W. 1/2 Mer., OR State



SYMBOLS

- ◆ Official corner found
- ◇ Probable corner found, authenticity doubtful.
- Corner searched for and not found.

Reported by A. B. Wood  
THE Eng. Tech.  
DATE 3/3/78

MARKS:

Sto. Corner common to Secs. 29, 27, 34 & 37 is a mound of stone,  
tree/rock, fire pit, iron pipe, size 7" x 8" x 16"

ADDITIONAL INFORMATION

Reported by Starker  
Forestry 1977  
Benton Co. File NO.  
06489


rd STONE 7' x 5 1/2" with 3 notches  
ONE AND 1 notch on 3 sides  
STONE IS AGAINST THE BASE OF A  
26" D. FIR ON WHICH IS PLACED A BLM  
TAG 9/10/77 9439401 28 145  
SAID TREE IS 5 FT. 1" from stone

rd DTS 48' 0" E 45' 0" E 35 49'  
VISIBLE TO BANG  
20' 0" E 15 54' 0" (50 16') 48 11  
48' 0" E 15 54' 0" (125 1) 123 1 11  
48' 0" E 15 54' 0" (24 86) 45 61  
NOTE BEAR 265 ... REAL GOOD

LOCAL RECORD  
 CORNERS OF THE CADASTRAL SURVEY GRID

DEPARTMENT OF THE INTERIOR  
 BUREAU OF LAND MANAGEMENT

T. 145 R. 24, W Mer., 02 State



SYMBOLS

- ◆ Official corner found
- ◇ Probable corner found, authenticity doubtful.
- Corner searched for and not found.

Reported by G. B. Woolley  
 Title CET  
 Date 2/25/86

Sec. 33 Corner common to Secs. 27, 28, 33 & 34 is a mound of stone, tree/rock fire pit, iron pipe, size 7x8x16

LEGIBLE MARKS ON BEARING OBJECTS



KIND	Rotten snag	Rotten snag	Rotten snag	DF
SIZE	48	48"	48"	26
BEARING	N91°40'	S51°40'W	N55°40'W	S15°E
DISTANCE	75.2	127.1	95'	2'
BY TAG POSTED	Loc. Tag			8+ tag

ADDITIONAL INFORMATION

Location tags posted  
 DF 28" S86°E 190  
 DF 10" N78°W 240  
 DF 20" N19°E 69  
 Gas. stone is wedged in Bark of 26" D

DSC 9600-1 (March 1978)

(OVER)