

D. NEVIN

1994

180 13

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 14 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| | <p>A fir stump, 42 ins. diam., bears N. 68½° E., 104 lks. dist., with healed blaze.</p> <p>A fir, 35 ins. diam., bears N. 53° W., 87 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Evans</p> <p>A fir, 12 ins. diam., bears N. 38° E., 30½ lks. dist., with healed blaze. (Record, N. 39° E.)</p> <p>A fir, 20 ins. diam., bears S. 64 ¾° E., 73½ lks. dist., with healed blaze. (Record, S. 63½° E.)</p> <p>The corner is located in NE. cor. of logged area and fence corner with down fences extending S. and E.</p> |
| | <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 0° 25' 00" E., bet. secs. 9 and 10.</p> <p>Ascend over SW. slope, through moderate timber and undergrowth.</p> |
| 5.55 | Spur, slopes S. 45° E.; continue ascending over broken E. slope. |
| 40.180 | Point for the X sec. cor. of secs. 9 and 10, at proportionate distance, there is no remaining evidence of the original corner. |
| | <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¼ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 14 S R 7 W</p> <p style="text-align: center;"> X</p> <p style="text-align: center;">S 9 S 10</p> <p style="text-align: center;"> 1994</p> |
| | <p>from which</p> <p>A fir, 12 ins. diam., bears N. 78 ¾° E., 33 lks. dist., mkd. X S10 BT.</p> <p>A fir, 15 ins. diam., bears S. 46° W., 15 lks. dist., mkd. X S9 BT.</p> <p>Deposit a white "DREP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p> |
| 43.545 | <p>The remains of an original line tree, a fir stump, 52 ins. diam., with two notches on S. face. This now becomes an angle point.</p> <p>Drive an iron rod, 24 ins. long, 5/8 in. diam., 20 ins. into the center of stump, with aluminum cap mkd.</p> |

147400543

181 14

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 14 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| | AP S 9 S 10 1994 |
| | from which |
| | A fir, 20 ins. diam., bears S. 74½° E., 29½ lks. dist., mkd. AP S10 BT. |
| | A fir, 9 ins. diam., bears N. 59° W., 26 lks. dist., mkd. AP S9 BT. |
| | _____ |
| | N. 0° 23' 00" E., beginning new measurement. |
| | Ascend over SE. slope. |
| 4.85 | Ridge, bears N. 40° E. and S. 40° W.; desc. over broken NW. slope. |
| 19.30 | Spur, slopes W.; continue descending over broken NW. slope. |
| 35.10 | Spur, slopes W.; continue descending over NW. slope. |
| 36.665 | The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. |
| | T 14 S R 7 W S S 3 _____ S 9 S 10 1976 |
| | from which the remains of the original bearing trees |
| | A fir stump, 60 ins. diam., bears N. 63½° E., 85 lks. dist., with healed blaze. |
| | A fir, 50 ins. diam., bears S. 35° E., 43 lks. dist., with healed double blaze. |
| | A decayed fir stump, size indeterminate, bears S. 26° W., 24 lks. dist., with scribe marks R / and other illegible scribe marks visible on decayed blaze. |
| | A root hole, bears N. 45° W., 36 lks. dist., alongside of which is a down fir, 45 ins. diam., with healed blaze. |
| | and bearing trees mkd. by Evans |
| | A fir, 12 ins. diam., bears N. 35° E., 52½ lks. dist., with healed blaze. |
| | A fir, 37 ins. diam., bears S. 57½° W., 48½ lks. dist., with healed blaze. |
| | and a new bearing tree |
| | A fir, 8 ins. diam., bears N. 75 3/4° W., 53½ lks. dist., mkd. T14S R7W S4 BT. |