

147440700

DATE 11/15/2016TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 3 CORNER NORTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON SOUTH LINE OF SECTION 34, TOWNSHIP 13 SOUTH, RANGE 7 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED SEPTEMBER 10, 1856. *SET POST FROM WHICH A MAPLE 10" DIA BEARS S72°W, 34 LINKS (22.44 FEET); A MAPLE 18" DIA BEARS S70°E, 43 LINKS (28.38 FEET). A LINE TREE FIR 24" DIA BEARS EAST, 1.69 CHAINS (111.54 FEET). A LINE TREE FIR 36" DIA BEARS EAST, 1.77 CHAINS (116.82 FEET). A LINE TREE CEDAR 30" DIA BEARS WEST, 7.57 CHAINS (499.62 FEET).*
- [02] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 25, 1891. *A POST 4" SQUARE FIRMLY SET IN THE GROUND MARKED "1/4S" ON SOUTH FACE FROM WHICH A MAPLE 10" DIA (GLO BT) BEARS S72°W, 34 LINKS (22.44 FEET) MARKED "1/4S BT"; A MAPLE 18" DIA (GLO BT) BEARS S70°E, 43 LINKS (28.38 FEET), MARKS OVERGROWN. A LINE TREE FIR 36" DIA (GLO) BEARS EAST, 1.70 CHAINS (112.20 FEET) WITH 2 NOTCHES ON EAST AND WEST SIDES. A LINE TREE FIR 36" DIA (GLO) BEARS EAST, 1.78 CHAINS (117.48 FEET) WITH 2 NOTCHES ON EAST AND WEST SIDES. A LINE TREE CEDAR 30" DIA (GLO) BEARS WEST, 7.57 CHAINS (499.62 FEET) WITH 2 NOTCHES ON EAST AND WEST SIDES.*
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED FEBRUARY 25, 2004. *POINT FOR THE STANDARD 1/4 SECTION CORNER OF SECTION 3 ONLY, AT PROPORTIONATE DISTANCE, THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER. SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T14S R7W 1/4 S3 SC 2003" FROM WHICH A FIR 13" DIA BEARS S73-1/2°E, 24.5 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S3 SC BT"; A FIR 16" DIA BEARS S63°W, 11.4 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S3 SC BT". DEPOSIT A MAGNET IN A WHITE PLASTIC CASE AT THE BASE OF THE STAINLESS STEEL POST.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME