

147500400

CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc
10/04/2010

CORNER NUMBER
147500400

STEP	HISTORY	RESTORATION
Form Prepared, DB		
Field Inspection, DB	11/23/16	
Finish index (count unit)	11/23/16	
Counter Index		
GIS Index Form		
Checked, DB		
Form Edited, DB		
Form Signed, DB		
Authorize Payment, DB		
Archive Digital Files		
Collect Documents		
PDF File		
Copy For Filming		
Scanned (pdf to laserfiche)		
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

COMMENTS:

DATE 11/23/2016

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 14 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 15
NORTHEAST CORNER SECTION 22
NORTHWEST CORNER SECTION 23**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY CHARLES M. COLLIER, D.S., DATED MAY 12, 1893. SET A POST 4 FEET LONG, 4" SQUARE, 24" IN GROUND, MARKED "T14S S14" ON NORTHEAST FACE, "R7W S23" ON SOUTHEAST FACE, "S22" ON SOUTHWEST FACE, AND "S15" ON NORTHWEST FACE, WITH 2 NOTCHES ON EAST EDGE AND 3 NOTCHES ON SOUTH EDGE, FROM WHICH A FIR 18" DIA BEARS N11-1/2°E, 24 LINKS (15.84 FEET) MARKED "T14S R7W S14 BT"; A FIR 16" DIA BEARS S17-3/4°E, 16 LINKS (10.56 FEET) MARKED "T14S R7W S23 BT"; A FIR 12" DIA BEARS S64-1/4°W, 11 LINKS (7.26 FEET) MARKED "T14S R7W S22 BT"; A FIR 30" DIA BEARS N72°W, 34 LINKS (22.44 FEET) MARKED "T14S R7W S15 BT".
- [02] GENERAL LAND OFFICE (GLO) NOTES BY J. C. LEWIS, SPECIAL INSPECTOR, DATED MAY 29, 1893. FIND A FIR POST 4" SQUARE, SET FIRMLY IN GROUND, MARKED "T14S S14" ON NORTHEAST, "R7W S23" ON SOUTHEAST, "S22" ON SOUTHWEST, AND "S15" ON NORTHWEST, WITH 3 NOTCHES ON SOUTH CORNER AND 2 NOTCHES ON EAST CORNER, FROM WHICH A FIR 20" DIA (GLO BT) BEARS N12°E, 24 LINKS (15.84 FEET) MARKED "T14S R7W S14 BT"; A FIR 18" DIA (GLO BT) BEARS S18°E, 16 LINKS (10.56 FEET) MARKED "T14S R7W S23 BT"; A FIR 12" DIA (GLO BT) BEARS S64-1/2°W, 12 LINKS (7.92 FEET) MARKED "T14S R7W S22 BT"; A FIR 36" DIA (GLO BT) BEARS N72°W, 35 LINKS (23.10 FEET) MARKED "T14S R7W S15 BT".
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LARRY D. EVANS, CADASTRAL SURVEYOR, DATED MARCH 23, 1977. THE SECTION CORNER MONUMENTED WITH AN IRON PIPE, 1-1/2" DIA, FIRMLY SET, PROJECTING 24" ABOVE GROUND, FROM WHICH A FIR STUMP 28" DIA (GLO BT) BEARS N11-1/2°E, 24 LINKS (15.84 FEET), WITH SCRIBE MARKS "BT" VISIBLE ON OPEN BLAZE; A ROOT HOLE (GLO BT) BEARS S17-3/4°E, 16 LINKS (10.56 FEET); A ROOT HOLE (GLO BT) BEARS S64-1/4°W, 11 LINKS (7.26 FEET), A FIR STUMP 44" DIA (GLO BT) BEARS N72°W, 34 LINKS (22.44 FEET), WITH HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T14S R7W S15 S14 S22 S23 1977" FROM WHICH A FIR 4" DIA BEARS N64-1/2°E, 30-1/2 LINKS (20.13 FEET) MARKED "X BT"; A FIR 6" DIA BEARS S2-1/2°E, 24-1/2 LINKS (16.17 FEET) MARKED "T14S R7W S23 BT"; A FIR 4" DIA BEARS S69°W, 41-1/2 LINKS (27.39 FEET) MARKED "X BT"; A FIR 7" DIA BEARS N58°W, 21-1/2 LINKS (14.19 FEET) MARKED "T14S R7W S15 BT". RESET IRON PIPE ALONGSIDE IRON POST.
- [04] BENTON COUNTY CORNER RESTORATION NO. 2564. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY SURVEY NO. 8445 BY THEODORE JAMES LANGTON, P.L.S., DATED AUGUST 9, 1990. FOUND BLM BRASS CAP MARKED "T14S R7W S15 S14 S22 S23 1977" ON 2-1/2" INNER DIAMETER PIPE IN SALAL ON A SOUTHWEST SLOPE. FOUND D. FIR STUMP 28" DIA (GLO BT) BEARS N11°30'E, 24 LINKS (15.84 FEET) WITH SCRIBING VISIBLE ON AN OPEN FACE; D. FIR STUMP 44" DIA (GLO BT) BEARS N72°W, 34 LINKS (22.44 FEET), HEALED FACE; D. FIR 7" DIA (BLM BT) BEARS N64°30'E, 30.5 LINKS (20.13 FEET), HEALED FACE; D. FIR WINDFALL 6" DIA (BLM BT) BEARS S2°30'E, 24.5 LINKS (16.17 FEET); D. FIR 9" DIA (BLM BT) BEARS S69°W, 41.5 LINKS (27.39 FEET), HEALED FACE; D. FIR 10" DIA (BLM BT) BEARS N58°W, 21.5 LINKS (14.19 FEET), HEALED FACE.
- [06] BENTON COUNTY SURVEY NO. 8912 BY THEODORE JAMES LANGTON, P.L.S., DATED NOVEMBER 29, 1994. FOUND BLM BRASS CAP MARKED "T14S R7W S15 S14 S22 S23 1977" ON 2-1/2" INNER DIAMETER PIPE IN SALAL ON A SOUTHWEST SLOPE. FOUND D. FIR STUMP 28" DIA (GLO BT) BEARS N11°30'E, 24 LINKS (15.84 FEET) WITH SCRIBING VISIBLE ON AN OPEN FACE; D. FIR STUMP 44" DIA (GLO BT) BEARS N72°W, 34 LINKS (22.44 FEET), HEALED FACE; D. FIR 7" DIA (BLM BT) BEARS N64°30'E, 30.5 LINKS (20.13 FEET), HEALED FACE; D. FIR WINDFALL 6" DIA (BLM BT) BEARS S2°30'E, 24.5 LINKS (16.17 FEET); D. FIR 9" DIA (BLM BT) BEARS S69°W, 41.5 LINKS (27.39 FEET), HEALED FACE; D. FIR 10" DIA (BLM BT) BEARS N58°W, 21.5 LINKS (14.19 FEET), HEALED FACE.
- [07] BENTON COUNTY SURVEY NO. 9522 BY JIM S. PETERSON, P.L.S., DATED DECEMBER 27, 1999. FOUND 1977 3-1/4" BRASS CAP. FOUND FIR 14" DIA (BLM BT) BEARS N58°W, 21-1/2 LINKS (14.19 FEET), HEALED FACE; FIR STUMP 44" DIA (GLO BT) BEARS N72°W, 34 LINKS (22.44 FEET), AXE WORK; FIR SNAG 10" DIA (BLM BT) BEARS S69°W, 41-1/2 LINKS (27.39 FEET), HEALED FACE; FIR STUMP 28" DIA (GLO BT) BEARS N11-1/2°E, 24 LINKS (15.84 FEET), SCRIBING VISIBLE; FIR 10" DIA (BLM BT) BEARS N64-1/2°E, 30-1/2 LINKS (20.13 FEET), HEALED FACE; FIR DOWN 4" DIA (BLM BT) BEARS S2-1/2°E, 24-1/2 LINKS (16.17 FEET), NO MARKS VISIBLE. CORNER LIES ON STEEP SOUTH SLOPE, 100' NORTH OF CREEK.
- [08] BENTON COUNTY SURVEY NO. 9892 BY JIM S. PETERSON, P.L.S., DATED DECEMBER 27, 1999. CONTAINS THE SAME INFORMATION AS C.S. 9522.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821**RESEARCH BY:** DAVID L. MALONE, P.L.S.**DATA ENTRY BY:** SAME

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

2564


T 14 S, R 7 W, W. B. & M., BENTON COUNTY, OREGON

REPORTED BY EVANS

TITLE CADASTRAL SURVEYOR

SECTION 14

DATE MARCH 1977



● OFFICIAL CORNER FOUND

○ CORNER SET

Sect. COMMON TO SEC. 14 15 22 & 23
 IS iron post 2 1/2" x 28" w/ brass cap
 DESCRIBE

ADDITIONAL INFORMATION

28" fir stump - N 11 1/2° E 24 IKs w/ BT" on open blaze
root hole - S. 17 3/4° E 16 IKs
root hole - S. 64 1/4° W 11 IKs.
44" fir stump - N 72° W, 34 IKs w/ heeled blaze
set iron pipe (1 1/2" dia.) along side of iron post

SEE PG. 12 OF THE BLM FIELD NOTES IN THE T14S
R7W FILE IN THE CORNER RESTORATION COR-
RESPONDENCE FILE DRAWER (CJL 7/23/90).

OVER

LEGIBLE MARKS ON BEARING OBJECTS

" x BT"	T14S R7W S23 BT	" x BT"	T14S R7W S15 BT
KIND FIR	FIR	FIR	FIR
SIZE 4	6"	4"	7"
BEARING N 64 1/2° E	S 2 1/2° E	S 69° W	N 58° W
DISTANCE 30 1/2 IKs	24 1/2 IKs	41 1/2 IKs	21 1/2 IKs
BT TAG POSTED			