

DATE 12/14/2011

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 2 CORNER NORTHWEST
DONATION LAND CLAIM NONE CORNER N/A

COMMON CORNER(S):

NORTHEAST CORNER OF SECTION 3, T. 14 S., R. 7 W.
POINT ON SOUTH LINE OF SECTION 35, T. 13 S., R. 7 W.

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED JUNE 6, 1856. SET STANDARD CORNER FROM WHICH A MAPLE 20" DIA BEARS S40°W, 10 LINKS (6.60 FEET); A HEMLOCK 20" DIA BEARS S62°E, 39 LINKS (25.74 FEET).
- [02] GLO NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 21, 1891. FOUND POST 4" SQUARE FIRMLY SET MARKED "S2SC" ON SOUTHEAST FACE AND "R7WT14SS3" ON SOUTHWEST FACE WITH 2 NOTCHES ON EAST EDGE FROM WHICH A MAPLE 20" DIA BEARS S40°W, 10 LINKS (6.60 FEET), MARKS OVERGROWN; A HEMLOCK 20" DIA BEARS S62°E, 39 LINKS (25.74 FEET), MARKS OVERGROWN.
- [03] GLO NOTES BY CHARLES M. COLLIER, D.S., DATED MAY 2, 1893. FOUND POST 5" SQUARE FIRMLY SET MARKED "S2SC" ON SOUTHEAST FACE AND "T14SR7WS3" ON SOUTHWEST FACE WITH 2 NOTCHES ON EAST EDGE AND 4 NOTCHES ON WEST EDGE FROM WHICH A MAPLE 20" DIA BEARS S40°W, 10 LINKS (6.60 FEET) MARKED "T14SR7WS3BT"; A HEMLOCK 20" DIA BEARS S62°E, 39 LINKS (25.74 FEET) MARKED "T14SR7WS2BT".
- [04] BENTON COUNTY CORNER RESTORATION NO. 2495 BY ARTHUR E. MOSHER, P.L.S., DATED APRIL 4, 1974. FOUND MAPLE 27" DIA BEARS S40°W, 10 LINKS (6.60 FEET) SCRIBES VISIBLE. SET 5/8" X 30" IRON ROD FROM WHICH A DOUGLAS FIR 9" DIA BEARS S44°E, 17.4 FEET MARKED "T14SR7WS2BT"; A DOUGLAS FIR 10" DIA BEARS S59°W, 23.2 FEET MARKED "T14SR7WS3BT".
- [05] BUREAU OF LAND MANAGEMENT NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED JUNE 17, 2003 THRU FEBRUARY 25, 2004. FOUND 5/8" IRON ROD PROJECTING 6" ABOVE GROUND FROM WHICH A MAPLE 28" DIA BEARS S40°W, 7.2 FEET WITH AXE MARKS VISIBLE ON OPEN BLAZE; A FIR 21" DIA BEARS S45°E, 18.1 FEET WITH A HEALED BLAZE; A FIR 19" DIA BEARS S63°W, 23.5 FEET WITH A HEALED BLAZE. SET A STAINLESS STEEL POST 28" LONG, 2-1/2" DIA, 22" IN THE GROUND WITH BRASS CAP OVER IRON ROD.

NOTES:

THIS IS A MICROSOFT WORD 2003 DOCUMENT NAMED "47500700" CREATED FROM A BOILER PLATE DOCUMENT NAMED "CORNER".

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME