

DATE 12/13/2011

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 2 CORNER NORTH 1/4
DONATION LAND CLAIM NONE CORNER N/A

COMMON CORNER(S):

POINT ON SOUTH LINE OF SECTION 35, T. 13 S., R. 7 W.

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) BY DENNIS HATHORN, D.S., DATED JUNE 6, 1856. SET STANDARD 1/4 SECTION POST FROM WHICH A FIR 24" DIA BEARS S60°W, 26 LINKS (17.16 FEET); A FIR 12" DIA BEARS S20°E, 22 LINKS (14.52 FEET).

[02] GLO NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 21, 1891. FOUND A POST 4" SQUARE FIRMLY SET IN THE GROUND MARKED "1/4S" ON SOUTH FACE FROM WHICH A FIR 24" DIA BEARS S60°W, 26 LINKS (17.16 FEET) MARKED "1/4SBT"; A FIR 12" DIA BEARS S20°E, 22 LINKS (14.52 FEET) MARKED "1/4SBT".

[03] BENTON COUNTY SURVEY NO. 4423 BY LEO J. MARTIN, P.L.S., DATED MARCH, 1967. SET 3/4" X 3/8" GALVANIZED IRON PIPE BY PROPORTIONATE MEASUREMENT. SCRIBED A FIR 44" DIA BEARS S64°E, 67.0 FEET MARKED "1/4S2BT".

NOTES:

THIS IS A MICROSOFT WORD 2003 DOCUMENT NAMED "47540700" CREATED FROM A BOILER PLATE DOCUMENT NAMED "CORNER".

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE

ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821

RESEARCH BY: DAVID L. MALONE, P.L.S.

DATA ENTRY BY: SAME