

**147600540**

**CORNER FILE TRACKING**

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc  
10/04/2010

<b>CORNER NUMBER</b>
<b>147600540</b>

<b>STEP</b>	<b>HISTORY</b>	<b>RESTORATION</b>
Form Prepared, DB	11/15/10	
Field Inspection, DB		
Finish index (count unit)	11/15/10	
Counter Index		
GIS Index Form		
Checked, DB		
Form Edited, DB		
Form Signed, DB		
Authorize Payment, DB		
Archive Digital Files		
Collect Documents		
PDF File		
Copy For Filming		
Scanned (pdf to laserfiche)		
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

**COMMENTS:**

DATE 11/15/2016

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 11 CORNER EAST 1/4  
DONATION LAND CLAIM N/A CORNER N/A

**COMMON CORNER(S):**  
WEST 1/4 CORNER SECTION 12

**RECORDS (INFORMATION IN BOLD /ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY CHARLES M. COLLIER, D.S., DATED MAY 12, 1893. SET A POST 3 FEET LONG, 3" SQUARE, **24" IN GROUND MARKED "1/4S" ON WEST FACE FROM WHICH A FIR 15" DIA BEARS S71°20'W, 293 LINKS (193.38 FEET) MARKED "1/4S BT"; A DEAD FIR 30" DIA BEARS N49-1/2°E, 116 LINKS (76.56 FEET) MARKED "1/4S BT"**.
- [02] BENTON COUNTY SURVEY NO. 9698 BY N. WOOD AND R. SMITH, A BLM ADMINISTRATIVE SURVEY DATED SUMMER, 1972. SET **3/4" PIPE BY PROPORTION. FIR 9" DIA BEARS N85°W, 4.6 FEET; FIR 12" DIA BEARS S63°E, 8.8 FEET.**
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY DANNY J. NEVIN, CADASTRAL SURVEYOR, DATED OCTOBER 19, 1994. POINT FOR THE 1/4 SECTION CORNER AT PROPORTIONATE DISTANCE. THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER. SET A STAINLESS STEEL POST, **28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T14S R7W 1/4 S11 S12 1993" FROM WHICH A FIR 16" DIA BEARS S62-3/4°E, 14-1/2 LINKS (8.70 FEET), MARKED "1/4 S12 BT"; A FIR 11" DIA BEARS N82°W, 7-1/2 LINKS (4.95 FEET), MARKED "1/4 S11 BT"**. FROM THIS POINT, A POINT UNOFFICIALLY ESTABLISHED BY A BLM ADMINISTRATIVE SURVEY IN 1972, BEARS S80°05'00"W, 0.003 CHAINS (0.20 FEET), MONUMENTED WITH AN IRON PIPE, 3/4" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND. REMOVE THE IRON PIPE AND DEPOSIT INSIDE STAINLESS STEEL POST.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME