

147640700

DATE 05/05/2016TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 1 CORNER NORTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON SOUTH LINE OF SECTION 36, TOWNSHIP 13 SOUTH, RANGE 7 WEST

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED JUNE 9, 1856. SET POST FROM WHICH A FIR 36" DIA BEARS S70°E, 25 LINKS (16.50 FEET); A FIR 12" DIA BEARS S60°W, 36 LINKS (23.76 FEET).

[02] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 23, 1891. A POINT FROM WHICH A FIR 36" DIA (GLO BT) BEARS S70°E, 25 LINKS (16.50 FEET) MARKED "1/4S BT"; A FIR 12" DIA (GLO BT) BEARS S60°W, 36 LINKS (23.76 FEET) MARKED "1/4S BT". AS THE ORIGINAL POST HAS ROTTED AWAY I SET A NEW POST 3 FEET LONG, 3" SQUARE, 24" IN GROUND MARKED "1/4S SC" ON SOUTH FACE.

[03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 31, 1991. CORNER PERPETUATED BY AN UNOFFICIAL BLM ADMINISTRATIVE SURVEY IN 1979, MONUMENTED WITH AN IRON PIPE, 3/4" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, FROM WHICH A FIR SNAG 31" DIA (GLO BT) BEARS S70°E, 25 LINKS (16.50 FEET), NO MARKS VISIBLE. (BLM FORESTER REPORTED FINDING SCRIBING ON BARK IN 1964). AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, DIRECTLY OVER IRON PIPE, WITH BRASS CAP MARKED "1/4 S1 T14S R7W SC 1991" FROM WHICH A FIR 5" DIA BEARS S50°E, 42-1/2 LINKS (28.05 FEET) MARKED "X BT" ON DOUBLE BLAZE; A FIR 7" DIA BEARS S1-1/4°W, 51 LINKS (33.66 FEET) MARKED "1/4 S1 SC BT".

[04] BENTON COUNTY SURVEY NO. 9866 BY JIM S. PETERSON, P.L.S., DATED APRIL 11, 2000. FOUND 3-1/4" BLM BRASS CAP. FOUND FIR 10" DIA (BLM BT) BEARS S50°E, 42-1/2 LINKS (28.05 FEET), HEALED FACE; FIR 10" DIA (BLM BT) BEARS S1-1/4°W, 51 LINKS (33.66 FEET), HEALED FACE; FIR SNAG 34" DIA (GLO BT) BEARS S70°E, 25 LINKS (16.50 FEET), NO MARKS VISIBLE. CORNER LIES ON EAST SLOPE.

[05] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY RICHARD S. KAISER, CADASTRAL SURVEYOR, DATED MARCH 17, 2008. MONUMENTED WITH A STAINLESS STEEL POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 1" ABOVE GROUND, WITH A BRASS CAP MARKED "1/4 S1 T14S R7W SC 1991" FROM WHICH A FIR SNAG 32" DIA (GLO BT) BEARS S70°E, 16.2 FEET, NO SCRIBE MARKS VISIBLE; A FIR 13" DIA (BLM BT) BEARS S50°E, 28.0 FEET, WITH A HEALED DOUBLE BLAZE; A FIR 12" DIA BEARS S1-1/4°W, 33.7 FEET, WITH A HEALED BLAZE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME