

**147841020**

DATE 04/06/2017

TOWNSHIP 14 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER N/A  
DONATION LAND CLAIM JOHN KELLUM NO. 41 CORNER SOUTHEAST

**COMMON CORNER(S):**

NONE

**RECORDS (INFORMATION IN BOLD /ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

**BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.**

- [01]** GENERAL LAND OFFICE (GLO) NOTES OF THE JOHN KELLUM DONATION LAND CLAIM (DLC) NO. 41 BY DENNIS HATHORN, D.S., DATED DECEMBER 11, 1857. **SET POST FROM WHICH A MAPLE 6" DIA BEARS N50°E, 19 LINKS (12.54 FEET); A MAPLE 9" DIA BEARS N70°W, 32 LINKS (21.12 FEET).**
- [02]** BENTON COUNTY SURVEY NO. 1190 (OLD NO. 53) FIELD NOTES (FIELD BOOK 79, PAGE 17) BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 30, 1932. **SET BUGGY AXLE 5' X 1-1/2" X 1-1/2"**.
- [03]** BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 202, BY W. C. GALLOWAY, C.S., DATED OCTOBER 1, 1932. **SET A BUGGY AXLE. FOUND PRINT OR EVIDENCE OF CORNER OF FORMER SURVEY.**
- [04]** BENTON COUNTY CORNER RESTORATION NO. 2625. **TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [05]** BENTON COUNTY MAP NO. 14-7-00002 BY W. C. GALLOWAY, C.S., DATED OCTOBER 21, 1916. **BUGGY AXLE.**
- [06]** BENTON COUNTY MAP NO. 14-7-00005 BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. **BUGGY AXLE. 5 FEET LONG.**
- [07]** BENTON COUNTY SURVEY NO. 5639 BY FRED I. LEMKE, P.L.S., DATED FEBRUARY 28, 1974. **CORNER NOT FOUND.**
- [08]** BENTON COUNTY SURVEY NO. 7074 BY DAVID K. BATEMAN, P.L.S., DATED MAY 5, 1980. **CORNER NOT FOUND.**

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

## CORNER RESTORATION BOOK NO. 1

C.S. Road #591  
Decker Road  
Witnesses  
Emile E. Lorain  
Harold Merryman  
by W.C. Galloway

Witnesses as  
above

1/4 Sec. Cor. between secs. 32 & 33. T. 12 S. R. 6 W.  
Set a 3/4" iron rod (midsheld brace) both stumps with letters found  
Orig. Fir 6" in dia. bears N. 61° E. 14 Stump rotten.  
" 6" " " " N. 27° W. 05 " good condition  
Mkd. " 30" " " " S 68° 10' W. 2.102

June 1934

Inferior Corner of Hixhish Banks D.L.C. 6. 6 & 48 T. 28 S.  
Set a 1" Pipe, Found brick bats at corner R. 6 W.  
found Oak 24 N 65° W. 34 dead

Marked a fir 20" in dia. bears N 17° E. 0.45 chains  
" " " " " N 68° W. 1.313 " + 4' 15" = 1.309  
" " " " " S 46° W. 1.122 "

June 1934

Mark's Road #596  
Frank Böttger  
and Emile E. Lorain  
by W.C. Galloway  
July 28, 1934

C.S. 53 cont.  
Witnesses  
G. Mark Grogg  
Emile E. Lorain  
by W.C. Galloway  
Oct. 1, 1932

C.S. #128  
by MC. Galloway  
Witnesses  
Frank Saenger and  
Gussie W. G. Saw. Hurling  
March 20, 1912

Witnesses as above  
March 3, 1912

C.S. #128  
Witnesses as above  
B.E. Martin  
& S.W. Fender  
Aug. 1912  
Oct. 1938  
Trees mkd. and  
stone replaced

1/4 Sec. Cor. bet. Secs. 22 & 23 T. 10 S. R. 7 W.  
Set a 1 1/4" Shaft (1/2 of an axle)

Set from Fir 40" N 50° W. 59 lks. lower blaze on snag

" " " 40" N 7° E. 479 " Cut into marks. Good tree.

Marked a fir 13" in dia. bears N 34° E. 2.22 chain to nail inside

" on Alder 20" " " S 84 3/4° E. 5.52 "

" " " 20" " " S 19° W. 1.0915 " Nail inside

Most South S.W. Corner of John Kellum D.L.C. #41714-7

Set a 1/2" Galv. pipe on Fence line 10.50 S. of Interior Corner

Marked a Willow 20" in dia. bears S. 83° W. 7.30

" on Alder 17" " " " N. 7° E. 4.17

A 1" Pipe on S.L. Rycraft Claim line. S. 0° 13' W. 2.430

S.E. Cor. of John Kellum D.L.C. # 418 46 Tps 14 S. Rs. 788 W

Set a Buggy axle. found print or evidence of corner of former survey.

N.E. corner of Section 4 T. 14 S. R. 7 W on std. line

Set a wagon spring (leaf) fir down, dogwood with sprouts (ex. in 1938)

Fir 48" in dia. bears S. 55° E. 1.145 chains

" 54" " " " S 14° W. .384 "

N.W. corner of Sec. 4 T. 14 S. R. 7 W.

Set a 1 1/2" x 14" Iron pin

Fir 12" in dia. bears S. 65° E. .53 std.

" 15" " " " S. 10° W. .80 obs. std.

1/4 Sec. Cor. on N. of Sec. 4 on 3rd Std. parallel T. 14-7

Set a 1' x 2 1/2" x 26" Iron bar

Color stump 48" in dia. bears S 60° E. .30 chs. std.

Mkd. fir 5" in dia. bears N. 97 1/4° E. .334 "

" 4" " " " S 70 3/4° E. .133 "

C.S.  
Witness  
J.E. B.  
Arthur  
Fred C.  
by W.C.  
Oct. 9,  
C.S.

Witness  
signature  
Pg. 12  
by W.  
May 1

C.S.  
Witness  
by W.  
(July)

C.S.  
Witness  
James  
Emile  
F.M.

Witness  
Jun

Witness  
abr  
Jun

Witness  
Em  
W.  
C.  
et

Witness  
L.  
J.

Witness  
L.  
J.

Witness  
L.  
J.

S.E. corner of John Kellum DLC 41 and 46, Twp. 14 S R 7 and 8 W. 2625

Reestablishment by W. C. Galloway

October 1, 1932

Set a buggy axle, found print of evidence of corner of former survey. 3100  
Witnesses G. Merle Gragg and Emil E. Larkin