

**148100100**

DATE 02/03/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 31 CORNER SOUTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 36, TOWNSHIP 14 SOUTH, RANGE 9 WEST  
NORTHWEST CORNER SECTION 6, TOWNSHIP 15 SOUTH, RANGE 8 WEST  
NORTHEAST CORNER SECTION 1, TOWNSHIP 15 SOUTH, RANGE 9 WEST**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. *SET POST 4-1/2 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T14S R8W S31" ON THE NORTHEAST FACE, "T15S R8W S6" ON THE SOUTHEAST FACE, "T15S R9W S1" ON THE SOUTHWEST FACE, AND "T14S R9W S36" ON THE NORTHWEST FACE, WITH SIX NOTCHES ON THE NORTH, SOUTH, EAST AND WEST EDGES. DUG PITS 24" X 18" X 12" LENGTHWISE ON EACH LINE NORTH, SOUTH, EAST AND WEST OF POST 6 FEET DISTANT, AND RAISED MOUND OF EARTH 2-1/2 FEET HIGH, 5 FEET AT BASE, AROUND POST FROM WHICH A RED FIR 36" DIA BEARS S73°55'W, 395 LINKS (260.70 FEET), MARKED "T14S R9W S1 BT"; DEAD FIR STUMP 18" DIA BEARS N80°E, 81 LINKS (53.46 FEET), MARKED "T14S R8W S31 BT".*
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY STEPHEN D. HARDIN, CADASTRAL SURVEYOR, DATED NOVEMBER 21, 1979. *POINT FOR THE CORNER AT PROPORTIONATE DISTANCE, THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER. SET AN IRON POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, WITH BRASS CAP MARKED "T14S R9W R8W S36 S31 S1 S6 T15S 1978" FROM WHICH A FIR 13" DIA BEARS N66-1/2°E, 73 LINKS (48.18 FEET), MARKED "T14S R8W S31 BT"; FIR 21" DIA BEARS S77-1/2°E, 44 LINKS (29.04 FEET), MARKED "T15S R8W S6 BT"; FIR 6" DIA BEARS S4-1/2°W, 39 LINKS (25.74 FEET), MARKED "X BT"; FIR 14" DIA BEARS N26-1/2°W, 82-1/2 LINKS (54.45 FEET), MARKED "T14S R9W S36 BT".*
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY STEPHEN D. HARDIN, CADASTRAL SURVEYOR, DATED MARCH 7, 1983. *POINT FOR THE CORNER AT PROPORTIONATE DISTANCE, THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER. FROM THIS POINT THE CORNER ERRONEOUSLY REESTABLISHED BY HARDIN IN 1978-1979, BEARS SOUTH, 0.205 CHAINS (13.53 FEET), SET, MARKED, AND WITNESSED AS DESCRIBED IN THE OFFICIAL RECORD. REMOVE THE IRON POST, AND AT THE TRUE CORNER POINT RESET THE IRON POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, WITH BRASS CAP MARKED "T14S R9W R8W S36 S31 S1 S6 T15S 1983 1978" FROM WHICH A FIR 14" DIA (BLM BT) BEARS N83-1/2°E, 68-1/2 LINKS (45.21 FEET), WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON PARTIALLY HEALED BLAZE; FIR 25" DIA (BLM BT) BEARS S54-1/4°E, 54-1/2 LINKS (35.97 FEET), WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON PARTIALLY HEALED DOUBLE BLAZE; FIR 6" DIA (BLM BT) BEARS S1-3/4°W, 60-1/2 LINKS (39.93 FEET), WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON PARTIALLY HEALED DOUBLE BLAZE; FIR 17" DIA BEARS N34-1/4°W, 64 LINKS (42.24 FEET), WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON PARTIALLY HEALED BLAZE.*
- [04] BENTON COUNTY SURVEY NO. 7723 BY GARY T. JOHNSTON, P.L.S., DATED FEBRUARY 8, 1985. *FOUND BRASS CAP RESET BY CADASTRAL SURVEY IN 1983. BEARING TREES WITH RECORD MEASUREMENTS TO CENTER OF TREE: D. F. 14" DIA (BLM BT) BEARS N83-1/2°E, 68-1/2 LINKS (45.21 FEET), SCRIBE MARKS VISIBLE ON PARTIALLY HEALED FACE; D. F. 25" DIA (BLM BT) BEARS S54-1/4°E, 54-1/2 LINKS (35.97 FEET), SCRIBE MARKS VISIBLE ON PARTIALLY HEALED FACE; D. F. 6" DIA (BLM BT) BEARS S1-3/4°W, 60-1/2 LINKS (39.93 FEET), SCRIBE MARKS VISIBLE ON PARTIALLY HEALED FACE; D. F. 17" DIA BEARS N34-1/4°W, 64 LINKS (42.24 FEET), SCRIBE MARKS VISIBLE ON PARTIALLY HEALED FACE.*
- [05] BENTON COUNTY SURVEY NO. 10747 BY ROBERT ALAN COOK, P.L.S., DATED DECEMBER 4, 2015. *CORNER NOT TIED OR DESCRIBED.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME