

148100440

DATE 11/30/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 18 CORNER WEST 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

EAST 1/4 CORNER SECTION 13, TOWNSHIP 14 SOUTH, RANGE 9 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. *SET ALDER POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON WEST FACE, FROM WHICH AN ALDER 8" DIA BEARS N9-1/2°E, 30 LINKS (19.80 FEET), MARKED "1/4S BT"; RED FIR 12" DIA BEARS N62°W, 55 LINKS (36.30 FEET), MARKED "1/4S BT".*
- [02] OREGON STATE HIGHWAY DEPARTMENT ROLL MAP 1F-6-19 FOR THE LOCATED LINE, MISSOURI BEND SECTION OF THE ALSEA HIGHWAY, BENTON COUNTY, DATED JULY 31, 1925. *CORNER TIED BUT NOT DESCRIBED.*
- [03] OREGON STATE HIGHWAY DEPARTMENT ROLL MAP 1B-19-23 FOR THE CONSTRUCTED LINE, MISSOURI BEND SECTION OF THE ALSEA HIGHWAY, DATED FEBRUARY, 1933. *CORNER TIED BUT NOT DESCRIBED.*
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY C. ALBERT WHITE, CADASTRAL SURVEYOR, DATED AUGUST 30, 1967. *POINT FOR THE 1/4 SECTION CORNER AT PROPORTIONATE DISTANCE, THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER. SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "1/4 S13 S18 R9W R8W T14S 1967" FROM WHICH A FORKED MAPLE 38" DIA BEARS S13-1/2°E, 38 LINKS (25.08 FEET), MARKED "1/4 S18 BT"; FORKED MAPLE 33" DIA BEARS S80°W, 64 LINKS (42.24 FEET), MARKED "1/4 S13 BT".*
- [05] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY C. ALBERT WHITE, HARVEY E. WOFFORD, AND STEPHEN D. ALBRIGHT, CADASTRAL SURVEYORS, DATED MAY 21, 1970. *1/4 SECTION CORNER.*
- [06] BENTON COUNTY SURVEY NO. 8660 BY LES ROBERTS, P.L.S., DATED NOVEMBER 20, 1992. *FOUND 1967 BLM BRASS CAP MARKED "T14S R9W R8W 1/4 S13 S18 1967". MAPLE 36" DIA (BLM BT) BEARS S13°E, 24.3 FEET, SCAR VISIBLE; MAPLE 40" DIA (BLM BT) BEARS S81°W, 41.6 FEET, SCAR VISIBLE.*
- [07] BENTON COUNTY PARTITION PLAT 2000-44 BY THEODORE JAMES LANGTON, P.L.S., DATED DECEMBER 27, 1999. *FOUND 3-1/4" BLM BRASS CAP ON 2" OUTSIDE DIAMETER PIPE MARKED "T14S R9W R8W 1/4 S13 S18 1967".*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME