

148140600

DATE 10/27/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 7

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED DECEMBER 5, 1856. *SET POST FROM WHICH A FIR 36" DIA BEARS N20°E, 47 LINKS (31.02 FEET); FIR 30" DIA BEARS S10°W, 60 LINKS (39.60 FEET).*
- [02] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 8, 1891. *OLD POST AND BEARING TREES DESTROYED. SET AN ALDER POST 3 FEET LONG, 3" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON NORTH FACE, FROM WHICH A RED FIR 10" DIA BEARS S19°E, 35 LINKS (23.10 FEET), MARKED "1/4S BT"; ALDER 6" DIA BEARS N49-1/2°E, 94 LINKS (62.04 FEET), MARKED "1/4S BT".*
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY C. ALBERT WHITE, HARVEY E. WOFFORD, AND STEPHEN D. ALBRIGHT, CADASTRAL SURVEYORS, DATED MAY 21, 1970. *THE 1/4 SECTION CORNER MONUMENTED WITH AN IRON PIPE, 2" DIA, FIRMLY SET, EXTENDING 10" ABOVE GROUND, FROM WHICH A SAWED FIR STUMP 40" DIA (GLO BT) BEARS S20-1/2°E, 35 LINKS (23.10 FEET), WITH SCRIBE MARKS "1/4" VISIBLE ON OPENED BLAZE; ALDER 22" DIA BEARS N40°E, 46 LINKS (30.36 FEET), WITH SCRIBE MARKS "1/4" VISIBLE ON OPEN BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "S6 1/4 S7 T14S R8W 1969" FROM WHICH A FIR 25" DIA BEARS S9-1/2°E, 40 LINKS (26.40 FEET), MARKED "1/4 S7 BT". RESET IRON PIPE ALONGSIDE IRON POST.*
- [04] BENTON COUNTY SURVEY NO. 6306 BY FRED I. LEMKE, P.L.S., DATED JANUARY 31, 1977. *FOUND BLM BRASS CAP.*
- [05] BENTON COUNTY SURVEY NO. 7203 BY GARY T. JOHNSTON, P.L.S., DATED NOVEMBER, 1980. *FOUND 1969 BLM BRASS CAP AND 2" IRON PIPE.*
- [06] LINCOLN COUNTY SURVEY NO. 9577 BY MICHAEL D. LEMKE, P.L.S., DATED MAY 20, 1981. *FOUND 1969 BLM BRASS CAP.*
- [07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT W. DAHL, CADASTRAL SURVEYOR, DATED JULY 15, 1987. *THE 1/4 SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MARKED "S6 1/4 S7 T14S R8W 1969" FROM WHICH A FIR STUMP 40" DIA (GLO BT) BEARS S20-1/2°E, 35 LINKS (23.10 FEET), WITH FRAGMENTARY SCRIBE MARKS VISIBLE ON OPENED BLAZE; ALDER 21" DIA BEARS N40°E, 46 LINKS (30.36 FEET), WITH SCRIBE MARKS "1/4S" VISIBLE ON PARTIALLY HEALED BLAZE; FIR 33" DIA (BLM BT) BEARS S9-1/2°E, 40 LINKS (26.40 FEET), WITH HEALED BLAZE. SET METAL FENCE POST ALONGSIDE IRON POST.*
- [08] BENTON COUNTY SURVEY NO. 9289 (ALSO BEING LINCOLN COUNTY SURVEY NO. 15507) BY C. HENRY COLE, P.L.S., DATED MARCH 3, 1998. *FOUND 3-1/4" BRASS CAP MARKED "S6 S1/4 S7 T14S R8W 1969".*
- [09] BENTON COUNTY SURVEY NO. 9680 BY JIM S. PETERSON, P.L.S., DATED FEBRUARY 14, 2001. *FOUND 3-1/4" BLM BRASS CAP.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME