

148200200

DATE 09/10/2019TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 29 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 30
NORTHEAST CORNER SECTION 31
NORTHWEST CORNER SECTION 32**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 8, 1891. SET CHERRY POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND MARKED "T14S R8W S29" ON THE NORTHEAST FACE, "S30" ON THE NORTHWEST FACE, "S31" ON THE SOUTHWEST FACE, AND "S32" ON SOUTHEAST FACE, WITH 5 NOTCHES ON EAST EDGE AND 1 NOTCH ON SOUTH EDGE, FROM WHICH A FIR 8" DIA BEARS S50-1/2°E, 75 LINKS (49.50 FEET), MARKED "T14S R8W S32 BT"; FIR 42" DIA BEARS S44°W, 62 LINKS (40.92 FEET), MARKED "T14S R8W S31 BT"; FIR 10" DIA BEARS N58°W, 61 LINKS (40.26 FEET), MARKED "T14S R8W S30 BT"; FIR 36" DIA BEARS N11°E, 81 LINKS (53.46 FEET), MARKED "T14S R8W S29 BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED AUGUST 12, 1960. CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM THE ORIGINAL BEARING TREES: FIR DEAD AND DOWN 50" DIA (GLO BT) BEARS N11°E, 81 LINKS (53.46 FEET), MARKED WITH A HEALED BLAZE; FIR 23" DIA (GLO BT) BEARS S50-1/2°E, 75 LINKS (49.50 FEET), MARKED WITH A HEALED BLAZE; FIR 50" DIA (GLO BT) BEARS S44°W, 62 LINKS (40.92 FEET), MARKED WITH A HEALED BLAZE; FIR 23" DIA (GLO BT) BEARS N58°W, 61 LINKS (40.26 FEET), MARKED "R8W S" ON EXPOSED FACE OF PARTIALLY OPENED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T14S R8W S30 S29 S31 S32 1960" FROM WHICH A MAPLE 12" DIA BEARS N71-1/2°E, 25 LINKS (16.50 FEET), MARKED "T14S R8W S29 BT"; FIR 12" DIA BEARS S13-3/4°E, 51 LINKS (33.66 FEET), MARKED "T14S R8W S32 BT"; FIR 10" DIA BEARS S64-1/2°W, 67 LINKS (44.22 FEET), MARKED "T14S R8W S31 BT"; FIR 18" DIA BEARS N26-3/4°W, 108 LINKS (71.28 FEET), MARKED "T14S R8W S30 BT".
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY STEPHEN D. HARDIN, CADASTRAL SURVEYOR, DATED NOVEMBER 21, 1979. CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MARKED "T14S R8W S30 S29 S31 S32 1960" FROM WHICH A ROOT HOLE BEARS N11°E, 81 LINKS (53.46 FEET), WITH A DOWN FIR ALONGSIDE, 50" DIA (GLO BT) WITH HEALED BLAZE; FIR 35" DIA (GLO BT) BEARS S50-1/2°E, 75 LINKS (49.50 FEET), WITH HEALED BLAZE; FIR 55" DIA (GLO BT) BEARS S44°W, 62 LINKS (40.92 FEET), WITH HEALED BLAZE; ROOT HOLE BEARS N58°W, 61 LINKS (40.26 FEET), WITH A DOWN FIR ALONGSIDE, 24" DIA (GLO BT) WITH SCRIBE MARKS "R8W S" VISIBLE ON OPENED BLAZE; MAPLE 17" DIA (BLM BT) BEARS N71-1/2°E, 26 LINKS (17.16 FEET), WITH SCRIBE MARKS "14S R8W S29 BT" VISIBLE ON PARTIALLY HEALED BLAZE; FIR 15" DIA (BLM BT) BEARS S13-3/4°E, 51 LINKS (33.66 FEET), WITH HEALED BLAZE; FIR 14" DIA (BLM BT) BEARS S64-1/2°W, 68 LINKS (44.88 FEET), WITH HEALED BLAZE; FIR SNAG 20" DIA (BLM BT) BEARS N26-3/4°W, 108 LINKS (71.28 FEET), NO MARKS VISIBLE.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY STEPHEN D. HARDIN AND FRANK A. TUERS, CADASTRAL SURVEYORS, DATED OCTOBER 30, 1989. CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MARKED "T14S R8W S30 S29 S31 S32 1960" FROM WHICH A ROOT HOLE BEARS N11°E, 81 LINKS (53.46 FEET), WITH A DOWN FIR ALONGSIDE, 50" DIA (GLO BT) WITH HEALED BLAZE; FIR 35" DIA (GLO BT) BEARS S48-3/4°E, 75 LINKS (49.50 FEET), WITH HEALED BLAZE; FIR 51" DIA (GLO BT) BEARS S44°W, 62 LINKS (40.92 FEET), WITH HEALED BLAZE; ROOT HOLE BEARS N58°W, 61 LINKS (40.26 FEET), WITH A DOWN FIR ALONGSIDE, 24" DIA (GLO BT) WITH DECAYED BLAZE; MAPLE 19" DIA (BLM BT) BEARS N71-1/2°E, 26 LINKS (17.16 FEET), WITH SCRIBE MARKS "S R8W S2" VISIBLE ON PARTIALLY HEALED BLAZE; FIR 23" DIA (BLM BT) BEARS S13-3/4°E, 51 LINKS (33.66 FEET), WITH HEALED BLAZE; FIR 14" DIA (BLM BT) BEARS S64-1/2°W, 68 LINKS (44.88 FEET), WITH HEALED BLAZE; FIR SNAG 15" DIA (BLM BT) BEARS N26-3/4°W, 108 LINKS (71.28 FEET), NO MARKS VISIBLE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME