

148200340

DATE 10/31/2013TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 19 CORNER EAST 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

WEST 1/4 CORNER OF SECTION 20

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 8, 1891. SET FIR POST 3-1/2 FEET LONG, 4 INCHES SQUARE, 24 INCHES IN THE GROUND, MARKED "1/4S" ON THE WEST FACE, FROM WHICH A FIR 18" DIA BEARS S9°W, 5 LINKS (3.30 FEET) MARKED "1/4S BT"; A FIR 8" DIA BEARS N41°E, 26 LINKS (17.16 FEET) MARKED "1/4S BT".
- [02] BENTON COUNTY SURVEY NO. 1639 (OLD NO. 362) FIELD NOTES (FIELD BOOK 99, PAGE 16) BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 27, 1943. SET A 3/4" BOLT. FIR 18" DIA (GLO BT) BEARS S9°W, 0.05 CHAINS (3.30 FEET) STANDING DEAD; NORTHEAST FIR DOWN. MARKED CEDAR 9" DIA BEARS N32-1/2°E, 0.404 CHAINS (26.66 FEET); NOT MARKED FIR 30" DIA BEARS S70°E, 0.355 CHAINS (23.43 FEET); MARKED MAPLE 15" DIA BEARS N84°W, 0.129 CHAINS (8.51 FEET).
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 235 BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 27, 1943. SET 3/4" BOLT. FIR 18" DIA (GLO BT) BEARS S9°W, 0.05 CHAINS (3.30 FEET) STANDING DEAD; OTHER TREE DOWN. MARKED CEDAR 9" DIA (CSBT) BEARS N32-1/2°E, 0.124 CHAINS (8.18 FEET); NOT MARKED FIR 30" DIA (CSBT) BEARS S70°E, 0.355 CHAINS (23.43 FEET); MARKED MAPLE 15" DIA (CSBT) BEARS N84°W, 0.129 CHAINS (8.51 FEET).
- [04] BENTON COUNTY CORNER RESTORATION NO. 2702. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY SURVEY NO. 1698 (OLD NO. 362) FIELD NOTES (FIELD BOOK 99, PAGE 20) BY W. C. GALLOWAY, C.S., DATED OCTOBER 19, 1944. 1/4 SECTION CORNER.
- [06] BENTON COUNTY MAP NO. 14-8-00008 BY W. C. GALLOWAY, C.S., DATED DECEMBER, 1937. 3/4" BOLT. FIR 18" DIA (GLO BT) BEARS S9°W, 0.05 CHAINS (3.30 FEET) STANDING DEAD; CEDAR 9" DIA (CSBT) BEARS N32-1/2°E, 0.404 CHAINS (26.66 FEET); NOT MARKED FIR 30" DIA (CSBT) BEARS S70°E, 0.355 CHAINS (23.43 FEET); MAPLE 15" DIA (CSBT) BEARS N84°W, 0.129 CHAINS (8.51 FEET).
- [07] BENTON COUNTY MAP NO. 14-8-00007 BY W. C. GALLOWAY, C.S., DATED DECEMBER 2, 1944. 3/4" BOLT. FIR 18" DIA (GLO BT) BEARS S9°W, 0.05 CHAINS (3.30 FEET) STANDING; CEDAR 9" DIA (CSBT) BEARS N32-1/2°E, 0.404 CHAINS (26.66 FEET); NOT MARKED FIR 30" DIA (CSBT) BEARS S70°E, 0.355 CHAINS (23.43 FEET); MAPLE 15" DIA (CSBT) BEARS N84°W, 0.129 CHAINS (8.51 FEET).
- [08] BENTON COUNTY SURVEY NO. 6029 BY FRED I. LEMKE, P.L.S., DATED DECEMBER 31, 1975. FOUND 3/4" BOLT. FIR STUMP 30" DIA (CSBT) BEARS S70°E, 23.4 FEET; FIR STUMP 12" DIA BEARS SOUTH, 4 FEET; MAPLE 28" DIA (CSBT) BEARS N84°W, 8.67 FEET. SCRIBED CEDAR 31" DIA BEARS N32-1/2°E, 26.29 FEET.
- [09] BENTON COUNTY SURVEY NO. 6095 BY L. W. BARBER, PROJECT ENGINEER, DATED 1976. 3/4" IRON BOLT AND THREE BEARING TREES.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 766-6821**RESEARCH BY:** DAVID L. MALONE, P.L.S.**DATA ENTRY BY:** SAME

CORNER RESTORATION BOOK NO. 1

- C.S. 126 by W.C.G.
Apr. 24, 1942
Waller Fawcett
Everett Padgett
- 1/4 Sec. Cor. bet. Secs. 16 and 17 T 14-8
Set 1/2" pipe. Orig. cor. Notch in old log of cor.
Fir 24" in dia. bears S. 1° E. 1.34 std.
" 24" " " S 2° W. 1.25 "
- W.C.G. and
V.M. Peterson
Aug. 7, 1942.
- 1/4 Sec. Cor. bet. Secs. 15 and 16 T 14-8
Set a 3/4" pipe 20 kts. N. of cr.
Maple 12" now 22" in dia. bears S. 60° W. .59 chs. std. S. of cr.
Mkd. Alder 28" " " S. 78 1/2° E. .877 " measure to 1 on N. of tree
" Fir 56" " " S. 27 1/2° E. .5924 " ahead of rail on W. S 23° 04' E.
- C.S. # 362
by W.C.G.
Restoration Laboratory
and O. Ed. Mescher
David Roe
Sep. 27, 1943
- 1/4 Sec. Cor. bet. Secs. 19 and 20 T 14-8
Set 3/4" bolt
Fir 18" in dia. bears S. 9° W. .05 chs. std. dead. Other tree down
Mkd. Cedar 9" " N 32 1/2° E. .124 "
Fir 30" in " " S. 70° E. .355 " not mkd.
Mkd. Maple 15" " N. 84° W. .129 "
- As above
also Geo. W. Shannon
and father were
here
- Sept. 29, 1943
- by W.C.G.
Mescher and
David Roe
Sept 29, 1943
- 1/4 Sec. Cor. bet. Secs. 20 and 29 T. 14-8
Set 3/4" pipe
Alder 30" in dia. bears N 37 1/2° E. .06 and Alder 30° S 56 1/2° E 18 kts. ^{Edown.}
Mkd. Maple 40" in dia. bears N 3° 50' E. 1.651 chs. mark W.
" Ash 26" " " N. 75 1/2° E. .526 " " N.
Corner to Sections 19, 20, 29 and 30 T 14-8
Set a Studebaker car axle with Timkin bearing. ^{Sharp hillside W. of cr. Foot} sharp ridge.
Fir 10" in dia. bears S. 71° W. .11 chs. std. all other trees found down
Mkd. Cedar 5" " N. 81° 20' E. .249 " at top of upper blaze 5' up
" Fir 20" " S. 42° W. .163 "
" " 21" " N. 15° W. .430 "
- C.S. # 107
Dec. 6, 1943
T.J. Storker
and R.F. Olson
- 1/4 Sec. Corner bet. Secs. 11 & 14 T 14-8
Set 1" pipe
Fir 12" now 48" in dia. bears N. 25° E. .48 chs. std.
Mkd. " 29" " " S. 48° E. .446 "
" Dogwood 5" " " S. 16° 47' E. .680 "
" 60" " " S. 48° W. 350 " to blaze
- C.S. # 72
by W.C. Galloway
May 8, 1944
Ed. P. Rickard
- Most N. N.E. Cor. of Wm. Crow Ch. 42 T 15-5
Stone at fence corner 5" x 7" x 10"
W. fir 16" in dia. bears South .079 chs.
Set a 1" pipe South .215 chs.
- C.S. # 72
by W.C. G.
July 1, 1937
Rudolph Stewart
Warren Doidge
- Corner to Secs. 1, 2, 11 and 12 T. 15-5
Stone set by Geo. W. Wagoner
Mkd. Oak Forked 24" and 32" N. 81° 45' E. .922
" " 6" S. 2° E. 2.088

$\frac{1}{4}$ -Section corner between sections 19 and 20, Twp. 14-8

Reestablishment by W. C. Galloway

Sept. 27, 1943

Set $\frac{5}{8}$ " bolt

Fir 18" in diam bears S 9° W
 Cedar 9" in diam bears N 32 $\frac{1}{2}$ ° E
 Fir 30 in diam bears S 70° E
 Maple 15" in diam bears N 84° W
 Witnesses O. Ed. Mesecher and David Roe

.05 chains
 .124 chains
 .355 chains
 .129 chains