

**148240100**

DATE 02/06/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 32 CORNER SOUTH 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 5, TOWNSHIP 15 SOUTH, RANGE 8 WEST

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. SET FIR POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON NORTH FACE, FROM WHICH A RED FIR 24" DIA BEARS S53-1/2°W, 29 LINKS (19.14 FEET), MARKED "1/4SBT"; RED FIR 18" DIA BEARS NORTH, 38 LINKS (25.08 FEET), MARKED "1/4SBT".
- [02] BENTON COUNTY SURVEY NO. 530 (OLD NO. 243) FIELD NOTES (FIELD BOOK 20, PAGE 37) BY W. C. GALLOWAY, C.S., DATED OCTOBER 16, 1915. SET 3/8" X 1-1/4" IRON BAR. FIR 18" DIA (GLO BT) BEARS N2°W, 0.38 CHAINS (25.08 FEET), STANDING DEAD; FIR 24" DIA (GLO BT) BEARS S61°30'W, 0.29 CHAINS (19.14 FEET), STANDING; FIR 28" DIA BEARS N17°E, 0.694 CHAINS (45.80 FEET).
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 98, BY W. C. GALLOWAY, C.S., DATED OCTOBER 16, 1915. SET 3/8" X 1" IRON BAR. FIR 18" DIA (GLO BT) BEARS N2°W, 0.38 CHAINS (25.08 FEET), STANDING DEAD GIRDLED; FIR 24" DIA (GLO BT) BEARS S61°30'W, 0.29 CHAINS (19.14 FEET), STANDING; FIR 28" DIA (CSBT) BEARS N17°E, 0.694 CHAINS (45.80 FEET).
- [04] BENTON COUNTY CORNER RESTORATION NO. 2761. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY MAP NO. 15-8-00002 BY W. C. GALLOWAY, C.S., DATED OCTOBER, 1915. 3/8" X 1-1/4" IRON. FIR 18" DIA (GLO BT) BEARS N2°W, 0.38 CHAINS (25.08 FEET), STANDING; FIR 24" DIA (GLO BT) BEARS S61°30'W, 0.29 CHAINS (19.14 FEET), STANDING; FIR 28" DIA (CSBT) BEARS N17°E, 0.694 CHAINS (45.80 FEET).
- [06] BENTON COUNTY SURVEY NO. 7406 BY JIM S. PETERSON, P.L.S., DATED JUNE 4, 1982. FOUND 3/8" X 1-1/4" IRON BAR.
- [07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY DANNY J. NEVIN, CADASTRAL SURVEYOR, DATED APRIL 4, 1994. CORNER MONUMENTED WITH AN IRON BAR, 3/8" X 1-1/4", FIRMLY SET, PROJECTING 3" ABOVE GROUND, FROM WHICH A FIR 45" DIA (GLO BT) BEARS S61-1/2°W, 29 LINKS (19.14 FEET), WITH HEALED BLAZE; ROOT HOLE BEARS N27°E, 69-1/2 LINKS (45.87 FEET), ALONGSIDE OF WHICH IS A DOWN FIR 32" DIA (CSBT), NO MARKS VISIBLE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, DIRECTLY OVER IRON BAR, WITH BRASS CAP MARKED "T14S R8W S32 1/4 S5 T15S 1994" FROM WHICH A FIR 22" DIA BEARS N47-1/4°E, 62-1/2 LINKS (41.25 FEET), MARKED "1/4 S32 BT".

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

## CORNER RESTORATION BOOK NO. 1

CS. # 244  
W.C. Galloway C.S.

Meander corner on W. bank of East Willamette River  
8.03 chs. South of Cor. to secs. 1, 6, 7 & 12 T. 12 S. R. 4 & 5 W.  
Drove nail in root on steep bank about 3ft. lower than level ground  
Ash stump 20" in dia. bears S. 42° 15' W. .47 chs.  
" 6" " " " N 45° E. .75 " std. remkd.  
Marked Ash 10" " " " N. 8° W. .195 "

CS. # 244

CS. # 243  
W.C. Galloway C.S.

1/4 sec. cor. between secs. 4 & 5 T. 15 S. R. 8 W.  
Set brake lever  
Fir 50" in dia. bears S. 7° E. 1.95 chs. stump.  
" 60" " " " S. 64° W. 3.92 " std.  
Witnesses M.W. & Lester Skeels Oct. 12 1915.

Corner to Secs. 4, 5, 8 & 9 T. 15 S. R. 8 W.  
Set a wringer orig. cor. N.E. snag. N.W. stump.  
Alder 3" in dia. bears N. 6° E. .170 chs.  
Fir 12" " " " S. 62° E. .07 " std.  
" 7" " " " S. 22° W. .23 " " not grown over  
" 30" " " " N. 17° 40' W. .720 "  
Witnesses M.W. & Lester Skeels, W.A. Moore & Joe Davis Oct. 13, 1915.

1/4 cor. between secs. 5 & 6 T. 15 S. R. 8 W.  
Set Iron 1" X 2 1/2" X 24" part of blow. Orig. cor. Letters on log of stump N.E.  
2 alders sw.  
Mkd. Fir 16" in dia. bears N. 68° 30' E. 1.194 chs. Vert. L 17° 45'  
" Alder 7" " " " N. 38° 45' W. .530 "  
Witnesses M.W. & Lester Skeels, W.A. Moore, Joe Davis & A. Tilson, Oct. 14, 1915

CS  
CS. # 190  
W.C. Galloway C.S.

1/4 cor. between secs. 5 & 8 T. 15 S. R. 8 W.  
Set a 3/4" rod Alder down. Corner in the draw or ditch of a  
steep canyon steep hillside s. of cor. & West also pretty steep on N.  
Fir 14" in dia. bears S. 73° E. .29 chs. std. dead.  
" 16" " " " S. 73° E. .600 "  
Maple 15" " " " N 30° W. .400 "  
Alder 20" " " " North .120 " This alder bears name & date of  
first survey. also mkd. C.S. 243 BT.  
Witnesses M.W. & Lester Skeels, Joe Davis and W.A. Moore Oct. 15, 1915.

1/4 cor. between secs. 3 & 5 Tps. 14 & 15 S. R. 8 W.  
Set a 3/8" X 1" iron bar  
Fir 18" in dia. bears N. 2° W. .38 chs. std. dead. girdled.  
" 28" " " " N. 17° E. .694 "  
" 24" " " " S. 61° 30' W. .29 " "  
Witnesses Joe Davis, Lester Skeels & W.A. Moore Oct. 16, 1915.

CS. # 245  
W.C. Galloway C.S.

Cor. to secs. 25, 26, 35 & 36 T. 13 S. R. 5 W.  
Set 3/4" pipe found old oak stake which is driven by pipe also small stone.  
Ash 5" in dia. bears N. 15° E. .88 chs. std.  
" 3" " " " S. 19° 45' E. .08 " "  
Oak 14" " " " S. 31° W. .670 "  
" 15" " " " N. 24° 30' W. 4.19 " " Witnesses Lolan Beach, R.R. Taylor &  
Michael Rickard. Oct. 20, 1915

Miscellan  
E.S

$\frac{1}{4}$ -Corner between sections 32 and 5, Twp. 14 and 15 S., R. 8 W.

2761

3258

Reestablishment by W. C. Galloway

October 16, 1915

Set  $\frac{3}{8}$ " iron bar

Fir 18" in diam bears N 2° W

.38 chains (std. dead)

Fir 28" in diam bears N 17° E

.694 chains

Fir 24" in diam bears S 61° 30' W

.29 chains (standing)

Witnesses Joe Davis, Lester Skells and W. A. Moore