

**148300100**

DATE 02/06/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 32 CORNER SOUTHEAST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 33, TOWNSHIP 14 SOUTH, RANGE 8 WEST  
NORTHWEST CORNER SECTION 4, TOWNSHIP 15 SOUTH, RANGE 8 WEST  
NORTHEAST CORNER SECTION 5, TOWNSHIP 15 SOUTH, RANGE 8 WEST**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. SET FIR POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T14S33" ON THE NORTHEAST FACE, "SR8WS4" ON THE SOUTHEAST FACE, "T15S5" ON THE SOUTHWEST FACE, AND "S32" ON THE NORTHWEST FACE WITH 2 NOTCHES ON THE WEST EDGE AND 4 NOTCHES ON THE EAST EDGE, FROM WHICH A RED FIR 14" DIA BEARS S2-1/2°W, 58 LINKS (38.28 FEET), MARKED "T15SR8WS5BT"; RED FIR 18" DIA BEARS N43°W, 55 LINKS (36.30 FEET), MARKED "T14SR8WS32BT"; ALDER 12" DIA BEARS N77°E, 5 LINKS (3.30 FEET), MARKED "T14SR8WS33BT"; ALDER 8" DIA BEARS S41°E, 6 LINKS (3.96 FEET), MARKED "T15SR8WS4BT".
- [02] BENTON COUNTY SURVEY NO. 1276 (OLD NO. 359) FIELD NOTES (FIELD BOOK 79, PAGE 21) BY W. C. GALLOWAY, C.S., DATED MAY 7, 1936. SET 5/8" X 24" BOLT. ALDER N77°E GONE. ALDER 8" DIA (GLO BT) BEARS S30°E, 0.060 CHAINS (3.96 FEET); FIR 14" DIA (GLO BT) BEARS S5°W, 0.580 CHAINS (38.28 FEET); ALDER 14" DIA BEARS S14°W, 0.122 CHAINS (8.05 FEET); FIR 30" DIA BEARS N30°30'W, 0.969 CHAINS (63.95 FEET).
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 208, BY W. C. GALLOWAY, C.S., DATED MAY 7 1936. SET 5/8" X 24" BOLT, STONES. ALDER 8" DIA (GLO BT) BEARS S31°E, 0.06 CHAINS (3.96 FEET), STANDING; FIR 14" DIA (GLO BT) BEARS S3-1/2°W, 0.58 CHAINS (38.28 FEET), STANDING; FIR 8" DIA (GLO BT) BEARS N32°W, 0.49 CHAINS (32.34 FEET), DOWN; MARKED ALDER 14" DIA (CSBT) BEARS S12-1/2°W, 0.122 CHAINS (8.05 FEET); BLAZED FIR 30" DIA (CSBT) BEARS N32°W, 0.969 CHAINS (63.95 FEET).
- [04] BENTON COUNTY CORNER RESTORATION NO. 2956. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY MAP NO. 15-8-00002 BY W. C. GALLOWAY, C.S., DATED OCTOBER, 1915. 5/8" IRON ROD. ALDER 8" DIA (GLO BT) BEARS S31°E, 0.06 CHAINS (3.96 FEET), STANDING; FIR 14" DIA (GLO BT) BEARS S3-1/2°W, 0.58 CHAINS (38.28 FEET), STANDING; ALDER 14" DIA (CSBT) BEARS S12-1/2°W, 0.122 CHAINS (8.05 FEET); FIR 30" DIA (CSBT) BEARS N32°W, 0.969 CHAINS (63.95 FEET), NOT LETTERED.
- [06] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY HARVEY E. WOFFORD, CADASTRAL SURVEYOR, DATED APRIL 29, 1968. CORNER MONUMENTED WITH AN IRON PIPE, 3/4" DIA, FIRMLY SET, PROTRUDING 1" ABOVE GROUND, FROM WHICH A FIR 38" DIA (GLO BT) BEARS S2-1/2°W, 58 LINKS (38.28 FEET), WITH OPEN AND BURNED BLAZE; FIR STUMP 38" DIA (CSBT) BEARS N32°W, 98 LINKS (64.68 FEET), WITH OPEN AND BURNED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T14S R8W S32 S33 S5 S4 T15S 1968" FROM WHICH AN ALDER 10" DIA BEARS N10-3/4°E, 105 LINKS (69.30 FEET), MARKED "T14S R8W S33 BT"; ALDER 6" DIA BEARS S88-3/4°E, 58 LINKS (38.28 FEET), MARKED "T15S R8W S4 BT"; FIR 40" DIA BEARS N69-1/4°W, 106 LINKS (69.96 FEET), MARKED "T14S R8W S32 BT".
- [07] BENTON COUNTY SURVEY NO. 7041 BY MICHAEL D. LEMKE, P.L.S., DATED DECEMBER 27, 1979. FOUND 2" IRON PIPE WITH BLM BRASS CAP.
- [08] BENTON COUNTY SURVEY NO. 7406 BY JIM S. PETERSON, P.L.S., DATED JUNE 4, 1982. FOUND BLM BRASS CAP.
- [09] BENTON COUNTY SURVEY NO. 7969 BY THEODORE JAMES LANGTON, P.L.S., DATED FEBRUARY 19, 1987. FOUND 3-1/4" BLM BRASS CAP MARKED "T14S R8W S32 S33 S5 S4 T15S 1968" ON 2-1/2" OUTSIDE DIAMETER PIPE. FOUND ALDER 12" DIA (BLM BT) BEARS S88-1/2°E, 58 LINKS (38.28 FEET), BARK SCRIBED "T15SR8WS4BT"; FIR STUMP 42" DIA (GLO BT) BEARS S6°W, 59 LINKS (38.94 FEET), NO VISIBLE SCRIBING ON HACKED FACE; FIR STUMP 40" DIA (BLM BT) BEARS N67°W, 106 LINKS (69.96 FEET), NO OBVIOUS MARKS; ALDER 31" DIA (BLM BT) BEARS N12-1/4°E, 105 LINKS (69.30 FEET), NO VISIBLE MARKS.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

## CORNER RESTORATION BOOK NO. 1

C.S. 208 Cont.  
by W.C. Galloway Es.  
Witnesses, Adrien Seits,  
James Johnston  
and Roy Starr  
May 18, 1935

$\frac{1}{4}$  Sec. corner between sections 21 & 22 T. 13 S. R. 6 W.  
Set a  $\frac{3}{4}$ " Galv. pipe 24" long  
Fir 60" in dia. bears S. 2° E. 1.69 chs, dead snag, letters on upper blaze  
" 18" " " " N. 44 $\frac{1}{2}$ ° W. 1.19 " std.  
Mkd. " 12" " " " S. 41° W. .368 "

As above  
May 22, 1935

$\frac{1}{4}$  Sec. corner between sections 22 & 27 T. 13 S. R. 6 W.  
Set a  $1\frac{1}{4}$ " x 20" pipe  
Fir 8" (no 33) in dia. bears S. 84° W. .55 chs. std.  
Mkd. fir 20" " " " N 73° 40' E. 480 "  
" Yew 24" " " " S 13° 30' E. 634 "

As above  
May 24, 1935

Corner to Sections 21, 22, 27 & 28 T. 13 S. R. 6 W.  
Set a  $\frac{3}{4}$ " x 24" pipe - (6" of pipe lying by vertical pipe)  
Fir 12" in dia. bears N. 46° E. 96 links, std.  
Dogwood 6" " " " S. 44° E. 145 " "  
Mkd. fir 60" " " " S. 29 $\frac{1}{4}$ ° W. 103.4 " to face and 106.7 to cen.  
" Yew 6" " " " S. 42° W. 119 " std. dead  
Fir 8" " " " " N. 68° W. 143 " stump with B.T.  
" " 11" " " " N. 11° W. 64.0 "

C.S. 339 Cont.  
by W.C. Galloway  
Feb. 7, 1936.

Corner to sections 11, 12, 13 & 14 T. 11 S. R. 6 W. Mill. Mer.  
Set a 2" x 20" shaft. <sup>not found</sup> Found cherry 4" N. 70° W. .26 of chain, others down and gone  
Marked a fir 24" in dia. bears N. 19° 20' E. .739 chs. (cut) bearings from line  
" " 36" " " " S. 72° 40' E. .660 " windthrown 1949  
" " 56" " " " S. 39° 30' W. " "  
" " 56" " " " N. 74° W. 480 chs. Nail in north side for measure

"

$\frac{1}{4}$  Section corner between sections 12 & 13 T. 11 S. R. 6 W.  
Set a  $\frac{3}{4}$ " x 30" Galv. pipe, From Fir 7" N. 6° E. 35 lks. std. dead and  
Group of Maples around position of Maple 6" S 15° E 7 links.  
Mkd. Maple 12" in dia. bears S. 16° E. .046 of chain bearings from line  
" a fir 26" " " " N. 72° W. .391 " "

C.S. 243 con  
Witnesses  
W.D. Risky,  
Harold McCormick  
Willis L. Buok  
May 7, 1936.

Corner to Secs. 32, 33, 4 & 5 Tps. 14 & 15 S. R. 8 W. W.M.  
Set  $\frac{3}{8}$ " x 24" bolt stones  
From Alder 8" S. 31° E. .06 chs. std.  
" Fir 14" S. 3 $\frac{1}{2}$ ° W. .58 " " , Fir 8" N. 32° W. 49 down  
Mkd. Alder 14" S. 12 $\frac{1}{2}$ ° W. 122 "  
Blazed Fir 30" N. 32° W. 969 "

Witnesses etc as  
above.

$\frac{1}{4}$  Sec. Cor. bet. secs. 32 & 33 T. 14 S. R. 8 W.  
Set a  $\frac{3}{4}$ " x 19" Iron rod. Orig. cor.  
Alder 12" in dia. bears S. 16° E. .72 std. (Bearings from Sec. line linked on both  
Firs 24" " " " " N. 13° W. 184 " .197 to cen. of tree.

Corner to sections 32, 33, 4 and 5, Twp. 14 and 15 S., R. 8 W. W. M.  
Reestablishment by W. C. Galloway

May 7, 1936

3261

Set 5/8" x 24" bolt

Alder 8" in diam bears S 31° E

Fir 14" in diam bears S 3½° W

Alder 14" in diam bears S 12½° W

Fir 8" in diam bears N 32° W

Fir 30" in diam bears N 32° W

02956  
.06 chains

.58 chains

.122 chains

.49 chains(down)

.969 chains

Witnesses W. D. Risley, Harold McCormick and Willis L. Buck