

148300600

DATE 06/19/2003TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 04 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):
SOUTHEAST OF SECTION 5
NORTHEAST OF SECTION 8
NORTHWEST OF SECTION 9


RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED JULY 3, 1856. SET POST FROM WHICH A FIR 40" DIA BEARS S67°W, 178 LINKS (117.48 FEET); A FIR 40" DIA BEARS S61°E, 176 LINKS (116.16 FEET); A FIR 24" DIA BEARS N1-1/2°W, 240 LINKS (158.40 FEET); AND A FIR 24" DIA BEARS N1-1/2°E, 243 LINKS (160.38 FEET).
- [02] BENTON COUNTY SURVEY NO. 555 (OLD NO. 126) FIELD NOTES (FIELD BOOK 21, PAGE 56) BY W. C. GALLOWAY, C.S., DATED JULY 12, 1916. SET 1" GALVANIZED PIPE. FOUND CHARRED WOOD (PT. STAKE) WITH ANGLES. FIR 40" DIA (GLO BT) BEARS S61°E, 1.76 CHAINS (116.16 FEET) STANDING. FIR 65" DIA BEARS N20°30'E, 2.326 CHAINS (153.52 FEET); CHERRY 6" DIA BEARS S70°40'W, CALCULATED 1.269 CHAINS (83.75 FEET); AND FIR 58" DIA BEARS N12°50'W, CALCULATED 2.123 CHAINS (140.12 FEET).
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 109 BY W. C. GALLOWAY, C.S., DATED JULY 12, 1916. SET 1" GALVANIZED PIPE. FOUND CHARRED WOOD WITH ANGLES OR AX MARKS. STAKE PRINT. FIR 40" DIA (GLO BT) BEARS S61°E, 1.76 CHAINS (116.16 FEET) STANDING. FIR 65" DIA (CSBT) BEARS N20°30'E, 2.326 CHAINS (153.52 FEET); CHERRY 6" DIA (CSBT) BEARS S70°40'W, 1.269 CHAINS (83.75 FEET); AND FIR 58" DIA (CSBT) BEARS N12°50'W, 2.118 CHAINS (139.79 FEET).
- [04] BENTON COUNTY CORNER RESTORATION NO. 2658. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY MAP NO. 14-8-00003 BY W. C. GALLOWAY, C.S., DATED APRIL 30, 1918. 1" GALVANIZED PIPE. FIR 65" DIA (CSBT) BEARS N20°30'E, 2.326 CHAINS (153.52 FEET) STUMP; FIR 40" DIA (GLO BT) BEARS S61°E, 1.76 CHAINS (116.16 FEET) STUMP; FIR 58" DIA (CSBT) BEARS N12°50'W, 2.118 CHAINS (139.79 FEET); MAPLE 22" DIA BEARS S59°14'W, 1.481 CHAINS (97.75 FEET); FIR 22" DIA BEARS S15°22'E, 1.260 CHAINS (83.16 FEET).
- [06] BENTON COUNTY SURVEY NO. 2305 BY CURTIS C. HANSON, C.S., AND MARTIN L. BEYERLEIN, D.C.S., DATED SEPTEMBER, 1951. FOUND GALVANIZED PIPE. FIR STUMP 65" DIA (CSBT) BEARS N20°30'E, 2.326 CHAINS (153.52 FEET); FIR STUMP 40" DIA (GLO BT) BEARS S6°E (SIC), 1.76 CHAINS (116.16 FEET); FIR 58" DIA (CSBT) BEARS N2°50'W (SIC), 2.118 CHAINS (139.79 FEET) STANDING; MAPLE 22" DIA BEARS S59°W, 1.481 CHAINS (97.75 FEET); FIR 22" DIA BEARS S15°22'E, 1.260 CHAINS (83.16 FEET).
- [07] BENTON COUNTY SURVEY NO. 4426 BY B. OSBURN SHAW, P.L.S., DATED JULY 27, 1967. FOUND 3/4" PIPE. SET 1/2" PIPE BEARS S0°44'E, 208.20 FEET, 2.5 FEET EAST OF FENCE. SET 1/2" PIPE BEARS S0°44'E, 237.50 FEET.
- [08] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY C. ALBERT WHITE, HARVEY E. WOFFORD AND STEPHEN D. ALBRIGHT, CADASTRAL SURVEYORS, DATED MAY 21, 1970. FOUND 1" PIPE EXTENDING 8" ABOVE GROUND FROM WHICH A SAWED AND ROTTED FIR STUMP 44" DIA (GLO BT) BEARS S61°E, 176 LINKS (116.16 FEET) WITH SCRIBE MARKS "T14S R8W S9" VISIBLE ON OPENED BLAZE; A ROTTED FIR SNAG (GLO BT) BEARS S67°W, 178 LINKS (117.48 FEET) WITH NO MARKS REMAINING; A SAWED FIR STUMP 65" DIA (CSBT) BEARS N20-1/2°E, 236 LINKS (155.76 FEET) WITH NO MARKS VISIBLE ON OPENED AND BURNED BLAZE; A SAWED FIR STUMP 22" DIA (CSBT) BEARS S15-1/4°E, 126 LINKS (83.16 FEET) WITH NO MARKS REMAINING. SET A 2-1/2" DIA IRON POST, 28" LONG, 24" IN THE GROUND WITH A BRASS CAP MARKED "T14S R8W S5 S4 S8 S9 1970" FROM WHICH A FIR 12" DIA BEARS N12°E, 38 LINKS (25.08 FEET) MARKED "T14S R8W S4 BT"; A FIR 16" DIA BEARS S81-3/4°E, 158 LINKS (104.28 FEET) MARKED "T14S R8W S9 BT"; A FIR 13" DIA BEARS S9-1/2°W, 18 LINKS (11.88 FEET) MARKED "T14S R8W S8 BT"; AND A FIR 11" DIA BEARS N24-1/2°W, 145 LINKS (95.70 FEET) MARKED "T14S R8W S5 BT". RESET IRON PIPE ALONGSIDE IRON POST.
- [09] STARKER FORESTS INC. SURVEY FILES CONTAIN A SECTION PLAT SHEET BY A. BLACHLY, DATED JULY 29, 1983. FOUND BLM IRON PIPE WITH BRASS CAP "1970" NEXT TO FOUND 3/4" IRON PIPE. OBSERVED NORTHEAST AND SOUTHEAST BEARING TREES TAGGED BY BLM. FOUND 1/2" THIN WALL IRON PIPE (S0°44'E, 208.20 FEET), FLUSH WITH GROUND, 2 FEET EAST OF FENCE ABOVE ROAD.
- [10] BENTON COUNTY SURVEY NO. 8676 BY JIM S. PETERSON, P.L.S., DATED JANUARY 15, 1993. FOUND 3" 1970 BLM BRASS CAP.
- [11] BENTON COUNTY SURVEY NO. 9260 BY JIM S. PETERSON, P.L.S., DATED NOVEMBER 11, 1997. FOUND 3" BRASS CAP WITH 1" IRON PIPE ALONGSIDE. FOUND A 44" ROTTED FIR STUMP (GLO BT) (S61°E, 176 LINKS) SCRIBING VISIBLE, ROTTED FIR STUB (GLO BT) (S67°W, 178 LINKS) NO MARKS VISIBLE, 65" FIR STUMP (CSBT) (N20-1/2°E, 236 LINKS) NO MARKS VISIBLE, 22" FIR STUMP (CSBT) (S15-1/4°E, 126 LINKS) AXE MARKS VISIBLE, 20" FIR (BLM BT) (N12°E, 38 LINKS) HEALED FACE, 26" FIR (BLM BT) (S9-1/2°W, 18 LINKS) HEALED FACE, 24" FIR (BLM BT) (S81-3/4°E, 158 LINKS) HEALED FACE, 26" FIR (BLM BT) (N24-1/2°W, 145 LINKS) HEALED FACE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 766-6821**RESEARCH BY:** BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.**DATA ENTRY BY:** BSA

CORNER RESTORATION BOOK NO. 1

- C.S. 251
 1/4 sec. cor. bet. secs. 11 & 12 T. 12 S. R. 7 W.
 Set 1" galv. pipe
 Fir 30" in dia. bears S. 75° E. 14" high stump
 " 20" " " West 10" " " or snag.
 Burnt fir 30" " N. 55° W. 140 to face.
 June 27, 1916.
- "
 Corner to secs. 11, 12, 13 & 14 T. 12 S. R. 7 W.
 Set 1 1/4" pipe in glass. SW ^{NW willow grove} " traces found N.E. fir stump.
 Fir 60" in dia. bears N. 71° E. 495 chs.
 " 40" " " S. 60° E. 2,555 " std.
 " 32" " " S. 46° W. 688 " "
 " 5" " " N. 63° 20' W. 190 " "
- "
 1/4 sec. cor. bet. secs. 12 & 13 T. 12 S. R. 7 W.
 Set 3/4" galv. pipe found stake lying down.
 Fir 48" in dia. bears N. 5° W. 1,30 chs. std.
 Cherry 6" " " S. 10° E. 34 " "
- "
 1/4 sec. cor. bet. secs. 1 & 12 T. 12 S. R. 7 W.
 Set 1 1/2" pipe & glass orig. cor. Both jumps std. TB. on cedar, check.
 W. Fir 17" in dia. bears S. 23° 40' W. 484 chs.
 " 22" " " N. 8° 40' W. 666 " "
- "
 Corner to secs. 4, 5, 8 & 9 T. 14 S. R. 8 W.
 Set 1" galv. pipe found charred wood with 2 or 3 marks. SHAK PRINT.
 Fir 65" in dia. bears N. 20° 30' E. 2,584 chs.
 " 40" " " S. 61° E. 176 " std.
 Cherry 6" " " S. 70° 40' W. 1,269 " "
 Fir 58" " " N. 12° 50' W. 2,118 " "
 Witness J. M. Spencer July 12, 1916.
- C.S. # 126
 Continued

- C.S. 252
 Interior corner of Jacob Holgate's D.L.C. # 43 T. 14 S. R. 7 W.
 Set ~~1 1/4" pipe in bottle. At 1/4 mile from out to rd. set from corners east.~~
~~Set from ash which is nearly lying flat, butt in ground.~~
~~Alder 3" N. 27° 23' E. 117 chs.~~
~~Bears N. 68° 15' W. 2,186 chs. washed out~~
~~Sept 12, 1914. S. 15° 18' W. 2,100 chs. set in gaps up on NW side~~
~~Willow 20" dia. and rotten N. 26° 25' W. 2,728~~
 Witnesses J.W. Bustert Finley Fullerton July 14, 1916.
 Sept. 7, 1914.
- C.S. Road # 379
 W.E. Wood witness
 Interior corner on E. line of Abiather Newton's D.L.C. # 42 T. 12 S. R. 5 W.
 Set a 2l. bottle
 Stone 6"x8"x14" East .66, SW of John Trapp C.I. # 38
 Oak 20" in dia. bears N. 42° 10' E. 2,144 chs. ^{THIS CORNER, THE OTHER CORNERS, BEARS.}
 Forked " 12"x16" " N. 27° 45' W. 612 " "
 July 22, 1916.
- "
 S.W. corner of John Trapp D.L.C. # 38 T. 12 S. R. 5 W.
 Stone 6"x8"x14"
 Oak 12" in dia. bears N. 26° E. 1,75 chs. std.
 Forked " 12"x16" " N. 60° 20' W. 1,090 " "
 July 22, 1916.

Corner to sections 4, 5, 8, and 9, Twp. 14 S., R. 8 W.

2658

Reestablishment by W. C. Galloway

July 12, 1916

Set 1" galvanized pipe, found charred wood with angles or ax marks. Stake print
Fir 65" in diam bears N 20° 30' E 2.526 chains
Fir 40" in diam bears S 61° E 1.76 chains (standing)
Cherry 6" in diam bears S 70° 40' W 1.269 chains
Fir 58" in diam bears N 12° 50' W 2.118 chains

Witness J. M. Spencer