

**148400100**

DATE 02/05/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 33 CORNER SOUTHEAST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

SOUTHWEST CORNER SECTION 34, TOWNSHIP 14 SOUTH, RANGE 8 WEST

NORTHWEST CORNER SECTION 3 AND NORTHEAST CORNER SECTION 4, TOWNSHIP 15 SOUTH, RANGE 8 WEST

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. SET MAPLE POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T14SR8WS34" ON THE NORTHEAST FACE, "T15SR8WS3" ON THE SOUTHEAST FACE, "S4" ON THE SOUTHWEST FACE, AND "S33" ON THE NORTHWEST FACE, WITH 3 NOTCHES ON THE EAST AND WEST EDGE, FROM WHICH A MAPLE 10" DIA BEARS S55°W, 212 LINKS (139.92 FEET), MARKED "T15S R8W S4 BT"; RED FIR 50" DIA BEARS N86°W, 64 LINKS (42.24 FEET), MARKED "T14S R8W S33 BT"; RED FIR 50" DIA BEARS N81°E, 123 LINKS (81.18 FEET), MARKED "T14S R8W S34 BT"; RED FIR 16" DIA BEARS S30-1/2°E, 236 LINKS (155.76 FEET), MARKED "T15S R8W S3 BT".
- [02] BENTON COUNTY SURVEY NO. 756 (OLD NO. 311) FIELD NOTES (FIELD BOOK 29, PAGE 9) BY WALTER W. LARSEN, D.C.S., DATED MARCH 21, 1921. SET 3" X 3" X 36" FIR STAKE. MAPLE 10" DIA (GLO BT) BEARS S55°W, 2.12 CHAINS (139.92 FEET), STANDING; FIR 50" DIA (GLO BT) BEARS N86°W, 0.64 CHAINS (42.24 FEET), DOWN; FIR 50" DIA (GLO BT) BEARS N81°E, 1.23 CHAINS (81.18 FEET), STANDING; FIR 16" DIA (GLO BT) BEARS S30-1/2°E, 2.36 CHAINS (155.76 FEET), STANDING.
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 151, BY WALTER W. LARSEN, D.C.S., NO DATE GIVEN. SET 3" X 3" X 36" FIR STAKE. MAPLE 10" DIA (GLO BT) BEARS S55°W, 2.12 CHAINS (139.92 FEET), STANDING; FIR 50" DIA (GLO BT) BEARS N86°W, 0.64 CHAINS (42.24 FEET), DOWN; FIR 50" DIA (GLO BT) BEARS N81°E, 1.23 CHAINS (81.18 FEET), STANDING; FIR 30" DIA (GLO BT) BEARS S30-1/2°E, 2.36 CHAINS (155.76 FEET), STANDING.
- [04] BENTON COUNTY CORNER RESTORATION NO. 2653. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY SURVEY NO. 756 (OLD NO. 311) BY WALTER W. LARSEN, D.C.S., DATED APRIL 1, 1921. FIR POST. MAPLE 10" DIA (GLO BT) BEARS S55°W, 2.12 CHAINS (139.92 FEET); FIR 50" DIA (GLO BT) BEARS N86°W, 0.64 CHAINS (42.24 FEET), DOWN; FIR 50" DIA (GLO BT) BEARS N81°E, 1.23 CHAINS (81.18 FEET); FIR 16" DIA (GLO BT) BEARS S30-1/2°E, 2.36 CHAINS (155.76 FEET).
- [06] BENTON COUNTY MAP NO. 15-8-00004 BY WALTER W. LARSEN, D.C.S., DATED APRIL 1, 1921. FIR STAKE 3" X 3". MAPLE 10" DIA (GLO BT) BEARS S55°W, 2.12 CHAINS (139.92 FEET), STANDING; FIR 50" DIA (GLO BT) BEARS N86°W, 0.64 CHAINS (42.24 FEET), DOWN; FIR 50" DIA (GLO BT) BEARS N81°E, 1.23 CHAINS (81.18 FEET), STANDING; FIR 16" DIA (GLO BT) BEARS S30-1/2°E, 2.36 CHAINS (155.76 FEET), STANDING.
- [07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY HARVEY E. WOFFORD, CADASTRAL SURVEYOR, DATED APRIL 29, 1968. CORNER MONUMENTED WITH AN IRON PIPE, 3/4" DIA, FIRMLY SET, PROTRUDING 2" ABOVE GROUND, FROM WHICH A FIR STUMP 64" DIA (GLO BT) BEARS N81°E, 123 LINKS (81.18 FEET), WITH NO MARKS VISIBLE ON OPENED BLAZE; FIR 51" DIA (GLO BT) BEARS S30-1/2°E, 236 LINKS (155.76 FEET), WITH NO MARKS VISIBLE ON OPEN BLAZE; MAPLE 33" DIA (GLO BT) BEARS S55°W, 212 LINKS (139.92 FEET), WITH HEALED BLAZE; FIR SNAG 60" DIA (GLO BT) BEARS N86°W, 64 LINKS (42.24 FEET), WITH NO MARKS VISIBLE ON OPEN BLAZE; FIR SNAG 25" DIA BEARS N32°E, 21-1/2 LINKS (14.19 FEET), WITH SCRIBE MARKS "3 T" VISIBLE ON OPEN BLAZE; FIR 30" DIA BEARS S40°W, 18 LINKS (11.88 FEET), WITH NO MARKS VISIBLE ON OPEN BLAZE. SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, DIRECTLY OVER THE IRON PIPE, WITH BRASS CAP MARKED "T14S R8W S33 S34 S4 S3 T15S 1968" FROM WHICH A CEDAR 13" DIA BEARS N41°E, 134 LINKS (88.44 FEET), MARKED "T14S R8W S34 BT"; FIR 20" DIA BEARS N76-1/2°W, 168 LINKS (110.88 FEET), MARKED "T14S R8W S33 BT".
- [08] BENTON COUNTY SURVEY NO. 6158 BY GARY T. JOHNSTON, P.E., DATED JUNE, 1976. FOUND BLM BRASS CAP.
- [09] BENTON COUNTY SURVEY NO. 7178 BY NORMAN D. SPRINGER, P.L.S., DATED OCTOBER 30, 1980. FOUND BLM BRASS CAP.
- [10] BENTON COUNTY SURVEY NO. 7407 BY GARY T. JOHNSTON, P.L.S., DATED APRIL 28, 1982. FOUND 1960 BLM BRASS CAP.
- [11] BENTON COUNTY CORNER RESTORATION NO. 2766 BY GARY T. JOHNSTON, LOGGING ENGINEER, DATED JUNE 22, 1982. FOUND 1960 BLM BRASS CAP. CEDAR 16" DIA (BLM BT) BEARS N41°E, 134 LINKS (88.44 FEET), PARTIALLY HEALED AND FACE ROTTEN; FIR 24" DIA (BLM BT) BEARS N76-1/2°W, 168 LINKS (110.88 FEET), HEALED OVER FACE; FIR 62" DIA (GLO BT) BEARS S30-1/2°E, 236 LINKS (155.76 FEET), OPEN BLAZE NO MARKS; BIG LEAF MAPLE 36" DIA (GLO BT) BEARS S55°W, 212 LINKS (139.92 FEET), HEALED BLAZE IN CLUMP OF TWO MAPLES; FIR SNAG 60" DIA (GLO BT) BEARS N86°W, 64 LINKS (42.24 FEET), OPEN BLAZE NO MARKS.
- [12] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY STEPHEN D. HARDIN AND FRANK A. TUERS, CADASTRAL SURVEYOR, DATED OCTOBER 30, 1989. CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 3" ABOVE GROUND, WITH BRASS CAP MARKED "T14S R8W S33 S34 S4 S3 T15S 1968" FROM WHICH A FIR STUMP, SIZE INDETERMINATE, (GLO BT) BEARS N81°E, 125 LINKS (82.50 FEET), NO MARKS VISIBLE; FIR 53" DIA (GLO BT) BEARS S30-1/2°E, 236 LINKS (155.76 FEET), WITH HEALED BLAZE; MAPLE 33" DIA (GLO BT) BEARS S55°W, 215 LINKS (141.90 FEET), WITH HEALED BLAZE; FIR SNAG, SIZE INDETERMINATE, (GLO BT) BEARS N86°W, 64 LINKS (42.24 FEET), NO MARKS VISIBLE; FIR STUMP 25" DIA BEARS N32°E, 20-1/2 LINKS (13.53 FEET), NO MARKS VISIBLE; FIR 37" DIA BEARS S40°E, 18 LINKS (11.88 FEET), WITH HEALED BLAZE; CEDAR 18" DIA (BLM BT) BEARS N38-1/2°E, 134 LINKS (88.44 FEET), WITH HEALED BLAZE; FIR 26" DIA (BLM BT) BEARS N76°W, 167 LINKS (110.22 FEET), WITH HEALED BLAZE.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821**RESEARCH AND DATA ENTRY BY:** DAVID L. MALONE, P.L.S.

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

2766

T 14 S, R 8 W, W. B. & M., BENTON COUNTY, OREGON

REPORTED BY Gary T. Johnston


SECTION 33

The information shown hereon was taken from  
the referenced county survey. Date: 7/30/80

TITLE Logging Engineer

DATE June 22, 1982

SEE C.S. #7407



● OFFICIAL CORNER FOUND

○ CORNER SET

SEC. CORNER COMMON TO SEC. 33, 34, 3 & 4  
is 1960 BLM Brass Cap  
DESCRIBE

ADDITIONAL INFORMATION

5th Bearing Tree 60" fir snag  
N 86 W 64 Lks.  
Open blaze no marks  
with BLM tag

Area to NE of corner has been logged and  
cleared this spring

OVER

LEGIBLE MARKS ON BEARING OBJECTS

	Partially healed and face rotten	Healed over face	Open Blaze no marks	Healed Blaze in clump of two maples
KIND	Cedar	Fir	Fir	Big leaf Maple
SIZE	13" now 16"	20" now 24"	51" now 62"	33" now 36"
BEARING	N 41 E	N 76½ W	S 30½ E	wlw Lks.
DISTANCE	134 Lks.	168 Lks.	236 Lks.	555 W
BT TAG POSTED	NO	BLM	BLM	BLM

C.S. 311

Sec. cor. betw sees. 2, 4, 33, 34 T 14+15 S R 8 W  
 Set 3x3x106" fir sth.  
 Maple 10" in dia. bears S 33° W. 2.12 chs  
 Fir 50" " " " N 86° W 167 " down  
 " 50" " " " N 81° E. 1.23 " std.  
 " 50" " " " S 30 1/2° E 2.36 " "



C.S. 311  
 Witnesses  
 Roy Van Pelt  
 H. Salyer  
 Butcher  
 Collins  
 Chas. Jordan  
 Puthor.

1/4 cor. betw. sees. 3+2 T 14+15 S R 8 W  
 Set. Stone 6"x6"x4" marked X  
 Fir 14" in dia bears N 18° 15' E .544 chs  
 " 6" " " " S 16° W .118 std.  
 " 10" " " " S. 57° E. .11 "

Sec. cor. betw Secs. 2, 3, 34, 35 T 14+15 S R 8 W.  
 Set Stone 4"x4"x3" and fir knot marked.  
 Fir 6" in dia bears N 76° W .51 chs  
 " 6" " " " N 104 1/2° E .378 "  
 Burnt fir 3 1/2" in " N 37 1/2° E .958 std.  
 " " 48 " " N 28° W. .94 "  
 Both alders gone.

C.S. 218 con.  
 Witnesses.  
 Geo. Coon  
 Tom

W.C. to Meander cor. <sup>North of Sec cor betw sees 19, 24, 25, 30</sup>  
<sup>27.9-37.2 27.102</sup> T 13 S R 4+5 W.  
 Set 1" angle x 30"  
 White Fir 8" in dia S 6° 30' W 1.425 chs  
 " " 32" " " S 47° W 1.328 "

1/4 cor betw. Secs. 19+24 T 13 S R 4+5 W.  
 Set 1 1/2" x 40" pipe  
 Ash 8" in dia. bears S 40° E. 1.328 chs  
 Balm 30" " " " N 77° E 1.070 "

at 69.542 S.E. Int. cor. Able. Hulburt Ct. 60 T 13 S R 4+5 W  
 Set 1" angle iron x 30"  
 Ash 24" in dia bears N 32° W. .272 chs  
 Oak 14" " " " S 33° W. .350 "

Witness cor to see.  
 (see 131.1303) Sec. cor betw sees. 13, 18, 24, 19 T 13 S R 4+5 W  
 Set 5"x5"x24" pipe pitch stake 1.156 N of cor.  
 Fir 24" in dia bears S 45° 45' W .137 chs  
 " 22 " " " N 60° 45' W .365 "  
 " 22 " " " N 18° 15' E .390 "  
 Oak 6" " " " S 78° 45' E .186 "

W.C. to 1/4 cor. betw. sees 15, 18 T 13 S R 4+5 W W.M.  
 Set Flow stake - E side is 45° E of 1/4 cor  
 Maple 14" in dia bears S 89° 30' E 2.250  
 " " " " " N 53° 15' E 2.066  
 No reason for setting cor this way but  
 was due to misreading tape.

Section corner between sections 3, 4, 33 and 34, Twp. 14 and 15 S ~~26.58~~ W.

Reestablishment by W. C. Galloway

1921

3138

Set 3" x 3" x 36" Fir stake

Maple 10" in diam bears S 55° W	2.12 chains (standing)
Fir 50" in diam bears N 86° W	.64 chains (down)
Fir 50" in diam bears N 81° E	1.23 chains (standing)
Fir 30" in diam bears S 30 $\frac{1}{2}$ ° E	2.36 chains (standing)

Witnesses George Hendrix, Ethan Hendrix and Jesse Cook