

**148400700**

DATE 10/26/2020TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 3 CORNER NORTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**NORTHEAST CORNER SECTION 4, TOWNSHIP 14 SOUTH, RANGE 8 WEST  
POINT ON SOUTH LINE SECTION 34, TOWNSHIP 13 SOUTH, RANGE 8 WEST**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED SEPTEMBER 10, 1856. *SET STANDARD CORNER FROM WHICH A CHINKAPIN 8" DIA BEARS S31°E, 48 LINKS (31.68 FEET); FIR 50" DIA BEARS S68°W, 50 LINKS (33.00 FEET).*
- [02] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. *FOUND A POST GREATLY DECAYED. DESTROYED THE OLD POST AND IN ITS PLACE SET A FIR POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T14S S3" ON SOUTHEAST FACE AND "R8W S4" ON SOUTHWEST FACE, WITH 3 NOTCHES ON EAST AND WEST EDGES, FROM WHICH THE BEARING TREES ARE AS DESCRIBED BY THE SURVEYOR GENERAL WITH WELL-DEFINED BLAZES. REMOVED GROWTH OF WOOD OVER MARKINGS ON BEARING TREE IN SECTION 4 TO MAKE THE SAME NOTICEABLE.*
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. *THE STANDARD CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A CHINQUAPIN OAK 14" DIA (GLO BT) BEARS S31°E, 48 LINKS (31.68 FEET), WITH A WEATHERED FACE IN A PARTIALLY HEALED BLAZE; SAWED FIR STUMP 60" DIA (GLO BT) BEARS S68°W, 50 LINKS (33.00 FEET), WITH AN OPENED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "S4 S3 T14S R8W SC 1960" FROM WHICH A FIR 24" DIA BEARS S74°E, 36 LINKS (23.76 FEET), MARKED "T14S R8W S3 SC BT"; FIR 18" DIA BEARS S25°W, 21 LINKS (13.86 FEET), MARKED "T14S R8W S4 SC BT".*
- [04] BENTON COUNTY SURVEY NO. 4734 BY HOWARD E. TAYLOR, P.E., DATED FEBRUARY 25, 1969. *FOUND GLO 1957 BRASS CAP. FIR 50" DIA (GLO BT) BEARS S68°W, 33.0 FEET, NOW STUMP.*
- [05] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY C. ALBERT WHITE, HARVEY E. WOFFORD, AND STEPHEN D. ALBRIGHT, CADASTRAL SURVEYORS, DATED MAY 21, 1970. *THE STANDARD CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, EXTENDING 6" ABOVE THE GROUND, MARKED AND WITNESSED AS DESCRIBED IN THE OFFICIAL RECORD OF THE 1960 REMONUMENTATION.*
- [06] BENTON COUNTY SURVEY NO. 6508 BY GARY T. JOHNSTON, P.L.S., DATED OCTOBER, 1977. *FOUND BRASS CAP.*
- [07] BENTON COUNTY SURVEY NO. 6618 BY GARY T. JOHNSTON, P.L.S., DATED APRIL, 1978. *FOUND BRASS CAP.*
- [08] BENTON COUNTY SURVEY NO. 9280 BY ROYCE HILL, P.L.S., DATED MARCH 18, 1998. *FOUND 2-1/2" IRON POST, FIRMLY SET, 4" ABOVE GROUND WITH 3-1/4" BRASS CAP MARKED "T13S S34 S4 S3 SC T14S R8W 1960", FROM WHICH CHINQUAPIN OAK SNAG 14" DIA (GLO BT) BEARS S31°E, 31.78 FEET TO A NAIL SET SIDE AND CENTER, WITH MOSTLY DECAYED OPEN BLAZE, NO MARKS VISIBLE; DOUGLAS FIR STUMP 60" DIA (GLO BT) BEARS S68°W, 33.0 FEET, WITH PARTIALLY HEALED AND OPENED BLAZE, NO MARKS VISIBLE; DOUGLAS FIR WINDFALL 30" DIA (BLM BT) BEARS S74°E, 23.8 FEET, WITH BURIED FACE; DOUGLAS FIR 37" DIA (BLM BT) BEARS S25°W, 13.9 FEET, WITH HEALED BLAZE; YEW 16" DIA BEARS S79°E, 44.82 FEET TO A NAIL SET SIDE AND CENTER, WITH A 3/4" BRASS WASHER MARKED "LS 2289" TACKED TO THE FACE, MARKED "T14SR8WS3SCBT"; HEMLOCK 6" DIA BEARS S64-1/4°W, 28.96 FEET TO A NAIL SET SIDE AND CENTER, WITH A 3/4" BRASS WASHER MARKED "LS 2289" TACKED TO THE FACE, MARKED "T14SR8WS4SCBT"; ALDER 10" DIA BEARS N71-1/2°W, 39.58 FEET TO A NAIL SET SIDE AND CENTER, WITH A 3/4" BRASS WASHER MARKED "LS 2289" TACKED TO THE FACE, BARK SCRIBED "XBT". A 6 FOOT BY 1/2" WHITE FIBERGLASS POST BEARS WEST, 1 FOOT.*
- [09] BENTON COUNTY SURVEY NO. 10799 BY ROBERT ALAN COOK, P.L.S., DATED NOVEMBER 30, 2016. *FOUND 1960 BLM BRASS CAP UP 5". D. FIR 50" DIA BEARS S25°W, 13.9 FEET, WITH HEALED FACE; D. FIR 15" DIA BEARS S64°15'W, 29.0 FEET, WITH HEALED FACE; ALDER 12" DIA BEARS N71°30'W, 39.6 FEET.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME