

148640100

DATE 07/16/2019

TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 36 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):

NORTH 1/4 CORNER SECTION 1, TOWNSHIP 15 SOUTH, RANGE 8 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 25, 1891. *SET FIR POST 4 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON NORTH FACE, FROM WHICH AN ALDER 10" DIA BEARS N82°E, 77 LINKS (50.82 FEET), MARKED "1/4S BT"; RED FIR 6" DIA BEARS S80°W, 26 LINKS (17.16 FEET), MARKED "1/4S BT".*
- [02] BENTON COUNTY SURVEY NO. 7434 BY THEODORE JAMES LANGTON, P.L.S., DATED JULY 28, 1982. *SET 8 PENNEY NAIL WITH 1" SHINER IN TOP OF DOWNED 24" FIR LOG THAT LAYS NORTH AND SOUTH ON A STEEP SLOPE APPROXIMATELY 70 FEET WEST OF RAVINE ON SOUTH EDGE OF CLEARCUT. SET 5/8" X 30" REBAR WITH YELLOW PLASTIC CAP STAMPED "NORTH STAR" BEARS N79°08'36"W, 2.50 FEET, AS REFERENCE TO THE TRUE CORNER. SET (REFERENCED TO TRUE CORNER) ALDER 23" DIA BEARS N55°E, 7.9 FEET, BARK SCRIBED "X" OVER "BT"; MAPLE 19" DIA BEARS S58-1/2°E, 7.9 FEET, BLAZED AND SCRIBED "N1/4 S1 BT".*
- [03] BENTON COUNTY CORNER RESTORATION NO. 2943. *TRANSCRIBED FROM RECORD [02] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME


BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

02043

T. 15 S, R. 8 W, W. B. & M., BENTON COUNTY, OREGON

REPORTED BY Bill Lauer
 TITLE Northstar Surveying Inc
 DATE 8/16/82

SECTION 1



- OFFICIAL CORNER FOUND
- CORNER SET

1/4 CORNER COMMON TO SEC. 36 &
 IS S Penney nail w/ 1" spiner in
DESCRIBE 24" fir log

ADDITIONAL INFORMATION

The corner lies on a steep
slope ~ 70' W of a ravine on
the S-edge of a clearing.
A 5/8" rebar w/ "Northstar" cap
lies N 79° 08' 36" W, 2.50' as
reference to the true corner

see C.S. 7434

LEGIBLE MARKS ON BEARING OBJECTS

<u>set</u>			
<u>X</u>	<u>N 1/4</u>		
<u>BT</u>	<u>S 1</u>		
	<u>BT</u>		
KIND	<u>Alder</u>	<u>Maple</u>	
SIZE	<u>23"</u>	<u>19"</u>	
BEARING	<u>N 55° E</u>	<u>S 58 1/2° E</u>	
DISTANCE	<u>7.9'</u>	<u>7.9'</u>	
BT TAG POSTED	<u>10</u>	<u>10</u>	

OVER