

S. HARDIN / F. TUERS. 1986

7  
113

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A dogwood, 7 ins. diam., bears S. 58½° E., 46½ lks. dist., mkd. T14S R7W S31 BT on bark.</p> <p>S. 88° 41' 00" W., bet. secs. 25 and 36, marking and blazing the true line.</p> <p>Descend over gentle W. slope, through moderate timber and undergrowth.</p>
17.25	Bummer Creek, 15 lks. wide, course N. 35° W.; asc. over steep NE. slope.
18.615	An original line tree, a fir, 63 ins. diam., in good condition, with 2 notches on E. and W. sides. This now becomes an angle point.
	from which
	<p>A stainless steel post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 21° 22' W., 23.2 lks. dist., with brass cap mkd. RM AP S36 1986 and an arrow pointing to the angle point.</p> <p>A fir, 38 ins. diam., bears N. 81½° W., 36 lks. dist., mkd. AP S25 BT.</p> <p>Deposit: a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
	N. 89° 50' 00" W., beginning new measurement.
	Ascend over steep NE. slope.
1.345	Point for the E 1/16 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>E 1/16 S 25 S 36 1986</p>
	from which bearing tree mkd. by Wiljo E. Green, Registered Land Surveyor No. 563, in 1978
	A fir, 40 ins. diam., bears S. 20½° E., 84 lks. dist., with healed blaze.

148663200  
→