

**148840060**

DATE 01/06/2021

TOWNSHIP 14 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 3 CORNER N/A  
DONATION LAND CLAIM EMERSON REDNOR NO. 40 CORNER NORTH-NORTHWEST

**COMMON CORNER(S):**

NONE

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE EMERSON REDNOR DONATION LAND CLAIM (DLC) NO. 40 BY DENNIS HATHORN, D.S., DATED JULY 7, 1856. *SET POST FROM WHICH AN OAK 18" DIA BEARS N87-1/2°W, 219 LINKS (144.54 FEET); ASH 9" DIA BEARS S88-1/2°E, 700 LINKS (462.00 FEET).*
- [02] BENTON COUNTY SURVEY NO. 542 (OLD NO. 248) FIELD NOTES (FIELD BOOK 20, PAGE 67) BY W. C. GALLOWAY, C.S., DATED FEBRUARY 22, 1916. *SET AN IRON 1" X 30". OAK 15" DIA BEARS S35°30'W, 0.140 CHAINS (9.24 FEET); OAK 18" DIA (GLO BT) BEARS S87°30'W, 2.19 CHAINS (144.54 FEET), STANDING.*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 103, BY W. C. GALLOWAY, C.S., DATED FEBRUARY 22, 1916. *SET 1" X 30" IRON. OAK 15" DIA (CSBT) BEARS S35°30'W, 0.140 CHAINS (9.24 FEET); OAK 18" DIA (GLO BT) BEARS S87°30'W, 2.19 CHAINS (144.54 FEET), STANDING.*
- [04] BENTON COUNTY CORNER RESTORATION NO. 2807. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY MAP NO. 14-8-00002 BY W. C. GALLOWAY, C.S., DATED APRIL 17, 1916. *1" X 30" IRON. OAK 15" DIA (CSBT) BEARS S35°30'W, 0.140 CHAINS (9.24 FEET); OAK 18" DIA (GLO BT) BEARS S87°30'W, 2.19 CHAINS (144.54 FEET), STANDING.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

CS. 4245

Most North N.W. corner of E. Redmout Cl. #40 T. 14 S. R. 8 W.  
Set 1" x 30" iron

Oak 15" in dia. bears S. 35° 30' W. 1400 lbs.  
" 18" " " " S. 87° 30' W. 219 " std.

Witnesses as last cor.

Feb. 22, 1916.

N.E. corner of E. Redmout Cl. #40 T. 14 S. R. 8 W.

Set 1 1/4" pipe 3" under surface set from line

Oak 15" in dia. bears N. 2° 22' E. 3.484 lbs.

" 10 " " " S. 89° W. 2.972 "

Fir 48" " " " West at s. edge of bark 3.885 lbs.

Witnesses as last corner

Feb. 23, 1916.

S.E. corner of E. Redmout Cl. #40 T. 14 S. R. 8 W.

Set 1/2" iron rod with glass

Oak 18" S. 5° 25' E. 5.635 lbs.

Remkd. Ash 9" in dia. bears S. 9° 44' W. 5.44 " std.

Witnesses as above + W.D. Risley.

Feb. 23, 1916.

Corner to secs. 10, 11, 14 & 15 T. 14 S. R. 8 W.

Set Qt. bottle F.

Fir 24" in dia. bears N. 36° 40' E. 1.954 lbs.

Alder 9" " " " S. 58° 15' W. 1.767 "

orig. Fir 24" " " " S. 72° 30' W. 1.726 "

orig. " 36" " " " N. 38° W. 1.41 " std.

Witnesses Edd. Taylor &amp; D.P. Loughbottom

Feb. 24, 1916.

1/4 sec. cor. between secs. 10 & 15 T. 14 S. R. 8 W.

Set Qt. bottle

Orig. fir 50" in dia. bears N. 55° E. 1.00 lbs. std.

" maple 12" " " " S. 62° W. 1.70 " "

Witnesses and date as above

1/4 sec. cor. between secs. 3 & 10 Tp. 14 S. R. 8 W.

Set a 1/2" x 2" x 10" iron pin. set from sec. cor.

Oak 12" in dia. bears N. 58° 11' W. 2.517 lbs.

Fir 16" " " " N. 56° 51' W. 2.036 "

Witnesses Edd. Taylor, Carl Ragsdale Mar. 2, 1916

Cor. to secs. 2, 3, 10 & 11 Tp. 14 S. R. 8 W.

Set 3/4" gal. pipe 2" under surface.

a 3/4" pipe at s. side of road bears S. 0° 05' E. 6.936<sup>lbs</sup> a stone bears N. 0° 05' W. 14357<sup>lbs</sup>

Witnesses Edd. Taylor, Carl Ragsdale, W.D. Risley, Mar. 2, 1916

1/4 sec. cor. on the north side of sec. 3, (3rd std. Parallel) Tp. 14 S. R. 8 W.

Set 3/4" x 36" gal. pipe. original cor. sec.

Double fir 30" in dia. bears S. 30° E. 1.22 lbs. Remkd. dead.

" 15" " " " S. 85° W. 1.214 " "

" 6" " " " N. 17° W. 1.074 " "

Witnesses Edd. Taylor &amp; Carl Ragsdale

Most north N. W. corner of E. Redmour cl 40, Twp. 14 S., R. 8 W.

2807

Reestablishment by W. C. Galloway

February 22, 1916

Set 1" x 30" iron

Oak 15" in diam bears S 35° 30' W

.140 chains

Oak 18" in diam bears S 87° 30' W

2.19 chains(standing)

Witnesses Edd Taylor, D. D. Longbottom, C. S. Seely