

149500300

DATE 10/19/2023TOWNSHIP 14 SOUTH, RANGE 9 WEST, WILLAMETTE MERIDIAN; SECTION 22 CORNER SOUTHEAST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER OF SECTION 23
NORTHWEST CORNER OF SECTION 26
NORTHEAST CORNER OF SECTION 27**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JUNE 15, 1892. SET SAND STONE 15" X 9" X 8", 10" IN THE GROUND, MARKED "T14SS23" ON THE NORTHEAST FACE, "R9WS26" ON THE SOUTHEAST FACE, "S27" ON THE SOUTHWEST FACE, AND "S22" ON THE NORTHWEST FACE, WITH 2 NOTCHES ON THE SOUTH AND EAST EDGES, FROM WHICH A RED FIR 28" DIA BEARS N37°E, 30 LINKS (19.80 FEET), MARKED "T14SR9WS23BT"; FIR 30" DIA BEARS S67°E, 31 LINKS (20.46 FEET), MARKED "T14SR9WS26BT"; ALDER 10" DIA BEARS S21-1/2°W, 27 LINKS (17.82 FEET), MARKED "T14SR9WS27BT"; RED FIR 20" DIA BEARS N33°W, 12 LINKS (7.92 FEET), MARKED "T14SR9WS22BT".
- [02] BENTON COUNTY SURVEY NO. 7373 BY JAMES W. PROCHNAU, P.L.S., DATED JANUARY 15, 1982. SET 3-1/4" ALUMINUM CAP IN 2-1/4" X 30" ALUMINUM PIPE WITH FLARED BOTTOM – ROCK MOUND. FOUND D. FIR STUMP 46" DIA (GLO BT) BEARS N37°E, 19.8 FEET; D. FIR STUMP 42" DIA (GLO BT) BEARS S55°E, 20.5 FEET; FIR STUMP 31" DIA (GLO BT) BEARS N27°W, 17.5 FEET. NORTHWEST BEARING TREE NOT CONSIDERED IN LOCATING CORNER POSITION (GROSSLY OFF CALL). SET REFERENCE MONUMENT 2-1/2" BRASS CAP IN 1" GALVANIZED IRON PIPE BEARS S45°W, 75.0 FEET. CAPS STAMPED PER BLM MANUAL PLUS THE TOWNSHIP, RANGE, 1981 AND PLS 1305.
- [03] BENTON COUNTY SURVEY NO. 7540 BY JIM S. PETERSON, P.L.S., AND NORMAN D. SPRINGER, P.L.S., DATED JUNE 6, 1983. FOUND 3" ALUMINUM CAP ON 2" ALUMINUM PIPE, MARKED "T14S R9W S22 S23 S27 S26 1981 PLS 1305". FOUND FIR STUMP 31" DIA (GLO BT) BEARS N27°W, 19.1 FEET, SCRIBING VISIBLE; FIR STUMP 46" DIA (GLO BT) BEARS N37°E, 20.5 FEET, NO MARKS; FIR STUMP 42" DIA (GLO BT) BEARS S55°E, 21.1 FEET, SCRIBING VISIBLE. REFERENCE MONUMENT BRASS CAP MARKED "T14S R9W S27 RM 1982 PLS 1305" BEARS S47°W, 74.9 FEET.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME