

N. PRICE / O. DAVELSBERG 1940

4-673D

28

32

Dependent Resurvey of the W. Bdy. of T. 15 S., R. 6 W.

- Chains.
- A fir, 36 ins. diam., bears N. 31° W., 58 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
 - A fir, 26 ins. diam., bears S. 89° W., 46 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
- Desc. 90 ft. over NW. slope.
- 40.10 A ravine, course SW.; asc. 15 ft. over SW. slope.
 - 40.32 Point for $\frac{1}{4}$ sec. cor. of sec. 18 only, determined by reference to bearings and distances of two original bearing trees.
- At point for corner,
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 18 only, with brass cap mkd.
- S18
1940
- from which
- A fir, 26 ins. diam., bears S. 40° E., 8 lks. dist., blaze healed. (Old B.T.)
 - A fir, 20 ins. diam., bears N. 52° W., 12 lks. dist., mkd. B T and other partial scribe marks on face of old badly weathered blaze, which I destroy. (Old B.T.)
 - A fir, 20 ins. diam., bears N. 51 $\frac{1}{2}$ ° E., 48 lks. dist., mkd. $\frac{1}{4}$ S 18 B T. (New B.T.)
- Thence
- N. 0° 04' E., continuing my measurement.
 - Asc. 16 ft. over SW. slope.
 - 42.60 A ravine, course SW.; asc. 333 ft. over SE. slope.
 - 50.60 A spur, slopes SW.; desc. 85 ft. over NW. slope.
 - 54.40 A ravine, course SW.; asc. 200 ft. over S. slope.
 - 61.00 A ridge, bears E. and W.; desc. 123 ft. over NE. slope.
 - 64.80 A ravine, course E.; asc. 15 ft. over broken E. slope.
 - 68.50 Confluence of branches, course E., 3 lks. wide, from W. 1 lk. wide and NW. 2 lks. wide; asc. 255 ft. over S. slope.
 - 80.89 Point for cor. of secs. 7, 12, 13, and 18, determined with reference to the record of the distances from the SE., SW., and NW. bearing trees.
- At point for corner,
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7, 12, 13, and 18, with brass cap mkd.

156100500

| | |
|---------|--|
| 4-673b | 29 |
| | 33 |
| Chains. | <p style="text-align: center;">T158 R7W/R6W S12/S7 S13/S18 1940</p> <p style="text-align: right;">from which</p> <p>A fir, 22 ins. diam., bears S. 86° E., 122 lks. dist., blaze healed, re-blazed and re-marked T 15 S R 6 W S 18 B T. (Old B.T.)</p> <p>A fir, 40 ins. diam., bears S. 53° W., 86 lks. dist., blaze healed, re-blazed and re-marked T 15 S R 7 W S 13 B T. (Old B.T.)</p> <p>A fir, 50 ins. diam., bears S. 56° W., 47 lks. dist., scribe marks on partly healed old blaze. (Old B.T.)</p> <p>A fir snag, 34 ins. diam., bears N. 31° W., 49 lks. dist., mkd. R 7 W T 15 S S 12 B T. (Old B.T.)</p> <p>A fir, 28 ins. diam., bears N. 87½° E., 126 lks. dist., mkd. T 15 S R 6 W S 7 B T. (New B.T.)</p> <p>A fir, 44 ins. diam., bears N. 74° W., 44 lks. dist., mkd. T 15 S R 7 W S 12 B T. (New B.T.)</p> <p>Land, mountainous. Soil, sandy and rocky loam; 3rd and 4th rate. Timber, fir, hemlock, cedar, maple, and alder. Undergrowth, vinemapple, salal, salmonberry, and hazel.</p> <hr/> <p>N. 0° 07' W., along the W. bdy. of sec. 7.</p> <p>Asc. 12 ft. over S. slope, through heavy timber and dense undergrowth.</p> <p>1.70 A ridge, bears E. and W.; desc. 171 ft. over NW. slope.</p> <p>13.10 A logging road, bears N. 60° E. and S. 45° W.</p> <p>22.60 A branch, 5 lks. wide, course SE.; asc. 260 ft. over S. slope; enter logged over area, bears NW. and SE.</p> <p>30.60 Leave logged over area, enter heavy timber and dense undergrowth, bears NW. and SE.</p> <p>40.40 Point for ¼ sec. cor. of sec. 7 only, T. 15 S., R. 6 W., determined by reference to the record distances from two original bearing trees.</p> <p>At point for corner,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 7 only, with brass cap mkd.</p> <p style="text-align: center;">¼ S7 1940</p> <p style="text-align: right;">from which</p> <p>A fir, 30 ins. diam., bears N. 55° W., 96 lks. dist., mkd. ¼ S B T. Marks obliterated. (Old B.T.)</p> <p>A fir, 16 ins. diam.; bears S. 13° E., 38 lks.</p> |