

156100600

DATE 01/24/2017**TOWNSHIP 15 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER SOUTHWEST DONATION LAND CLAIM N/A _____ CORNER N/A _____****COMMON CORNER(S):**NORTHWEST CORNER SECTION 7, TOWNSHIP 15 SOUTH, RANGE 6 WEST
POINT ON EAST LINE OF SECTION 12, TOWNSHIP 15 SOUTH, RANGE 7 WEST**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)****BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.**

- [01] GENERAL LAND OFFICE (GLO) NOTES BY KIMBALL WEBSTER, D.S., DATED JUNE 15, 1854. SET POST FROM WHICH A DOGWOOD 7" DIA BEARS **S19°E, 21 LINKS (13.86 FEET)**; A YEW 10" DIA BEARS **N73-1/2°E, 71 LINKS (46.86 FEET)**; A FIR 12" DIA BEARS **N69°W, 119 LINKS (78.54 FEET)**; A FIR 36" DIA BEARS **S53°W, 48 LINKS (31.68 FEET)**.
- [02] GENERAL LAND OFFICE (GLO) NOTES BY GEORGE MERCER, D.S., DATED JUNE 30, 1883. POST AND TREES STILL STANDING AS FOLLOWS: A DOGWOOD 7" DIA (GLO BT) BEARS **S19°E, 21 LINKS (13.86 FEET)**; A YEW 10" DIA (GLO BT) BEARS **N73-1/2°E, 71 LINKS (46.86 FEET)**; A FIR 12" DIA (GLO BT) BEARS **N69°W, 119 LINKS (78.54 FEET)**; A FIR 36" DIA (GLO BT) BEARS **S55°W, 48 LINKS (31.68 FEET)**.
- [03] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED JULY 30, 1897. A POST 24" ABOVE GROUND, 4" SQUARE, MARKED AND WITNESSED AS DESCRIBED BY THE SURVEYOR GENERAL.
- [04] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. POINT DETERMINED BY REFERENCE TO THE RECORD DISTANCES OF NORTHEAST, SOUTHWEST, AND NORTHWEST BEARING TREES. AT POINT FOR CORNER, SET AN IRON POST, 3 FEET LONG, 2" DIA, 28" IN THE GROUND, FOR CORNER OF SECTIONS 6 AND 7 ONLY, WITH BRASS CAP MARKED "T15S R7W S12 T15S S6 S7 R6W 1940" FROM WHICH A YEW 14" DIA (GLO BT) BEARS **N68-1/2°E, 71 LINKS (46.86 FEET)**, BLAZE HEALED, REBLAZED AND REMARKED "T15S R6W S6 BT"; A FIR 60" DIA (GLO BT) BEARS **S50-1/2°W, 48 LINKS (31.68 FEET)**, MARKED "T15S R7W S13 BT", I DESTROY ALL MARKS ON THIS BEARING TREE; A FIR 16" DIA (GLO BT) BEARS **N69°W, 119 LINKS (78.54 FEET)**, MARKED "T15S R7W S1 BT", I DESTROY ALL MARKS ON THIS BEARING TREE; A YEW 10" DIA BEARS **S48-1/2°E, 57 LINKS (37.62 FEET)**, MARKED "T15S R6W S7 BT".
- [05] BENTON COUNTY SURVEY NO. 1565 (OLD NO. 158) FIELD NOTES (FIELD BOOK 81, PAGES 32-33) BY BURT WILKES, D.C.S., DATED MARCH 26, 1941. U.S. BRASS CAP.
- [06] BENTON COUNTY MAP NO. 15-6-00003 BY BURT WILKES, D.C.S. DATED APRIL 3, 1941. U.S. MONUMENT. 2" PIPE BRASS CAP.
- [07] BENTON COUNTY SURVEY NO. 1565 (OLD NO. 158) BY BURT WILKES, D.C.S., DATED APRIL 4, 1941. U.S. MONUMENT. 2" PIPE BRASS CAP.
- [08] LANE COUNTY SURVEY NO. 2346. COPY OF RECORD [07] FILED IN LANE COUNTY.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821**RESEARCH BY:** DAVID L. MALONE, P.L.S.**DATA ENTRY BY:** SAME