

C. WANLESS/R. McMULLEN/D. MATTSON 1989

27

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 15 S., R. 6 W., Willamette Meridian, Oregon

156240500

0.85	Descend over S. slope, through heavy timber and dense undergrowth. Creek, 3 lks. wide, course S. 10° E.; asc. over SE. slope.
2.24	From this point, a point established by person(s) unknown, bears South, 1.860 chs. dist., monumented with an iron pipe, 1/2 in. diam., loosely set, projecting 6 ins. above ground.
6.80	Top of ascent; desc. over S. slope.
19.10	Ferguson Creek, 10 lks. wide, course S. 60° E.; asc. over NE. slope.
27.80	Top of ascent; desc. over NW. slope.
29.60	Creek, 5 lks. wide, course N. 30° E.; asc. over NE. slope.
38.73	From this point, a point established by person(s) unknown, bears South, 0.890 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground.
39.270	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 15 S R 6 W 1/4 S 8 1/4 S 17 1988
	from which
	A fir, 28 ins. diam., bears S. 80 1/2° E., 12 1/2 lks. dist., mkd. 1/4 S 17 BT.
	An alder, 11 ins. diam., bears N. 2 1/2° W., 25 lks. dist., mkd. 1/4 S 8 BT on bark.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over NE. slope.
56.40	Spur, slopes N.; desc. over NW. slope, also dirt road, 12 lks. wide, bears N. 15° W. and S. 15° E.
63.50	Gravelled road, 30 lks. dist., bears N. 60° E. and S. 60° W.
67.10	Creek, 4 lks. wide, course S. 60° W.; continue descent over NW. slope.

Form 7600 (Rev. November 1987) U.S. DE. OF M.

FIELD NOTE PAPER