

C. WANLESS/R. McMULLEN/D. MATTSON 1989

23

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 15 S., R. 6 W., Willamette Meridian, Oregon

156340500

CHAINS	
	S. 89° 16' 00" W., bet. secs. 9 and 16. Ascend over S. slope, through moderate timber and dense undergrowth.
3.20	Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.
33.10	Ravine, drains S. 10° W.; asc. over SE. slope.
39.370	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Drive an iron rod, 20 ins. long, 5/8 in. diam., 8 ins. into the root of a fir, 68 ins. diam., with aluminum cap mkd.
	T 15 S R 6 W $\frac{1}{4}$ $\frac{S 9}{S 16}$ 1988
	from which A fir, 7 ins. diam., bears N. 50° E., 22 lks. dist., mkd. $\frac{1}{4}$ S9 BT. A fir, 8 ins. diam., bears S. 27° .., 22 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	Ascend over E. slope.
44.00	Spur, slopes S. 10° E.; desc. over SW. slope.
46.10	Bottom of descent; asc. SE. slope.
50.35	Spur, slopes S. 10° W.; desc. over SW. slope.
66.60	Creek, 10 lks. wide, course S.; asc. S. slope.
72.90	Top of ascent; desc. SW. slope.
74.30	Ravine, drains S. 5° E.; asc. over NE. slope.
77.50	Top of ascent; desc. over SW. slope.
78.740	The cor. of secs. 8, 9, 16 and 17.
	N. 0° 50' 00" W., bet. secs. 8 and 9. Ascend over SE. slope, through moderate timber and dense undergrowth.

Form 9600-10a1 November 1987 U.S.D.I. BLM

FIELD NOTE PAPER