

W. GLENN / J. JELLEY 1963

366

FIELD NOTE PAPER

9

Remonumentation, Original Corner Points, T. 15 S., R. 6 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remains of bearing trees mkd. and recorded by C. M. Collier, County Surveyor, in 1898. Collier determined the cor. point from the original bearing trees, of which no evidence now remains.

Collier's bearing trees:

A down fir, 40 ins. diam., bears N. $34\frac{1}{2}^\circ$ E., 58 lks. dist., with healed double blaze.

A sawed fir stump, 32 ins. diam., bears N. $77\frac{1}{2}^\circ$ W., 44 lks. dist., with scribe marks CS visible on opened upper blaze and with a healed blaze at base.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S R 6 W

S 16 S 15

1963

from which new bearing trees

A fir, 6 ins. diam., bears N. $19\frac{1}{2}^\circ$ E., 17 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

A fir, 6 ins. diam., bears S. 44° W., 23 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

The corner is located under the S. side of a fir log, 40 ins. diam.

The cor. of secs. 9, 10, 15, and 16, determined at record bearing and distance from the original bearing trees:

A sawed fir stump, 34 ins. diam., bears N. 67° E., 51 lks. dist., with scribe mark T visible on opened lower blaze. Healed upper blaze.

A rotted fir stump, 34 ins. diam., bears S. 65° E., 50 lks. dist., no marks visible.

A sawed fir stump, 40 ins. diam., bears S. 34° W., 34 lks. dist., with scribe marks S16 visible on opened upper blaze. Healed lower blaze.

A sawed fir stump, 40 ins. diam., bears N. 24° W., 96 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S R 6 W

S 9 S 10

S 16 S 15

1963

from which new bearing trees

156400500

307

10

Remonumentation, Original Corner Points, T. 15 S., R. 6 W.

CHAINS

A fir, 8 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ E., 48 lks. dist., mkd. T15S R6W S10 BT.

A fir, 5 ins. diam., bears S. $3\frac{1}{4}^{\circ}$ E., 33 lks. dist., mkd. T15S R6W S15 BT.

A fir, 7 ins. diam., bears S. 54° W., $48\frac{1}{2}$ lks. dist., mkd. T15S R6W S16 BT.

A fir, 5 ins. diam., bears N. 86° W., 78 lks. dist., mkd. T15S R6W S9 BT.

From this point, an unmarked iron pipe, 1 in. diam., firmly set, protruding 18 ins. above ground, bears N. $10\frac{1}{2}^{\circ}$ E., $4\frac{1}{2}$ lks. dist.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, determined at record bearing and distance from the original bearing trees:

A white oak, 18 ins. diam., bears S. 11° E., 20 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened upper blaze. Healed blaze at base.

A down white oak, 12 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ W., 219 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on opened double blaze.

and a locally established bearing tree,

A fir, 11 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., $23\frac{1}{2}$ lks. dist., with scribe marks CS 297 BT visible on a partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S R 6 W
 $\frac{1}{4}$
 S 9 | S 10
 1963

from which a new bearing tree

A fir, 18 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 54 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with the original sandstone, 12 x 10 x 10 ins., loosely set, 4 ins. in the ground, now weathered and broken into many pieces, no marks visible, from which the remaining original bearing tree:

A sawed fir stump, 64 ins. diam., bears North, 121 lks. dist. (Record and to face, 118 lks.) with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.