

N. PRICE 10. DAUELSBERG.

1940

4-678b

120

Dependent Resurvey of Subdivisions of T. 15 S., R. 7 W.

Chains.

40.64 rolling broken S. slope.  
The cor. of secs. 7, 8, 17, and 18, which is a quartzite stone, 14x8x5 ins., firmly set, mkd. with 2 grooves on E. and 4 grooves on S. face.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone deposited at the base, for cor. of secs. 7, 8, 17, and 18, with brass cap mkd.

T15S R7W  
S7|S8  
S18|S17  
1940

from which

A fir, 36 ins. diam., bears N. 85° E., 63 lks. dist., dead and down, blaze healed. (Old B.T.)

A fir, 38 ins. diam., bears S. 11° E., 39 lks. dist., blaze healed. (Old B.T.)

A fir, 30 ins. diam., bears S. 13½° W., 43 lks. dist., blaze healed. (Old B.T.)

A fir, 20 ins. diam., bears N. 41° W., 76 lks. dist., blaze healed. (Old B.T.)

A fir, 44 ins. diam., bears N. 39½° E., 56 lks. dist., mkd. T 15 S R 7 W S 8 B T. (New B.T.)

Land, mountainous.

Soil, sandy and rocky loam; 3rd rate.

Timber, fir, hemlock, maple, alder, cedar, and yew.

Undergrowth, vinemaple, rhododendron, chinquapin, huckleberry, salmonberry, and hazel.

From the cor. of secs. 8, 9, 16, and 17, heretofore described

N. 78° 44' W., bet. secs. 8 and 17.

Asc. 800 ft. over SE. slope, through heavy timber and dense undergrowth.

29.01 The ¼ sec. cor., which is a sandstone, 20x14x5 ins., firmly set, mkd. ¼ on N. face.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone deposited at the base, for ¼ sec. cor., with brass cap mkd.

S8  
¼ S17  
1940

from which

A fir, 32 ins. diam., bears N. 37° W., 40 lks. dist., blaze healed. (Old B.T.)

A fir, 42 ins. diam., bears S. 10° E., 12 lks. dist., blaze healed. (Old B.T.)

157240500