

157340700

DATE 08/15/2019TOWNSHIP 15 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 4 CORNER NORTH 1/4DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON SOUTH LINE OF SECTION 33, TOWNSHIP 14 SOUTH, RANGE 7 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.**

- [01] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. **SET AN IRON POST, 3 FEET LONG, 1" DIA, 28" IN THE GROUND, WITH BRASS CAP MARKED "1/4 S4 1940" FROM WHICH A FIR 30" DIA BEARS S87°E, 29 LINKS (19.14 FEET), MARKED "1/4 S4 BT"; FIR 14" DIA BEARS S83°W, 67 LINKS (44.22 FEET), MARKED "1/4 S4 BT".**
- [02] BENTON COUNTY SURVEY NO. 1631 (OLD NO. 301) FIELD NOTES (FIELD BOOK 104, PAGE 17) BY W. C. GALLOWAY, C.S., DATED AUGUST 3, 1943. **3/4" PIPE WITH BRONZE CAP. FIR 28" DIA (GLO BT) BEARS EAST, 0.270 CHAINS (17.82 FEET); FIR 16" DIA (GLO BT) BEARS S85°40'W, 0.666 CHAINS (43.96 FEET) CENTERLINE.**
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 237 BY W. C. GALLOWAY, C.S., DATED AUGUST 8, 1943. **3/4" PIPE WITH BRONZE CAP. FIR 28" DIA (GLO BT) BEARS EAST, 27.0 LINKS (17.82 FEET); FIR 16" DIA (GLO BT) BEARS S85°40'W, 66.6 LINKS (43.96 FEET) TO CENTER OF TREE.**
- [04] BENTON COUNTY CORNER RESTORATION NO. 2935. **TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [05] BENTON COUNTY MAP NO. 15-7-00001 BY W. C. GALLOWAY, C.S., DATED AUGUST 30, 1943. **3/4" PIPE WITH CAP. FIR 28" DIA (GLO BT) BEARS EAST, 0.270 CHAINS (17.82 FEET) CENTER; FIR 16" DIA (GLO BT) BEARS S85°W, 0.666 CHAINS (43.96 FEET) CENTER.**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

C.S. No. 297

by W.C. July 1942
Witness K.M. Patterson

1/4 Sec. Sec. Cor. bet. Sections 10 and 15 T 15-6
Set branding Iron (J—) J with handle
Oak 12" in dia. bears S. 56° W. .52 std.
" 24" " " " N. 23° E. 1.60 chs. Stump.

C.S. No. 301

by W.C. Galloway cs
Witnesses Ralph Hall
Cliff. W. Rabar
Aug. 2, 1943

1/4 Sec. cor. bet sections 3 and 4 T 15-7
Cor. Set by U.S. Gen. Land Office Not exactly correct but excepted
3/4" Pipe with cap stamped 1/4 (3+4) Elev. 2450 feet
Hemlock 24" in dia. bears ³⁸S. 66° W. 13 lks. center of tree.
Fir 36" " " " ³⁵N. 17° E. 91 " " " "

Witnesses C.M. Rabar
and Neil Hawley
Aug. 3, 1943

Corner to Secs. 3, 4, 9 and 10 T. 15-7
1 1/4" pipe with cap (4+3 / 9+10)
Fir 24" in dia. bears (now 36") N. 89 1/2° E. 47.5 lks. to face
" 30 " " " (now 38) S 52 1/2° E. 39.0 " " "
" 32 " " " (now 36) S. 74° W. 22.9 " " "
Hemlock 24" " " (now 24) N 74° W. 25.7 " " "

Aug. 6, 1943

Neil Hawley witness

1/4 Sec. Cor. bet. Secs. 4 and 9 T 15-7
3/4" Pipe with bronze cap mkd. 3
Fir 24" now 30" bears. S 28° E. 41 lks. std. not measured
" 34" " 38" " N. 28° W. 69 " " " "

Aug. 8, 1943

Neil Hawley witness

1/4 Sec. Corner on north of Sec. 4 T 15-7
3/4" Pipe with bronze cap 4
Fir 28" in dia. bears East 27.0 lks.
" 16" " " " S. 85° 40' W. 66.6 lks. to center of tree

Aug. 1943

Neil Hawley

1/4 Sec. Corner on south bry. of sec. 33 T 14-7
3/4" Pipe with bronze cap 36 thick trees about 300 lks. W. of rock cliff.
Fir 7" in dia. bears N. 54° E. 37.5 lks. std. center of tree
" 6" " " " S. 11° W. 16 " " " "
" 10" " " " N. 62° W. 103 " "

Aug. 1943

Neil Hawley

Corner to secs. 3 and 4 on s. line of sec. 33 T. 14-7 T. 15-7
Pipe with bronze cap (3+3 / 4+3)
Fir 24" (now 50") in dia. bears S. 80 1/2° E. 84.4 lks. cen. of tree
" 12" " " " S. 62 1/2° W. 19.8 "
" 22" " " " S. 25° W. 244 " wind fall.

Aug. 19, 1943

Neil Hawley

1/4 Sec. Cor. bet. Secs. 4 and 5 T. 15-7
3/4" Pipe with bronze cap (5+4) W. of stone, Mound of stone 3' W.
Fir 11" in dia. bears S. 65° E. 15 lks. Elen 1800' cor. on ridge
" 15" " " " S. 43° W. 13.4"
in N. end of Rhododendron park

$\frac{1}{4}$ -Section corner on north of Section 4, Twp. 15-7

02985

Reestablishment by W. C. Galloway

August 8, 1943

$\frac{3}{4}$ " pipe with bronze cap

Fir 28" in diam bears East

27.0 links

Fir 16" in diam bears S 85° 40' W

66.6 links

Witness Neil Hawley

3466