

157400600

DATE 02/16/2007TOWNSHIP 15 SOUTH, RANGE 07 WEST, WILLAMETTE MERIDIAN; SECTION 03 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER OF SECTION 4
NORTHEAST CORNER OF SECTION 9
NORTHWEST CORNER OF SECTION 10**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED JULY 30, 1897. SET A HEMLOCK POST 3 FEET LONG, 3" SQUARE, 20" DEEP ON BED ROCK MARKED "T15S S3" ON NORTHEAST FACE, "R7W S10" ON SOUTHEAST FACE, "S9" ON SOUTHWEST FACE, AND "S4" ON NORTHWEST FACE WITH 5 NOTCHES ON SOUTH EDGE AND 3 NOTCHES ON EAST EDGE FROM WHICH A FIR 24" DIA BEARS N89°E, 49 LINKS (32.34 FEET), MARKED "T15SR7WS3BT"; FIR 30" DIA BEARS S59°E, 40 LINKS (26.40 FEET), MARKED "T15SR7WS10BT"; FIR 32" DIA BEARS S73°W, 25 LINKS (16.50 FEET), MARKED "T15SR7WS9BT"; HEMLOCK 24" DIA BEARS N75°W, 26 LINKS (17.16 FEET), MARKED "T15SR7WS4BT".
- [02] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. A BADLY WEATHERED HEMLOCK STAKE, MARKED "T15S R7W" AND OTHER PARTIAL SCRIBE MARKS. AT POINT FOR CORNER SET AN IRON POST, 3 FEET LONG, 2" DIA, 28" IN THE GROUND, WITH THE ORIGINAL STAKE DEPOSITED AT THE BASE, WITH A BRASS CAP MARKED "T15S R7W S4 S3 S9 S10 1940" FROM WHICH A FIR 34" DIA (GLO BT) BEARS N89°E, 49 LINKS (32.34 FEET), BLAZE HEALED; FIR 36" DIA (GLO BT) BEARS S53°E, 40 LINKS (26.40 FEET), BLAZE HEALED; FIR 34" DIA (GLO BT) BEARS S75-1/2°W, 24 LINKS (15.84 FEET), BLAZE HEALED; HEMLOCK 18" DIA (GLO BT) BEARS N73°W, 26 LINKS (17.16 FEET), BLAZE HEALED.
- [03] BENTON COUNTY SURVEY NO. 1631 (OLD NO. 301) FIELD NOTES (FIELD BOOK 104, PAGE 14) BY W. C. GALLOWAY, C.S., DATED AUGUST 3, 1943. 1-1/4" PIPE WITH BRONZE CAP. FIR 24" DIA (NOW 36") (GLO BT) BEARS N89-1/2°E, 0.475 CHAINS (31.35 FEET) TO FACE; FIR 30" DIA (NOW 38") (GLO BT) BEARS S52-1/2°E, 0.390 CHAINS (25.74 FEET) TO FACE; FIR 32" DIA (NOW 36") (GLO BT) BEARS S74°W, 0.229 CHAINS (15.11 FEET) TO FACE; HEMLOCK 24" DIA (NOW 24") (GLO BT) BEARS N74°W, 0.257 CHAINS (16.96 FEET) TO FACE.
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 237 BY W. C. GALLOWAY, C.S., DATED AUGUST 3, 1943. 1-1/4" PIPE WITH BRONZE CAP. FIR 24" DIA (NOW 36") (GLO BT) BEARS N89-1/2°E, 47.5 LINKS (31.35 FEET) TO FACE; FIR 30" DIA (NOW 38") (GLO BT) BEARS S52-1/2°E, 39.0 LINKS (25.74 FEET) TO FACE; FIR 32" DIA (NOW 36") (GLO BT) BEARS S74°W, 22.9 LINKS (15.11 FEET) TO FACE; HEMLOCK 24" DIA (NOW 24") (GLO BT) BEARS N74°W, 25.7 LINKS (16.96 FEET) TO FACE.
- [05] BENTON COUNTY CORNER RESTORATION NO. 2932. TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [06] BENTON COUNTY MAP NO. 15-7-00001 BY W. C. GALLOWAY, C.S., DATED AUGUST 30, 1943. 1-1/4" PIPE WITH CAP. FIR 24" DIA (GLO BT) BEARS N89°E, 0.475 CHAINS (31.35 FEET) TO FACE; FIR 30" DIA (GLO BT) BEARS S53°E, 0.390 CHAINS (25.74 FEET) TO FACE; FIR 32" DIA (GLO BT) BEARS S73-1/2°W, 0.229 CHAINS (15.11 FEET) TO FACE; HEMLOCK 24" DIA (GLO BT) BEARS N74-1/2°W, 0.257 CHAINS (16.96 FEET) TO FACE.
- [07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY DANIEL N. PATTERSON, CADASTRAL SURVEYOR, DATED AUGUST 26, 1996. MONUMENTED WITH AN IRON POST, 2" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MARKED "T15S R7W S4 S3 S9 S10 1940" FROM WHICH A SAWED FIR STUMP 36" DIA (GLO BT) BEARS N89°E, 49 LINKS (32.34 FEET), WITH HEALED BLAZE; SAWED AND DECAYED FIR STUMP 26" DIA (GLO BT) BEARS S53°E, 40 LINKS (26.40 FEET), NO MARKS VISIBLE; A ROOT HOLE (GLO BT) BEARS S75-1/2°W, 24 LINKS (15.84 FEET); UPROOTED, SAWED AND DECAYED HEMLOCK STUMP, SIZE INDETERMINATE, (GLO BT) BEARS N73°W, 26 LINKS (17.16 FEET), NO MARKS; FIR 8" DIA BEARS N14°E, 41 LINKS (27.06 FEET), MARKED "T15SR7WS3BT"; HEMLOCK 9" DIA BEARS S63-3/4°E, 22-1/2 LINKS (14.85 FEET), MARKED "T15SR7WS10BT"; HEMLOCK 7" DIA BEARS S61-1/4°W, 14 LINKS (9.24 FEET), MARKED "T15SR7WS9BT"; FIR 7" DIA BEARS N76°W, 9 LINKS (5.94 FEET), MARKED "T15SR7WS4BT".
- [08] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JANET R. MYERS, CADASTRAL SURVEYOR, DATED JUNE 6, 2001. MONUMENTED WITH AN IRON POST, 2" DIA, FIRMLY SET, PROJECTING 8" ABOVE GROUND, WITH BRASS CAP MARKED "T15S R7W S4 S3 S9 S10 1940" FROM WHICH A FIR STUMP 34" DIA (GLO BT) BEARS N89°E, 32.3 FEET, WITH A HEALED BLAZE; FIR STUMP 30" DIA (GLO BT) BEARS S53°E, 26.4 FEET, WITH A HEALED BLAZE; UPROOTED FIR STUMP 34" DIA (GLO BT) BEARS S75-1/2°W, 15.8 FEET, WITH AXE MARKS ABOVE A HEALED BLAZE; DECAYED HEMLOCK STUMP, SIZE INDETERMINATE, (GLO BT) BEARS N73°W, 17.2 FEET, WITH NO MARKS VISIBLE; FIR 8" DIA BEARS N15°E, 13.6 FEET TO A 2-1/2" x 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "T15SR7WS3BT"; HEMLOCK 10" DIA BEARS S63-1/2°E, 14.8 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "T15SR7WS10BT"; HEMLOCK 8" DIA BEARS S60°W, 9.5 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "T15SR7WS9BT"; FIR 8" DIA BEARS N77-1/2°W, 5.9 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "T15SR7WS4BT". EACH NEW BEARING TREE HAS A 2-1/2" x 1/4" MAGNETIC NAIL DRIVEN AT THE BASE ON THE RIGHT SIDE-CENTER.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.
DATA ENTRY BY: SAME

C.S. No. 297

by W.C. July 1942
Witness V.M. Patterson

1/4 Sec. Sec. Cor. bet. Sections 10 and 15 T 15-6
Set branding Iron (J) with handle
Oak 12" in dia. bears S. 56° W. .52 std.
" 24" " " " N. 23° E. 1.60 chs. Stump.

N. 20th

C.S. No. 301

by W.C. Galloway CS
Witnesses Ralph Hall
Cliff. W. Raber
Aug. 2, 1943

1/4 Sec. cor. bet sections 3 and 4 T 15-7
Cor. Set by U.S. Gen. Land Office Not exactly correct but excepted
3/4" Pipe with cap stamped 1/4 (3+4) Elev. 2450 feet
Hemlock 24" in dia. bears ^{36"}S. 66° W. 13 lks. center of tree.
Fir 36" " " " ^{33"}N. 17° E. 91 " " " "

15 900 and

Witnesses C.W. Raber
and Neil Hawley
Aug. 3, 1943

Corner to Secs. 3, 4, 9 and 10 T. 15-7
1 1/4" pipe with cap (4/3 / 9/10)
Fir 24" in dia. bears (now 36") N. 89 1/2° E. 47.5 lks. to face
" 30 " " " (now 38) S 52 1/2° E. 39.0 " " "
" 32 " " " (now 36) S. 74° W. 22.9 " " "
Hemlock 24" " " (now 34) N 74° W. 25.7 " " "



Aug. 6, 1943
Neil Hawley witness

1/4 Sec. Cor. bet. Secs. 4 and 9 T 15-7
3/4" Pipe with bronze cap mkd. 7
Fir 24" now 30" bears. S 28° E. 41 lks. std. not measured
" 34" " 38" " N. 28° W. 69 " " " "

Aug. 8, 1943
Neil Hawley witness

1/4 Sec. Corner on north of Sec. 4 T 15-7
3/4" Pipe with bronze cap 7
Fir 28" in dia. bears East 27.0 lks.
" 16" " " " S. 85° 40' W. 66.6 lks. to center of tree

Aug. 1943
Neil Hawley

1/4 Sec. Corner on south bry. of sec. 33 T 14-7
3/4" Pipe with bronze cap ³³ thick trees about 300 lks. W. of rock cliff.
Fir 7" in dia. bears N. 54° E. 37.5 lks. std. center of tree
" 6" " " " S. 11° W. 16 " " " "
" 10" " " " N. 62° W. 103 " "

Aug. 1943
Neil Hawley

Corner to secs. 3 and 4 on S. line of sec. 33 ^{T. 14-7} / ^{T. 15-7}
Pipe with bronze cap (23 / 4/3)
Fir 24" (now 50") in dia. bears S. 80 1/2° E. 84.4 lks. cen. of tree
" 12" " " " S. 62 1/2° W. 19.8 "
" 22" " " " S. 25° W. 244 " wind fall.

Aug. 19, 1943
Neil Hawley

1/4 Sec. Cor. bet. Secs. 4 and 5 T. 15-7
3/4" Pipe with bronze cap (5/7) W. of stone, Mound of stone 3' W.
Fir 11" in dia. bears S. 65° E. 15 lks. Elev 1800' Cor. on ridge
" 15" " " " S. 43° W. 13.4" in N. end of Rhododendron patch

Corner to sections 3, 4, 9 and 10, Twp. 15-7

02932

Reestablishment by W. C. Galloway

August 3, 1943

1 $\frac{1}{4}$ " pipe with cap

Fir 24" in diam bears N 89 $\frac{1}{2}$ ° E

47.5 links

Fir 30" in diam bears S 52 $\frac{1}{2}$ ° E

39.0 links

Fir 32" in diam bears S 74° W

22.9 links

Hemlock 24" in diam bears N 74° W

25.7 links

Witnesses C. W. Raver and Neil Hawley