

**157400640**

## CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc  
10/04/2010

<b>CORNER NUMBER</b>
<b>157400640</b>

<b>STEP</b>	<b>HISTORY</b>	<b>RESTORATION</b>
Form Prepared, DB	7/9/2019	12/26/24
Field Inspection, DB	12/19/24	12/19/24
Finish index (count unit)	7/9/19	12/19/24
Counter Index	12/23/24	12/23/24
GIS Index Form	12/23/24	12/23/24
Checked, DB	12/27/24	12/27/24
Form Edited, DB	1/02/25	1/02/25
Form Signed, DB	1/02/25	1/02/25
Authorize Payment, DB	—	—
Archive Digital Files	1/02/25	1/02/25
Collect Documents	1/02/25	1/02/25
PDF File	1/02/25	1/02/25
Copy For Filming	1/02/25	1/02/25
Scanned (pdf to laserfiche)	1/02/25	1/02/25
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

### COMMENTS:

DATE 07/09/2019TOWNSHIP 15 SOUTH, RANGE 07 WEST, WILLAMETTE MERIDIAN; SECTION 03 CORNER WEST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

EAST 1/4 CORNER OF SECTION 4

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED JULY 30, 1897. SET A FIR POST 3 FEET LONG, 3" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON WEST FACE FROM WHICH A FIR 36" DIA BEARS N15°E, 91 LINKS (60.06 FEET), MARKED "1/4S BT"; HEMLOCK 24" DIA BEARS N89°W, 13 LINKS (8.58 FEET), MARKED "1/4S BT".

[02] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. POINT FOR 1/4 SECTION CORNER DETERMINED BY REFERENCE TO DISTANCES FROM TWO ORIGINAL BEARING TREES. AT POINT FOR CORNER SET AN IRON POST, 3 FEET LONG, 1" DIA, 28" IN THE GROUND, WITH BRASS CAP MARKED "1/4 S4 S3 1940" FROM WHICH A FIR 52" DIA (GLO BT) BEARS N18°E, 91 LINKS (60.06 FEET) WITH HEALED BLAZE; HEMLOCK 38" DIA (GLO BT) BEARS S67°W, 13 LINKS (8.58 FEET) WITH HEALED BLAZE; FIR 46" DIA BEARS S33°W, 50 LINKS (33.00 FEET), MARKED "1/4S4BT".

[03] BENTON COUNTY SURVEY NO. 1631 (OLD NO. 301) FIELD NOTES (FIELD BOOK 104, PAGE 13) BY W. C. GALLOWAY, C.S., DATED AUGUST 2, 1943. FOUND 3/4" PIPE U.S. GEN. LAND OFFICE. FIR 36" DIA (NOW 52") (GLO BT) BEARS N17°E, 0.91 CHAINS (60.06 FEET) TO CENTER; HEMLOCK 24" DIA (NOW 30") (GLO BT) BEARS S66°W, 0.13 CHAINS (8.58 FEET) TO CENTER.

[04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 237 BY W. C. GALLOWAY, C.S., DATED AUGUST 2, 1943. CORNER SET BY U.S. GLO "NOT EXACTLY CORRECT BUT EXCEPTED". 3/4" PIPE WITH CAP (1940 GLO) STAMPED "1/4 3 4" (SIC). FIR 36" DIA (52") (GLO BT) BEARS N17°E, 91 LINKS (60.06 FEET) TO CENTER OF TREE; HEMLOCK 24" DIA (NOW 30") (GLO BT) BEARS S66°W, 13 LINKS (8.58 FEET) TO CENTER OF TREE.

[05] BENTON COUNTY CORNER RESTORATION NO. 2934. TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

[06] BENTON COUNTY MAP NO. 15-7-00001 BY W. C. GALLOWAY, C.S., DATED AUGUST 30, 1943. 3/4" PIPE WITH CAP. FIR 36" DIA (GLO BT) BEARS N52°E (SIC), 0.91 CHAINS (60.06 FEET) TO CENTER; HEMLOCK 24" DIA (GLO BT) BEARS S66°W, 0.13 CHAINS (8.58 FEET) TO CENTER.

[07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JANET R. MYERS, CADASTRAL SURVEYOR, DATED JUNE 6, 2001. MONUMENTED WITH AN IRON POST, 1" DIA, FIRMLY SET, PROJECTING 12" ABOVE GROUND WITH BRASS CAP MARKED "T15S R7W 1/4 S4 S3 1940" FROM WHICH A ROOT HOLE (GLO BT) BEARS N18°E, 60.1 FEET, ALONGSIDE OF WHICH IS AN UPROOTED FIR, SIZE INDETERMINATE, WITH HEALED BLAZE; DECAYED HEMLOCK STUMP (GLO BT), SIZE INDETERMINATE, BEARS S67°W, 8.6 FEET, NO MARKS VISIBLE; WITH HEALED BLAZE; FIR STUMP 48" DIA (GLO BT) BEARS S33°W, 33.0 FEET, WITH HEALED BLAZE; HEMLOCK 14" DIA BEARS S80-3/4°E, 20.6 FEET, MARKED "1/4 S3 BT"; HEMLOCK 21" DIA BEARS N71°W, 29.0 FEET, MARKED "1/4 S4 BT". ADD THE MARKS "T15S R7W" TO THE BRASS CAP. EACH NEW BEARING TREE HAS A 2-1/2" X 1/4" MAGNETIC NAIL DRIVEN AT THE BASE ON THE RIGHT SIDE-CENTER.

[08] BENTON COUNTY SURVEY NO. 10919 BY BRIAN M. PETERSON, P.L.S., DATED JULY 16, 2018. FOUND 3" BLM BRASS CAP (1940). FOUND FIR UPROOT 50" DIA (GLO BT) BEARS N18°E, 60.1 FEET, NO MARKS VISIBLE; ROTTED HEMLOCK STUMP (GLO BT) BEARS S67°W, 8.6 FEET, NO MARKS VISIBLE; FIR STUMP 48" DIA (GLO BT) BEARS S33°W, 33.0 FEET, HEALED FACE; HEMLOCK 18" DIA (BLM BT) BEARS S80-3/4°E, 20.6 FEET, SCRIBING VISIBLE; HEMLOCK 22" (BLM BT) DIA BEARS N71°W, 29.0 FEET, SCRIBING VISIBLE. SET HEMLOCK 12" DIA BEARS S59°W, 24.6 FEET, MARKED "1/4 S4 BT"; HEMLOCK 22" DIA BEARS N17°E, 35.6 FEET, MARKED "1/4 S3 BT".

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821**RESEARCH BY:** BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.**DATA ENTRY BY:** SAME

**BENTON COUNTY CORNER RESTORATION FORM, PAGE 1 OF 2, 157400640R3  
SEE CORNER HISTORY FORM FOR RECORDS ETC.**

CORNER RESTORATION FIELD BOOK NUMBER 35 PAGE(S) 46 - 47 DATE 12/19/2024  
TOWNSHIP 15 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 3 CORNER WEST 1/4  
DONATION LAND CLAIM N/A CORNER N/A  
CONDITION REPORT ; REFERENCED OUT X; RENEWED ; SURVEYED IN ;

**LOCATION AND COMMENTS:**

CORNER IS LOCATED ON A STEEP NORTHWEST FACING SLOPE IN A STAND OF MIXED AGE HEMLOCK TREES ON ALL SIDES. TO REACH CORNER FROM THE INTERSECTION OF BLM SOUTH FORK ROAD AND FALL CREEK ACCESS ROAD, TRAVEL WESTERLY ALONG FALL CREEK ACCESS ROAD FOR 0.43 MILES PAST THE TRAILHEAD PARKING AREA AND THROUGH THE GATE TO A WYE, STAY LEFT FOR 1.83 MILES TO A WYE, TURN RIGHT FOR 0.04 MILES TO A WYE, TURN RIGHT FOR 0.24 MILES TO A WYE, STAY LEFT FOR 0.44 MILES TO AN OLD WYE, STAY LEFT FOR 0.80 MILES TO A WYE, STAY LEFT FOR 0.49 MILES TO A WYE, TURN LEFT FOR 0.42 MILES TO A WYE IN A CLEAR CUT, TURN LEFT FOR 0.34 MILES TO THE END OF THE PASSABLE ROAD AND PARK, WALK SOUTHEASTERLY ALONG THE OLD ROADBED FOR 1,740 FEET TO THE BLAZED SECTION LINE, THEN FOLLOW THE SECTION LINE NORTH FOR 225 FEET TO THE CORNER. THE CORNER IS POOR FOR GPS CONTROL.

**MONUMENTS AND ACCESSORIES FOUND (CONDITION AND SOURCE):**

1. FOUND 2-1/2" BRASS CAP MARKED AS SHOWN ON PAGE 2 OF 2, ON 1" IRON PIPE, UNDISTURBED, SLIGHTLY LOOSE BUT STILL ACCEPTABLE, UP 12" ABOVE GROUND SURFACE, FOR THE CORNER.  
(SET FIR POST 3 FEET LONG, 3" SQUARE, 24" IN THE GROUND, MARKED "1/4 S" ON WEST FACE AS PER RECORD [01]).  
(POINT FOR 1/4 SECTION CORNER DETERMINED BY REFERENCE TO DISTANCES FROM TWO ORIGINAL BEARING TREES. AT POINT FOR CORNER SET AN IRON POST, 3 FEET LONG, 1" DIA, 28" IN THE GROUND, WITH BRASS CAP MARKED "1/4 S4 S3 1940" AS PER RECORD [02]).  
(FOUND 3/4" PIPE U.S. GEN. LAND OFFICE AS PER RECORD [03]).  
(3/4" PIPE WITH CAP (1940 GLO) STAMPED "1/4 3" AS PER RECORD [04]).  
(3/4" PIPE WITH CAP AS PER RECORD [06]).  
(MONUMENTED WITH AN IRON POST, 1" DIA FIRMLY SET, PROJECTING 12" ABOVE GROUND WITH BRASS CAP MARKED "T155 R7W 1/4 S4 S3 1940" AS PER RECORD [07]).  
(FOUND 3" BLM BRASS CAP (1940) AS PER RECORD [08]).
2. FOUND HEMLOCK STUMP 24" DIA THAT IS VERY ROTTEN WITH NO MARKS BEARS S66°44'W, 8.87 FEET TO CENTER.  
(HEMLOCK 24" DIA BEARS N89°W, 13 LINKS [8.58 FEET], MARKED "1/4S BT" AS PER RECORD [01]).  
(HEMLOCK 38" DIA BEARS S67°W, 13 LINKS [8.58 FEET] WITH HEALED BLAZE AS PER RECORD [02]).  
(HEMLOCK 24" DIA [NOW 30"] BEARS S66°W, 0.13 CHAINS [8.58 FEET] TO CENTER AS PER RECORDS [03] AND [04]).  
(HEMLOCK 24" DIA BEARS S66°W, 0.13 CHAINS [8.58 FEET] TO CENTER AS PER RECORD [06]).  
(DECAYED HEMLOCK STUMP, SIZE INDETERMINATE, BEARS S67°W, 8.6 FEET, NO MARKS VISIBLE AS PER RECORD [07]).  
(ROTTED HEMLOCK STUMP BEARS S67°W, 8.6 FEET, NO MARKS VISIBLE AS PER RECORD [08]).
3. FOUND D. FIR STUMP 44" DIA WITH HEALED BLAZE BEARS S32°03'W, 32.25 FEET TO CENTER.  
(FIR 46" DIA BEARS S33°W, 50 LINKS [33.00 FEET], MARKED "1/4S4BT" AS PER RECORD [02]).  
(FIR STUMP 48" DIA BEARS S33°W, 33.0 FEET, WITH HEALED BLAZE AS PER RECORD [07]).  
(FIR STUMP 48" DIA BEARS S33°W, 33.0 FEET, HEALED FACE AS PER RECORD [08]).
4. FOUND HEMLOCK 27" DIA WITH PARTIALLY HEALED FACE AND ILLEGIBLE SCRIBE MARKS BEARS N71°00'W, 29.17 FEET TO CENTER. HELD FOR BASIS OF BEARINGS FOR THIS RESTORATION. SET ALUMINUM NAIL AND PLASTIC WASHER IN SOUTHWESTERLY BASE FOR DISTANCE MEASUREMENT.  
(HEMLOCK 21" DIA BEARS N71°W, 29.0 FEET, MARKED "1/4 S4 BT" WITH A 2-1/2" X 1/4" MAGNETIC NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER AS PER RECORD [07]).  
(HEMLOCK 22" DIA BEARS N71°W, 29.0 FEET, SCRIBING VISIBLE AS PER RECORD [08]).
5. FOUND HEMLOCK 18" DIA WITH PARTIALLY HEALED FACE AND ILLEGIBLE SCRIBE MARKS BEARS S81°02'E, 20.60 FEET TO CENTER. SET ALUMINUM NAIL AND PLASTIC WASHER IN SOUTHERLY BASE FOR DISTANCE MEASUREMENT.  
(HEMLOCK 14" DIA BEARS S80-3/4°E, 20.6 FEET, MARKED "1/4 S3 BT", WITH A 2-1/2" X 1/4" MAGNETIC NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER AS PER RECORD [07]).  
(HEMLOCK 18" DIA BEARS S80-3/4°E, 20.6 FEET, SCRIBING VISIBLE AS PER RECORD [08]).
6. FOUND HEMLOCK 31" DIA WITH VISIBLE SCRIBING "1/4S3BT" BEARS N15°59'E, 34.57 FEET TO CENTER. FOUND NAIL IN NORTHWESTERLY BASE FOR DISTANCE MEASUREMENT.  
(SET HEMLOCK 22" DIA BEARS N17°E, 35.6 FEET, MARKED "1/4 S3 BT" AS PER RECORD [08]).
7. FOUND HEMLOCK 14" DIA WITH VISIBLE SCRIBING "1/4S4BT" BEARS S57°19'W, 24.64 FEET TO CENTER. FOUND NAIL IN SOUTHEASTERLY BASE FOR DISTANCE MEASUREMENT.  
(SET HEMLOCK 12" DIA BEARS S59°W, 24.6 FEET, MARKED "1/4 S4 BT" AS PER RECORD [08]).

**MONUMENT SET (PROCEDURES AND DESCRIPTION):**

FOUND 2-1/2" BRASS CAP MARKED AS SHOWN ON PAGE 2 OF 2, ON 1" IRON PIPE, UNDISTURBED AND SLIGHTLY LOOSE BUT ACCEPTABLE, UP 12" ABOVE GROUND SURFACE, FOR THE CORNER. THE BRASS CAP AND IRON PIPE WERE SET IN 1940 BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, BY REFERENCE TO DISTANCES FROM TWO ORIGINAL BEARING TREES. THE BRASS CAP AND IRON PIPE ARE ACCEPTED AS THE PERPETUATION OF THE ORIGINAL CORNER POSITION.  
SET TWO NEW IRON ROD ACCESSORIES AS SHOWN ON PAGE 2 OF 2. FOUND WHITE FIBERGLASS POST 4" NORTH OF BRASS CAP.  
SET 6 FOOT ORANGE CARSONITE "SURVEY MARKER" POST 1 FOOT SOUTH OF BRASS CAP.





C.S. No. 297

by W.C. Galloway  
Witness T.M. Pathman

1/4 Sec. Cor. bet. Sections 10 and 15 T 15-6  
Set branding iron (—) J with handle  
Oak 12" in dia. bears S 56° W .52 std  
" 24" " " N 23° E 1.60 chs. Stamp

N. 204

C.S. No. 301

by W.C. Galloway  
Witnesses Robt. Hall  
Chf. W. Raber  
Aug. 5, 1943

1/4 Sec. Cor. bet. Sections 3 and 4 T 15-7  
Cor. Set by U.S. Gen. Land Office. Not exactly correct but excepted  
3/4" Pipe with cap stamped by (514) Elev. 2450 feet  
Hemlock 24" in dia. bears S 66° W 13 lks. center of tree  
Fir 36" " " N 17° E 91 " " "

Witnesses C.W. Raber  
and Neil Hawley  
Aug. 5, 1943

Corner To Secs. 3, 4, 9 and 10 T 15-7  
1 1/4" Pipe with cap (513) (515)  
Fir 24" in dia. bears (true 30) N 89 1/2° E. 47.5 lks. to face  
" 30 " " " (true 30) S 52 1/2° E. 39.0 " " "  
" 32 " " " (true 30) S 74° W. 22.9 " " "  
Hemlock 24" " " (true 34) N 74° W. 25.7 " " "

Aug. 6, 1943

Neil Hawley witness

1/4 Sec. Cor. bet. Secs. 4 and 9 T 15-7  
3/4" Pipe with bronze cap mid. 1/2  
Fir 24" in dia. bears S 28° E. 41 lks. std. not measured  
" 34" " 38" " N. 28° W. 69 " " "

Aug. 8, 1943

Neil Hawley witness

1/4 Sec. Corner on north of Sec. 4 T 15-7  
3/4" Pipe with bronze cap 7  
Fir 28" in dia. bears East 270 lks.  
" 16" " " S. 85° 40' W. 66.6 lks. to center of tree

Aug. 1943

Neil Hawley

1/4 Sec. Corner on south bdy. of sec. 33 T 14-7  
3/4" Pipe with bronze cap 3 1/2 This tree about 300 lks. W of rock cap  
Fir 7" in dia. bears N 54° E. 37.5 lks. std. center of tree  
" 6" " " S. 11° W. 16 " " "  
" 10" " " N. 62° W. 10.3 " "

Aug. 1943

Neil Hawley

Corner To secs. 3 and 4 on s. line of sec. 33 T 14-7  
Pipe with bronze cap (713) (715)  
Fir 24" (true 30) in dia. bears S 80 1/2° E. 84.4 lks. cen. of tree  
" 12" " " S. 62 1/2° W. 19.8 "  
" 22" " " S. 25° W. 2.44 " wind fall

Aug. 19, 1943

Neil Hawley

1/4 Sec. Cor. bet. Secs. 4 and 5 T 15-7  
3/4" Pipe with bronze cap (514) W. of stone, Monument Stone 3 W.  
Fir 11" in dia. bears S 65° E. 15 lks. E. cen. 1800' cor. on ridge  
" 15" " " S. 43° W. 13.4 "

in head of Hadenston pass

$\frac{1}{4}$ -Section corner between sections 3 and 4, Twp. 15-7

02034

Reestablishment by W. C. Galloway

August 2, 1943

Corner set by U. S. Gen. Land Office, Not exactly correct but accepted.  
 $\frac{3}{4}$ " pipe with cap stamped  $\frac{1}{4}$  3 + 4 Elev. 2450 feet  
Hemlock 24" in diam bears S 66° W 13 links  
Fir 36" in diam bears N 17° E 91 links

Witnesses Ralph Hall and Cliff W. Raber