

S. HARDIN 1978

22

298

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 15 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.  
Soil, sandy clay loam.  
Timber, fir, hemlock, cedar, maple, and alder; under-  
growth, vine maple, salmonberry, hazel, salal, Oregon  
grape, devil's club, and fern.

158240500 →

From the 1/4 sec. cor. of secs. 8 and 17, monumented with  
the original sandstone, 14 x 14 x 6 ins., firmly set,  
projecting 5 ins. above ground, mkd. 1/4 S on N. face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 15 S R 8 W  
1/4 S 8  
S 17  
1978

from which

A hemlock, 10 ins. diam., bears N. 47 1/2° W., 24 1/2  
lks. dist., mkd. 1/4 S8 BT.

A cedar, 9 ins. diam., bears S. 12° W., 21 1/2 lks.  
dist., mkd. 1/4 S17 BT.

Deposit corner stone alongside iron post.

N. 87° 53' W., bet. secs. 8 and 17.

Descend 220 ft. over broken NW. slope.

20.185 Point for the W 1/16 sec. cor. of secs. 8 and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

W 1/16 S 8  
S 17  
1978

from which

A fir, 6 ins. diam., bears N. 15° W., 50 lks.  
dist., mkd. W 1/16 S8 BT.

A fir, 4 ins. diam., bears S. 60° W., 11 1/2 lks.  
dist., mkd. X BT.

Descend 60 ft. over NW. slope.

24.20 Creek, 5 lks. wide, course NW.; asc. 250 ft. over NE.  
slope.

33.90 Spur, slopes N.; desc. 150 ft. over NW. slope.

38.35 Creek, 5 lks. wide, course N.; asc. 45 ft. over E. slope.

40.37 The cor. of secs. 7, 8, 17, and 18, perpetuated and re-  
corded by Alan D. Reid, Forster, U. S. Forest Service,  
in 1959, monumented with an iron pipe, 1 1/2 ins. diam.,  
firmly set, projecting 8 ins. above ground, from which  
the remains of the original bearing trees: