

S. HARDIN 1978

20

296

Dependent Resurvey, Portion of Subdivisional Lines,
T. 15 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 19 ins. diam., bears S. $77\frac{1}{2}^\circ$ E., 35 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

At the corner point

Set an iron post, 23 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S R 8 W
 $\frac{1}{4}$ S 9
S 16
1978

from which

A fir, 41 ins. diam., bears N. 82° W., 120 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

An alder, 11 ins. diam., bears S. 40° E., 27 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, salmonberry, hazel, Oregon grape, and fern.

From the cor. of secs. 8, 9, 16, and 17, determined from the remains of the original bearing trees:

A fir snag, 33 ins. diam., bears S. 75° E., 57 lks. dist., no marks visible. (Record, 59 lks.)

A hemlock, 35 ins. diam., bears S. 36° W., 22 lks. dist., with healed blaze.

A fir snag, 15 ins. diam., bears N. $49\frac{1}{2}^\circ$ W., 63 lks. dist., no marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 15 S R 8 W
S 8 | S 9
S 17 | S 16
1978

from which new bearing trees

A hemlock, 14 ins. diam., bears N. 19° E., 42 lks. dist., mkd. T15S R8W S9 BT.

A cedar, 15 ins. diam., bears S. $47\frac{1}{2}^\circ$ E., 47 lks. dist., mkd. T15S R8W S16 BT.

A hemlock, 8 ins. diam., bears N. $29\frac{1}{2}^\circ$ W., 37 lks. dist., mkd. T15S R8W S8 BT.

N. $0^\circ 48'$ E., bet. secs. 8 and 9.

Descend 515 ft. over broken NW. slope, through heavy timber and dense undergrowth.

1158300500

