

S. HARDIN 1978

15

291

Dependent Resurvey, Portion of Subdivisional Lines,
T. 15 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	From which
	<p>A fir, 10 ins. diam., bears N. 6° E., 9½ lks. dist., mkd. N 1/16 S15 BT.</p> <p>A cherry, 8 ins. diam., bears S. 53° W., 22½ lks. dist., mkd. N 1/16 S16 BT.</p>
	<p>N. 0° 01' E., beginning new measurement.</p> <p>Descend 35 ft. over nearly level land.</p>
18.80	<p>Creek, 3 lks. wide, course E., also W. edge of small pond, edge bears N. and S.; asc. 15 ft. over gentle S. slope.</p>
20.29	<p>The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by W. C. Galloway, County Surveyor, in 1943, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:</p>
	<p>A root hole, bears S. 79° W., 30 lks. dist., with a down fir alongside, 28 ins. diam., with healed blaze. (Record, S. 74½° W.)</p> <p>A sawed fir stump, 16 ins. diam., bears N. 19½° W., 71 lks. dist., with scribe marks W S 9 BT visible on opened blaze. (Record, 70 lks.)</p>
	<p>and bearing trees mkd. by Galloway</p> <p>A fir, 21 ins. diam., bears N. 20° E., 32 lks. dist., with healed blaze.</p> <p>A cedar, 28 ins. diam., bears N. 86° W., 11 lks. dist., with healed blaze.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a stone collar, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 15 S R 8 W S 9 S 10 S 16 S 15 1978</p>
	<p>from which new bearing trees</p> <p>A fir, 26 ins. diam., bears N. 9½° E., 76½ lks. dist., mkd. T15S R8W S10 BT.</p> <p>A fir, 8 ins. diam., bears S. 32½° E., 38 lks. dist., mkd. X BT.</p> <p>A cedar, 27 ins. diam., bears S. 54° W., 40½ lks. dist., mkd. T15S R8W S16 BT.</p> <p>A cedar, 13 ins. diam., bears N. 75° W., 64 lks. dist., mkd. T15S R8W S9 BT.</p> <p>Reset iron pipe and set a 7 ft. steel fence post alongside iron post.</p>

158400500

