

**158700600**

DATE 07/17/2019TOWNSHIP 15 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 1 CORNER SOUTHEAST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**NORTHEAST CORNER SECTION 12, TOWNSHIP 15 SOUTH, RANGE 8 WEST  
POINT ON WEST LINE OF SECTION 7, TOWNSHIP 15 SOUTH, RANGE 7 WEST**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ALONZO GESNER, D.S., DATED JULY 28, 1891. *SET BASALT STONE 20" X 12" X 6", 15" IN THE GROUND, MARKED 5 NOTCHES TO THE SOUTH EDGE AND 1 NOTCH ON THE NORTH EDGE, FROM WHICH A HEMLOCK 20" DIA BEARS S12-1/2°W, 31 LINKS (20.46 FEET); MARKED "T15S R8W S12 BT"; HEMLOCK 20" DIA BEARS N20°W, 111 LINKS (73.26 FEET), MARKED "T15S R8W S1 BT"; RED FIR 32" DIA BEARS N79°E, 34 LINKS (22.44 FEET), MARKED "T15S R7W S6 BT"; RED FIR 30" DIA BEARS S21-1/2°E, 50 LINKS (33.00 FEET), MARKED "T15S R7W S7 BT".*
- [02] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED JULY 30, 1897. *STONE 5" ABOVE GROUND MARKED AND WITNESSED AS DESCRIBED BY SURVEYOR GENERAL.*
- [03] GENERAL LAND OFFICE (GLO) NOTES BY NORMAN D. PRICE, CADASTRAL ENGINEER, AND OSKAR T. DAUELSBERG, PUBLIC LAND SURVEYOR, DATED SEPTEMBER 16, 1940. *CORNER IS A QUARTZITE STONE, 24" X 16" X 8", MARKED WITH 1 NOTCH ON NORTH EDGE AND 5 NOTCHES ON SOUTH EDGE. AT POINT FOR CORNER SET AN IRON POST, 3 FEET LONG, 2" DIA, 28" IN THE GROUND WITH THE ORIGINAL STONE DEPOSITED AT THE BASE, WITH BRASS CAP MARKED "T15S T15S S1 R7W S12 R8W S7 1940" FROM WHICH A FIR 36" DIA (GLO BT) BEARS N79°E, 34 LINKS (22.44 FEET), MARKED "T15S R7W S6 BT". I DESTROY ALL MARKS ON THIS TREE. A FIR 36" DIA (GLO BT) BEARS S21-1/2°E, 50 LINKS (33.00 FEET), MARKED "T15S R7W S7 BT". I DESTROY ALL MARKS ON THIS TREE. A HEMLOCK 32" DIA (GLO BT) BEARS S12-1/2°W, 32 LINKS (21.12 FEET), BLAZE HEALED. A HEMLOCK 38" DIA (GLO BT) BEARS N23-3/4°W, 111 LINKS (73.26 FEET), BLAZE HEALED.*
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LYNN M. ROSEBERRY, CADASTRAL SURVEYOR, DATED JULY 5, 1963. *CORNER MONUMENTED WITH AN IRON POST, 2" DIA, FIRMLY SET, PROTRUDING 14" ABOVE THE GROUND, AND IN A MOUND OF STONE, 2-1/2 FOOT BASE, TO TOP, WITH BRASS CAP MARKED "T15S R8W R7W S1 S7 S12 1940" FROM WHICH A FIR 43" DIA (GLO BT) BEARS N79°E, 34 LINKS (22.44 FEET), MARKED WITH AN OPEN CHOPPED OFF BLAZE; FIR 43" DIA (GLO BT) BEARS S21-1/2°E, 50 LINKS (33.00 FEET), WITH A HEALED BLAZE; HEMLOCK 38" DIA (GLO BT) BEARS S12-1/2°W, 32 LINKS (21.12 FEET), WITH A HEALED BLAZE; HEMLOCK 40" DIA (GLO BT) BEARS N23-3/4°W, 111 LINKS (73.26 FEET), WITH SCRIBE MARKS "S R8W S1" VISIBLE ON PARTIALLY HEALED BLAZE.*
- [05] BENTON COUNTY SURVEY NO. 5626 BY ARTHUR E. MOSHER, P.L.S., DATED NOVEMBER, 1973. *FOUND BRASS CAP AND BEARING TREES.*
- [06] BENTON COUNTY SURVEY NO. 9364 (ALSO BEING LANE COUNTY SURVEY NO. 35683 AND 35684) BY JIM S. PETERSON, P.L.S., DATED AUGUST 27, 1998. *FOUND 2-1/2" GLO BRASS CAP (1940) IN MOUND OF STONE. FOUND HEMLOCK STUMP 40" DIA (GLO BT) BEARS N23-3/4°W, 111 LINKS (73.26 FEET), SCRIBING VISIBLE; FIR STUMP 42" DIA (GLO BT) BEARS N79°E, 34 LINKS (22.44 FEET), NO MARKS VISIBLE; FIR UPROOT 42" DIA (GLO BT) BEARS S21-1/2°W, 50 LINKS (33.00 FEET), HEALED FACE; HEMLOCK STUMP 44" DIA (GLO BT) BEARS S12-1/2°W, 32 LINKS (21.12 FEET), NO MARKS VISIBLE. SET HEMLOCK 10" DIA BEARS N84°E, 24.1 FEET, MARKED "X BT"; HEMLOCK 8" DIA BEARS S57°E, 30.9 FEET, MARKED "X BT"; HEMLOCK 6" DIA BEARS S42°W, 13.9 FEET, MARKED "T15S R8W S12 BT"; FIR 12" DIA BEARS N22°W, 79.6 FEET, MARKED "T15S R8W S1 BT".*
- [07] BENTON COUNTY SURVEY NO. 10798 BY ROBERT ALAN COOK, P.L.S., DATED SUMMER, 2016. *FOUND 1940 GLO BRASS CAP IN MOUND OF STONES.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME