1865 #61

Re-establishment 1/4 Section corner on line between Sections 21 & 28. T. 11 S. R. 11. W. The Stake is still standing but much decayed bearing trees are down but not destroyed, and agree with original notes, left the old Stake Standing and planted a Stone 14 x 12 x 10 inches Marked 1/4 S from which a Fir 48 in in diameter bears N. 45° 15' W. 97 feet dist Marked 1/4 S.B.T. A Spruce 24 in diameter bears N. 33° E. 165 feet Dist Marked 1/4 S. B. T.

There was at the time the original survey was made a Corner Established 20.00 Chns west from the corner to Sections 21. 22. 27 & 28. The Stake is gone but the bearing trees are still standing And agree with original note to-wit: a Fir 30 in in diameter bears N. 30° W. 50 links dist;

A Spruce 20 in in diameter bears S. 10° W 87 links dist at the point designated by Original notes Set a Sand Stone 24 x 12 x 5 inches marked 1/16. S. — Thro as the corner to Sections 21. 22. 27 & 28 was entirely obliterated measured East from this point 20.00 chns and set a Fir limb 4 feet long for corner Marked. S. 27. on S. E. face.

" S. 21 on N W "

T. 11. S. S. 22. " N. E "

R. 11. W. S. 28 S. W. " from which a Willow 8 in in diameter bears S. 80° W. 91 feet dist Marked S. 28. B. T. A Willow 8 in in diameter bears N. 25° W. 7 feet dist. Marked T. 11. S. S. 21. B. T. A Willow 8 in in diameter bears N. 11° E. 7 feet dist. Marked R. 11. W. S. 22. B. T. A Fir 40 in in diameter bears S 2° 30' E. 162 feet distant Marked S. 27 B. T.

A. L. Parker
County Surveyor

Received for Record and recorded this 30th day of Dec 1865