County Surveyor's Record, Benton County, Oregon.

SURVEY NO. of County Line #66 MADE FOR

In the matter of the survey of County Boundary between Benton and Gane Counties June 24 1901

Met with C. M. Collier County Surveyor of Gane County at what is pointed out as the Old Ford across Gong Tom River mentioned in the State Law as being three miles North of line defining boundary between the two counties Wesley Hinton and J D Hinton, Sons of Rowland Hinton being present, we together took their sworn statements in regard to the exact location of said ford at the time the law was made And at the time of a survey which they remembered to have been made in 1861 fixing position of County boundary Said survey made by Geo. Mercer of Benton and Mr. Hafft of Gane as surveyors acting upon the orders of their respective County courts, surveyed a part of said county line

Thence commencing at said ford upon Left Bank of Gong Tom at a point from which a White Oak 2 ft. in diam. bears South 20 lks. distant Var. 20 1/2 E.

16.04 Thence West 16.04 chs.
62.14 " South 62.14 "
96.23 " South 8° E 34.42 chs. Dep. 4.78 Lat. 34.09 chs.
149.82 " South 2 1/2° E 53.62 " " 1.87 " 53.59 "
218.50 South 65.68 chs. cross line between sections 4 and 9 of Tp. 15 South Range No. 5 West 40 lks. West of stone 4 x 5 ins marked C.S. previously set by Collier said stone being 20.02 1/2 chs. East of 1/4 sec. cor.
240.00 Thence South 24.50 chs. Three miles South of ford and to County line Between Benton and Gane counties Set oak post 8 x 8 ins 4 1/2 ft long 2 ft in ground with deposit of anthracite coal Marked post C.G. on West, Benton on North Gane on South. From which said post, A Pine Tree 36 ins in diameter bears South 6 1/2° W. 50 4/10 lks distant Marked tree C.G.B.T.
Thence East from last said post on East side of old tiritory road
19.91 1/2 Intersect line bet secs. 9 and 10 of Tp. 15 S. R 5 W. 16.18 chs. North of 1/4 section post. Both Bearing Trees to 1/4 section post are cut down marked new An Oak 5 ins. diam. brs. S. 80° E. 10 4/10 lks. dist.
" " 10 " " " " N. 32° E. 72" " "
Var. 21° E, Gat. 44 1/8 Lg, Dec, 23° 24' N, June 25. 1901
Set oak post 4 x 4 ins. with deposit of coal Marked C.G. on E. and W. faces
6.98 1/2 Left bank of Gong Tom
Set oak post 4 x 5 ins with deposit of coal. Marked Post C.G.
From which an oak 18 ins in diam bears South 24 1/2 West 133 lks dist
" " " Ash 14 " " " " N. 56 1/2° E. 30 " "
Measured North for base-line 74 1/2 lks Thence flag in line upon opposite bank bears South 7° East
9.14 1/2 Distance across river 216 links
52.00 North West end of Goodman's Lake
59.26 Enter Brabhams Lands
79.48 Intersect line between sections 10 and 11. 23.00 ch South of section Corner
Set oak post 4 x 5 ins. 4 ft. long 2 ft. in ground with deposit of Coal. Marked same C.G. on North and South 8/10 on West and 8/11 on East faces Var. 20° 45' East.
Thence East.
20.25 Set oak post 8 x 8 in, 4 1/2 ft. long 2 ft. in ground with deposit of coal Marked same Benton on North, Gane on South and C.L. on East and West faces. This post is upon West side of county road
60.00 Leave Richardson's and enter Washburn's lands
80.00 Cross line between sections 11 and 12,
22.65 South of section corner.
Set oak post 4 x 5 in. 4 1/2 ft. long 2 ft. in ground with deposit of coal Marked C.L. on North and South, 11 S. on West, 12 S. on East faces From which a red fir 8 ins. diam. bears E. 2 lks. distant
" " " " 14 " " " N. 72° W. 22 " "
Thence East
6.38 1/2 County Road. Set Oak post 8 x 8 ins. 4 1/2 ft. long 2 ft. in ground with deposit of stone coal Marked C.L. on East and West Benton on North Gane on South faces
From which a red fir 32 ins. diam. bears North 6 1/2° West 86 1/2 links distant
" " " " 16 " " " South 30 1/2° W. 136 " "
This post is upon East side of county road leading from Monroe to Junction Course of road S. 47 1/4° E.
30.40 Cross fence bet. Shipley and Washburn
32.23 Oak post 2 x 3 ins marked C.S. Bears North 25.7 lks.
33.82 Red fir 45 ins. in diameter,
60.36 1/2 Intersect West line of James E. Crowe Donation claim 24 4/10 lks S. of N.E. cor. of Chas Shipleys Land
74.12 Head of Lake 12 wide course S. 5° E.
80.36 Cross line between Sections 7 and 12. 22.49 ch South of sec. cor.
Set oak post 4 x 5 ins. 4 ft. long 2 ft. in ground

County Surveyor's Record, Benton County, Oregon.

SURVEY No..... MADE FOR.....

3939¹ GLASS & PRUDHOMME, PRINTERS AND BOOKBINDERS, PORTLAND, OR.

With deposit of coal. Marked C.T. on North and South, R. 5 on West and R. 4 on East faces. T
From which a red fir 14 ins. diam. bears North 56° W. 23 lks. dist.
" " An oak 36 " " " South 29 " "
1.00 Lake Creek 12 lks. wide outlet of lake course East
follow down stream crossing at intervals
8.21 Leave Lake Creek 20 lks. wide Course N.E. and Enter field.
23.34 Balm tree 30 ins in diam. marked same C.T. on East and West sides.
34.48 County Road leading from Monroe to Junction, known as the River Road, Course of road S. 57° E. Var. 20½ East
Set oak post 8x8 ins 4½ ft. long 2 ft. in ground with deposit of coal marked Benton North Lane on South, C.T. on East and West faces
From which an oak 4 ins. diam. bears South 72½° East. 31 lks. dist.
" " " A Pine 14 " " " South 3½ West 2 " "
A red fir 28 " " North 76° W 200 " "
41.05 Intersect Schenck's Granary 6 links North of South side the granary is about 300 lks. North of house.
50.68 A creek 10 lks. wide course N.W.
76.50 Offset 36 lks. to South to avoid dry bed of slough
Thence S. 85° E. 350 links Thence North 66½ lks into line.
The bearing trees to ¼ sec. post between sections 7 and 8 cannot be found
81.08 Set oak post 4x5 ins 4½ ft long 2 ft in ground with deposit of coal post marked C.T. on North and South faces
From which a White Fir 24 ins diam. bears South 25° East 84 lks dist.
" " " " 30 " " " North 80¾° East 132 " "
This post set East of section line to get it out of slough.
Thence East
35.82 Set vine Maple post 3x3 ins 3 ft. long
Marked C.T. on East and West faces
From which a maple 15 ins diam. bears bears N. 73¾° W. 46 lks. dist.
" " an ash 18 " " " S. 9¾° W. 40 " "
A maple 30 " " S. 70½° W. 94 " "
36.01 Left Bank of Willamette River Course N 47° W.
Variation 20½° East
June 27. 1901
June 28, 1901
Begin again post in county road 19.91½ chains West of post in line between sections 9 and 10 of Tp 15 S. R 5 W.
Thence West
23.70 White Oak 30 ins. diam. marked same C.T. on East and West.
60.60½ Cross line bet. sections 8 and 9 23.94 chs. South of section corner
Set oak post 4x5 ins 3½ ft. long 1 ft. in ground with deposit of coal marked same C.T. on north and South S. 9 on East and S. 8 on West faces made stone mound around post 2 ft. high
from which a pine 30 ins. diam. bears South 81¾° West 263 lks dist.
An oak 24" " " North 45° East 82 " "
Thence West Var. 20½° E
9.62 Oak 14 ins. diam. in line marked same C.T. on East side
36.00 Oak with old blaze upon E. East and West sides
evidence of original survey of county line
41.00 Top of assent upon North side of Hauck's Mountain near Summit of the same, Course of Mountain East and West
44.10 Old blazed oak 2 lks. South of line
70.00 Top of Mountain, begin to descend Var. 21° East
80.00 Intersect line between Sections 7 and 8. 24.40 chs. South of section corner Var. 23° East
Set oak post 4x5 ins. 4½ ft long 2 ft. in ground with deposit of coal post marked C.T. on North and South S. 7 on West S. 8 on East faces
From which an oak 20 ins. diam. bears N. 6° E. 64 lks. distant
" " " " 20 " " " South 52¾° E. 125 " "
Thence West
2.56 Laurel tree 12 ins diam. C.T. on West side, begin to descend
62.00 Foot of descent
63.00 Stream 2 lks wide Course North West, on North slope of hill
65.00 Descend gradually
76.40 Red fir Old blaze upon East and West sides 15 lks. South of line
81.29 Intersect line between sections 7 and 12 23.80 ch South of Sec. Cor
Set oak post 4x4 marked C.T. on North and South R 5 on East R 6 on West faces
From which a red fir 30 ins diameter bears North 33 links distant
A White oak 24." " " S. 72½ E. 42 " "
Thence West Var. 20½° E
80.25 Set post in line between sections 11 and 12 marked post C.T. 14.96 chains North of ¼ section corner
From last said post an oak 14 ins diam brs. S. 30½ E. 235 lks dist.
This post is on South slope of hill
Var. 21° E. Terminus of Survey

Recorded April 21, 1902

G. H. Waggoner
County Surveyor