County Surveyor's Record, Benton County, Oregon.

SURVEY No. ~~#~~ #68 MADE FOR William Huggins & Chris Tracer

39391 GLASS & PRUDHOMME, PRINTERS AND BOOKBINDERS, PORTLAND, OR.

1st Beginning at 1/4 sec. cor. bet secs 1 and 12 of Tp. 15 S R. 5 W.
40.00 Thence North 40.00 chs bet. Huggins & Tracer
Thence East
4.00 Slough 60 lks wide
6.00 County Road
20.00 West Boundary of A Howards land
Thence South 10.00 chs Howards S.W. corner
" East
9.00 Lemon's Slough
11.00 Over Slough
20.00 Huggins North South East Corner
" South North 10.00 chains 1/4 sec cor bet secs 1 and 6
Reestablished 1/4 sec cor bet. secs 1 and 6
D.H.W. B.T. Standing but burned and decaying
Set post from which a pine tree 30 ins diam marked C.S. 1/4 S. B.T. bears S 42 1/4 E 272 lks. distant.
Thence return South 10 chains set post for Willie Huggins
N.E. cor. 5 1/4 lks East of post previously set, this post marks true cor,
Thence South

Note
Changes in red ink have been found necessary to make notes consistent.
C.R. Beardsley
Examiner
Aug 9th, 1952

6.31 Right Bank of Lemons Slough
7.69 over the same
40.32 cor. of secs. 1, 6, 7 and 12
46.66 N.E. cor of James & P Crowe Donation Claim
North East B.T. Standing South West B T Stump
Set oak post for corner marked the same C.S.
19.97 Thence West 19.97 chains

2nd Begin again at cor to secs 1, 2, 11 and 12 (measured North 40.00
deposited stone 5 x 12 x 16 for 1/4 sec corner
Thence East 20.07 Deposited stone 7 x 8 x 12 for C Tracers N.W. cor.
from which an ash 14 ins. diam. bears S 80 3/4 W. 94 lks. dist.
" " " Oak 5 " " " S 1/4 E, 84 " "

3rd Begin again at cor of secs 1, 2, 11 & 12 Measured East 20.07 chs
Set Stone 3 x 5 x 12 for C Tracer's S W corner
From which an ash tree 12 ins in diam N 1/2 E 3 1/4 lks distant—
Begin again at cor of secs 1, 2, 11 & 12 Measured East 20.00
Deposited stone 4 x 8 x 16 for John Crows N.E. corner
Thence South 20.00 Set stone 4 x 7 x 16 ins John Crows S.E. Cor
40.36 East set stone 6 x 6 x 18 From which a chitim 5 ins brs S 86 W. 29 lks dist—
60.36 North 13.66 N.W. cor of James & P. Crowe D.L.C. Set stone 5 x 9 x 12 marked C.S.
North 6.34 set stone 4 x 7 x 14 for C. Tracers N.E. corner
Set stone 6 x 12 x 16 on centers of section 12. 40.14 1/2 South of 1/4 sec
cor bet secs 1 & 12 An Oak 16 ins diam brs S 1° W 388 lks distant
A pine 36 ins diam bears S 1/2 E 184 links distant—

Jan. 2nd, 1902. Assumed Date