County Surveyor's Record, Benton County, Oregon.

SURVEY No. 20 #83 MADE FOR Richard Scott

Oct 6th 1908.

Chs.

Beginning at the S.W. cor. of the Elizabeth Herbert D.L.C. #41 which I reestablished by driving down 1" iron rod and marking two trees,
An oak 12 in in diameter bears N 48-45 E 1.3' distant
" " 11 " " " " S 21-20 E 23.9' "
" " 14 " " " " S 85 W 30.9' "

I ran thence S 89-50 E by sun 1018.4' to the S.E. corner of same claim which I reestablished by setting a stone & stake & 18x10x9" from which
an oak 24" in diam. bears N 28° E 63.2'
" " 11" " " S-30' W 43.1'

I ran thence North to a point opposite the 1/4 Sec. cor. bet Secs 8 & 17 and corrected my line which correction is 18" to the West. & then came back to a point on this line which is 956.3' N. of said 1/4 Sec. corner and ~~ran thence East~~
Set an oak stake 4x4x30 mkd C.S. No 20 from which
an oak 20" in diameter bears N 2°-30' E 31.2'
" " 8" in " " S 45-40 E 7.8'

4.56' I ran thence East to center of ~~Longtom~~ creek (Muddy). width 30'
and at 274.1' Set stone 16x10x6 for Witness Corner on bank of Muddy from which
an oak 24" in diameter bears S 10°-30' E 12.1'
" " 11" " " " N 3°-45' W 10.1'

I then went to the N.E. Corner of the Wm Miller D.L.C. and ran
82.50' thence N 89° 47' W. to the N.W. " of above claim, I continued this line
1336.5' to the center of road and drove iron pipe (1½") for corner from which
a fir 12" in diameter bears S 12°-30' W. 149.0'
" " 8" " " N 21°-30' W. 79.1'

Thence N 1°-10' W
11.91' to the S. line of Herbert cl. Set 1½" angle iron for corner from which
an oak 9" in diameter bears S. 67°-40' E 8.2'
" " 10" " " " S 22°-30' W 20.2'
" " 30" " " " N 31°-30' W 26.6'

I then went to a point 27.7' N 89-47 W from the N.W. corner of the Miller D.L.C. and set a .22 caliber rifle barrel for corner from which
an oak 14" in diameter bears N 56-10 W 95'
" " 10" " " " S 76- W 79'

I ran thence N. to center of Muddy and at 1108.9' set W.C. which
17.67 is 42' from water edge on line, Set oak 2x4x30" from which
an oak 14" bears S 7°-15' E 13.5'
" " 16" " S 75-45 W 19.5'

Thence S 67°-50' W for location of Creek.
at 226.8' creek is 213.5' ± to line
at 500' " " 126' " " " average width 30'
at this point the land is rather a grass + bank on other side very little for 16 or
Field notes, went to a point 500' N of Herbert's S.E. Cor and thence
E 372.7. Creek is N 25°
+105.2' " " " 132'
+23.5 " " to Creek.
at 750' creek is E. 25½'

Magnetic Variation 21°-30' East.

Recorded Jan 21 1909
— by —
J. Marion Wilkins
County Surveyor.

FB #2, Pg. 7-9

7 Dick Scott Survey #20 Oct. 6, 08. #83

Survey No 20
Decs for Oct 6-8.

Beg at the N.E. Cor of Wm Mullen Dec, Reestab. cor. found oak Bt stump 24" dia. Set Stone for corner.

Thence N 87-45 W. at			
Set stake		1500	
Ver L 7-15 for		350.	
		1.70	
		5.20 =	515.8
Ver L 3-15 for Junk 5.2'		330.	329.3
L 6-15 "		570 350	497.00
Ver L 2-30 for Should be	5445.0	453.1	452.5'
Thence West to the The S.W. Cor of the Eliz Herbert D. Reestab cor. found 3 stumps. That fail conditions. Remarked trees.			
Junk oak 12" N 48-45 E		1.3'	
" 11" S-21-20 E		23.9'	
14" S 85 W.		30.9'	
thence E L 3-30		570'	= 499.0'
Post N 4' of	by Surv S 89-58 E. on this line 1800.		
Ver L 7-50		153'	151.5'
" " 6-30		570.	496.8'
Struck N 13.2'		4018.4' long	
4			
9.2' correction			

SURVEY NO. 20

5-3-55.6
9-48
5-13-43.6-W 1.29"
57.5
5-14-4 1.2-W 1.48"
E. Last 45°-35'-24"
5°-13-53.2
5°-13-19.6
SURVEY NO. 20
3.0
.7
4.2
5.20.
7.9
299
4680
4680
1000
515.8
329.3
497.00 00
5952.5
7.9
5960.4
5443.4
5415.4
586.6
5452.5
7.9
5444
401.8
453.9
10.2
1.68
11530
5765
5980.30
4809
4580
4950
4950
4950
5445.0 00
82.50
4392
1.68
1.92
1.92
1.92

8 Oct-7.

Thence N. Post 20' E.
set at 1000 - 15'
to Cent. sec. line. 956.34'.
Ojects W. 32' = 12ft W of line.
- 1500 - 40. Creek bank.
∠ Left 20" - 20'
" 20" 35' Line tree.
This line corrects N-16' W.
place cor at 956.34 + 24.8 W
Set stake 4x4x30" oak. mnks. + trees.
oak 20. N 25 30 E 31.2'
ash, 8" S 45-40 E 78'
Thence N 88-41 E, to W.C. 274.1'
Stone. 16 x 10" x 6"; for W.C.
pine oak, 24" = S 10-30 E 12.1'
" oak. N — N 3-45 W 10.1'
Width of Muddy, 30'. 12. to Creek.
Thence E 25.28'.
thence S. at 1000' Muddy is W 118'.
S. 1286 " 60.
1500' 20.8
Set stones 1142.2 West of Pt. Cor.
Set 1¼" pipe in Cen. of rd. (S.W. cor.)
Adm 12" S 12-30 W. 149'
" 8" N 21-30 W. 79.1
Line xs N-10' E on South to
Spears corner.

S.W.
N.W.
W.Cor.

4.0 2
6 5
2 5 3 2
2 8 3 2
3 1 1.5 - 2 2 2
2 3.9 2
3 1.7 9
1 3.7 6
8 2.7 4
8 2 0 8.5 4
1 1 0 4.9 0
5 4.4 9
oak 35' -
9 0
1 4.2 9
4 9.5 6
4 0
8 5 3.6
8 5 8.1
8 6 9 4
8 6 9 4 3 4
9 5 6.1
1 5.2 8
1 1.6 8.8
1 3.5 5
2 0
7.7 1 8.6
4 6.2 6
4 0 8
1 5 0 0
3 5 7.8
1 1 4 2.2
4 0 1.5
9 0 1.5
6 9 6.0
1 9 3.5
9 1.0
9 5 -
9 5 - 6.3 4
2 8.1 6 6
1 0 3.8 5
8 8.5.5 -
5 5.0 0
1 3 6
1 3.7 9
1 3.5 0
1 2 4
6 6 4
3 3 0
9 9 0
1 3 6 5.
2 2 0 0
2 7 3 0
3 0 0 3 0
4 4.4 4
9 5 6.3 1
4 2 5 0 0
4 7 8 1 7 0
1 9 1 2 6
3 8 2 5
5.1 1 2
5 8.4 7
8 8.3 4
2 8 1
9 0 1.5
9 0 1.5
2 0.0 0
4.7 2
1 5.2 8
1 0.
5.2 8
1 0.
1 5.2 8
9 1 6
9 1.2 8
1 0 0 4
to Water edg.

9 We ran thence N 1° W. 10'
K 2° 30'. 786.9'
set cor 4 S. N & line runs. Langlenn 11/2 11
a oak 7" S 67-40 E 8.2'
" " 10" S 77° 30 W 20.2'
" " 30" N 31-30 W 26'6
strikes 146.5 W of 1570 for
Herbert Cl.
Descrip of Herbert S.E. cor.
stone & stake 18 x 10 x 8"
an oak 24" N 28° E 63.2'
" " N. S.-30' W. 43.1'
Then [illegal] 1828.7 back pg.
for Burdens S.E. cor. set 2.2 Cal Sq Cor.
from ash 14" N 56-10 W 93.'
" 10" S 76- W 79.'
thence N. to W.C. 1108.9'
" water edge 42.'
" Width of Muddy 3 2 = 1166.9 to W
W.C. oak stake Mkd. 3 x 4 x 3"
oak 14" S-7-15 E 13.5
" 16" S 75-45 W. 19.5
thence N 67-30 W 8.1 Muddy 15.5' 2268 for location of creek
" N [illegal] 126. 500.
Next point back up B.T.
" N 67-30 W. 1063.9
" N-45' E 30'
cont Bk 4 Pg 2

[illegal] 750' N. of DLC. S.E. 25.2 to mid
E from 000-
372.7 Muddy N 25'
" 105.2 " " 132.
E " 73.5'
778.2' S. from DLC. th
N line of Muddy Cl
at DLC. SE cor.