

C.S. # 1276

Hardcopy 15-8#2

also see notes in file

F. B. 79-21

21 Reost County Survey 359

32 33 14 8 Set 5/8" x 24" bolt

5 4 15 8 Alder 8" S. 30° E. 0.60 Alder 177° E gone

Fir 14" S. 5° W. 580

127 6 Alder 14" S. 14° W. 1122

Fir 30" N 30° 30' W. 1.00 - 14° 15'

North by Needle
correction E. 1° 21'

1	L.R. 34'	-7° 35'	3.306	offset .032 E 545E
2		-10° 32'	5.451	171 E
3		-11° 30'	3.364	offset 244 E
4	L.R. 10 1/4'	-15° 17'	4.375	.091 E 356E
5		+15° 56'	5.944	175 350 E

Set screw in pitch stake L.R. 390

6		+7° 55'	4.783	.502 E
7		+31°	1.097	524 E
8		+28° 32'	5.126	.650 E
9		+18° 41'	.833	offset .649 E
10	L.R. 2° 14'		.799	.031 E offset 177E
11	X L.R. 42'	-26° 19'	6.334	.069 E .702 E offset
12	Reost L.R. 37° 57'	-0°	1.177	.724 E offset

1/4 sec. 33 32 Set 3/4" x 19" L. rod orig. cor.

Alder 12" S 18° E. 72 std.

Fir 24" N. 18° W. 184 face 197. cen. std.

May 7, 1936

For W.D. Risley

W.L. Buck

Harold McCormick

99125	98315	97992	
3306	5451	3364	
594750	98315		3277
297375	771575	391965	5359
297375	393260	587952	3296
	491575	293976	4219
327707250	535915065	293976	
989		329645088	16.151
29493			5716
26216	.96463	.02167	21867
29493	7375	422	4.765
29493	482315	4334	4.503
29493	675241	4334	.789
29493	289389	8668	5.678
29493	385852	.0914474	.928
29493	122025625	85717	40.269
29493	.99632	1097	
29493	4785	800018	
29493	797056	771493	
29493	697424	85717	
29493	398528	9403549	
29493	47653852	.03897	
29493	71135		
29493	.833	.031176	
29493	28419	5.678	
29493	28419	.0122276	
29493	75724	11356	
29493	7891009	11356	
29493	37057	11356	
29493	3433	5678	
29493	3024	.06938516	
29493	107		
534033 W		614976	
0820ts.		11770	
.032 E	40269	430177	
.491 E		450479	
.931 E		61497	
.069 E		61497	
.124 E		72381969	
.947 E			
		.02352	
		.94700	
		80538	
		141220	
		120807	
		208150	
		201345	
		67850	