

C.S. # 1299

Hardcopy 12-5 # 32

also see notes in file

F. B. 61-23

C. S. 75

S. line of Cate Tracts For Mrs. R.L. Gloss

22.86
36

From 3/4" pipe W. of Hwy. on N. line of Butterfield Cl.
B.S. on Pipe at E. of R.R. (front @ 10 N. of pipe
19' R. to E. + Measured S. 10
S. 4° 52' W.

W.H. Averill
J.D. Sprick

013716

2286

172

4572

22.859
5
0114275

016002

22.584

22.859

.025

8.000

8.000

6.859

+ .011

GN. 024

18.331 on S. line of Cate Tracts

18.355

18.331

.024

14.334 on S. line of 10' R.W.

West
Correction N. .02'

18.355 to 1/4" pipe of E. of R.R.

offsets

.422

& E. rail
(+.016 at 10'S)

10.354

.02806

4.2124

42832

20708

29053

324

20813

10.835

2905N.

28003.

.0105N.

10.835

4.960

15.795

4.960

20.759

18.952

1.409

10.350

4122

10.772

9.007

914

914

10.835

10.772

.063

R.R. N. 5° 54 1/2' E.

West

L.R. 1° 36 1/2'

Set 3/4" shaft.

10.354

offset
2905N.

+ .063

and S. 2855

20050 ± 2'

0105000

104063

9330

10.835

10.772

8.180

18.952

1.861

20.813

054

5

8.180

6

1.864.

-003

Striking N. of 1/4" pipe, W.C.

.280

Set a 3/4" pipe at lot cor.

.048 E. of W.C.

We set 3/4" pipe
Darnell's SW. cor.
E. 099

West
2339

Aug. 9, 1938

363

3/4" pipe

3.440

8.019

4.790

3.229

8.019

1.965

3.054

4.467

12

4.467

3/4" pipe

2239

1/4" pipe

3/4" pipe

23

8044

3/4" pipe

3/4" pipe in
1/4" pipe
E. of R.R.

10.637

1/4" pipe

E. of R.R.