

C.S. # 1393

See notes in file

F.B. 40-57

957

F/B 57, P. 57-58 1393 CS 1393.

County Survey 266  
T 10-3

Beg. at 1 1/4" pipe the N.E. corner of  
Sarah Atkins D.L.C. 45  
East

1		12.87	- 4.75	
	to a 1 1/4" iron rod (L.R. 5° 26'	9.743	) to iron iii.	
	From 1 1/4" iron rod 1287 E. of C. East	9.758	set on pipe	
3		2.729	set on iron	
4	-1° 12'	7.745		
5		1.631		
	Set a 1 1/4" pipe			
6	-15° 10'	8.45		
	Set a spike at water edge			
7	N. 8° 10' W.	1.399		
8	N. 24° 45' W.	3.2985		
9	N. 53° 03 1/2' W.	4.064		
10	N. 66° 40 1/2' W.	5.040		
11	N 84° 17 1/2' W.	3.803		
12	N. 73° 19' W	3.972		
13	N. 68° 02 1/2' W.	6.022		
14	S. 4° 45 1/2' W. + 8° 50'	1.929	offset 176 W.	
	to iron rod S. 0° 36' E.			

For C.G. Layton  
Adrian Scits chn.

7.064  
3,000  
4064

958  
Aug. 16, 1938

1 1/4" Iron Pin  
E 9.758

4" Cast Iron Pipe

9.758  
2.729  
7.743  
7743  
1.631  
9.374  
1.631  
8.16  
22.677  
.816  
21.861

73° 24' S. 78° 40 1/2' E to Δ 10 after change to  
73° 19'

1.898

1.906

4° 45 1/2'  
33  
5° 18 1/2'

957

F/B 57, Pg. 57-58 1393 CS 1393.

County Surrey 266  
T 10-3

Beg. at 1 1/4" pipe the N.E. corner of  
Sarah Atkins D.L.C. 45  
East

1		12.87	- 4.75
	to a 1 1/4" iron rod (L.R. 5°26'	9.743	) to iron li.
	From 1 1/4" iron rod 12.87 E. of C. East	9.758	set a pipe
3		2.729	set an iron
4	-1°12'	7.745	
5		1.631	
	Set a 1 1/4" pipe		
6	-15°10'	8.45	
	Set a spike at water edge		
7	N. 8°10' W.	1.399	
8	N. 24°45' W.	3.2985	
9	N. 53°03 1/2' W.	4.064	
10	N. 66°40 1/2' W.	5.040	
11	N 84°17 1/2' W.	3.803	
12	N. 73°19' W	3.972	
13	N. 68°02 1/2' W.	6.022	
14	S. 4°45 1/2' W. + 8°50'	1.929	offset .176 W.
	to iron rod S. 0°36' E.		

For C.G. Layton  
Adrian Scits chm.

7.064  
31000  
4064

958  
Aug. 16, 1938

1 1/4" Iron Pill  
E 9.758

4" Cast iron pipe.

9.758  
2.729  
7.743  
7743  
1.631  
9.374  
1.631  
.816  
22.677  
.816  
21.861

73° 24' S. 78° 40 1/2' Etc Δ 10 after change to  
73° 19'

1.898

1.906

4°45 1/2

33

5°18 1/2