

CS 4400
 Record of Survey
 for
KENNETH LEWIS
 in the
 Northeast Quarter of Section 16
 T.11S., R.6W. W.B. & M.
 Benton County, Oregon
 Scale: 1"=400' April 29, 1967

9-10

Parentheses indicate information from C.S. Records

Bearings from Solar observation

S.E. 1/4 Sec. 9

Fd. 4"x1" I. Bar - Fd sharpened oak post with S 15 S 16 S 9 S 10 scribed in post on ground nearby.
 Fd Oak 28" (10") N 31°E 6.95 ch - Checked dist. by pacing and bearing by compass only.
 Fd. Fir 43" S 41°W 36° with S. 16 B.F. marked in Bark - No previous record of this tree.
 Fence cor is 153 N and 4.9 E. of Bar.

(N 89°26'W 40.15 ch = 2649.9 - Orig. G.L.O. Notes)

N 89°45'E 2393.0

9
10
16
15
North
1961

Set 5/8"x30" re-bar
 Not necessarily on
 Section line.
 Fence is 8.0 E.

Fd. 5"x6"x12" Stone
 Fd Oak 15" (10") S 17°30'E 5.5
 Fd. Oak 30" (12") S 75°W 1.63 ch = 107.58
 Fd. remains of oak stump - Approx 24" down
 N 57°W 8816 = 58.08
 I chiseled X in stone and
 Set 1 1/2"x36" I. pipe 0.3 N. of
 X in stone.

N.E. Corner
 John Philips
 D.L.C. 60

REGISTERED
OREGON
 LAND SURVEYOR

Verle C. Moore

MAY 13, 1960
VERLE C. MOORE
 501